


POWER TRANSISTORS



TO-61

TYPE NO.	PT @ 25°C Watts	MAXIMUM RATINGS				h _{FE}		h _{FE} @		Sat Voltages		Test Conditions		I _{EB0} * ma
		BV _{CB0}	BV _{CE0}	BV _{EB0}	I _C	MIN	MAX	I _C	V _{CE}	V _{CE}	V _{BE}	I _C	I _B	
		V	V	V	A									
SPC153-04	200	65	40	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-06	200	85	60	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-08	200	105	80	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-10	200	125	100	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-12	200	145	120	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-14	200	165	140	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-16	200	185	160	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-18	200	205	180	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-20	200	225	200	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-22	200	245	220	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-24	200	265	240	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-26	200	285	260	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-28	200	305	280	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20
SPC153-30	200	325	300	25	7.5	15		1.5	4	1.3	2.5	1.5	.25	20

POWER TRANSISTORS



TO-61

TYPE NO.	PT @ 25°C Watts	MAXIMUM RATINGS				h _{FE}		h _{FE} @		Sat Voltages		Test Conditions		I _{EB0} * ma
		BV _{CB0}	BV _{CE0}	BV _{EB0}	I _C	MIN	MAX	I _C	V _{CE}	V _{CE}	V _{BE}	I _C	I _B	
		V	V	V	A									
SPC154-04	200	65	40	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-06	200	85	60	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-08	200	105	80	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-10	200	125	100	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-12	200	145	120	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-14	200	165	140	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-16	200	185	160	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-18	200	205	180	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-20	200	225	200	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-22	200	245	220	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-24	200	265	240	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-26	200	285	260	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-28	200	305	280	25	7.5	25		1.5	4	1.25	2	1.5	.25	20
SPC154-30	200	325	300	25	7.5	25		1.5	4	1.25	2	1.5	.25	20

*T_c = 175°C

