


# SILICON TRANSISTOR 2SC3618

# NPN SILICON EPITAXIAL TRANSISTOR POWER MINI MOLD

#### **DESCRIPTION**

2SC3618 is designed for audio frequency power amplifier and switching application, especially in Hybrid Integrated Circuits.



#### **FEATURE**

• High DC Current Gain hFE = 800 to 3200

#### ABSOLUTE MAXIMUM RATINGS $(T_A = 25 \degree C)$

so 25 \	/
o 25 \	/
o 15 \	/
oc) 0.7 A	4
ulse) 1.0 A	4
2.0 V	٧
150 °(	2
−55 to +150 °C	)
	25 No. 25

<sup>\*</sup>PW  $\leq$  10 ms, Duty Cycle  $\leq$  50 %

### ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C)

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Collector Cutoff Current	ІСВО			100	nA	V <sub>CB</sub> = 25 V, I <sub>E</sub> = 0
Emitter Cutoff Current	IEBO			100	nA	V <sub>EB</sub> = 10 V, I <sub>C</sub> = 0
DC Current Gain	hFE1 ***	800		3200		V <sub>CE</sub> = 2.0 V, I <sub>C</sub> = 300 mA
DC Current Gain	hFE2 ***	640				V <sub>CE</sub> = 2.0 V, I <sub>C</sub> = 500 mA
Collector Saturation Voltage	V <sub>CE(sat)</sub> ***		0.16	0.3	V	I <sub>C</sub> = 300 mA, I <sub>B</sub> = 3.0 mA
Base Saturation Voltage	VBE(sat) ***		0.75	1.2	V	IC = 300 mA, IB = 3.0 mA
Gain Bandwidth Product	fT	150	250		MHz	V <sub>CE</sub> = 5.0 V, I <sub>E</sub> = -300 mA
Output Capacitance	Cob		10		pF	V <sub>CB</sub> = 10 V, I <sub>E</sub> = 0, f = 1.0 MHz
Turn-on Time	ton ·	-	0.13		μs	Vcc = 10 V, V <sub>BE(off)</sub> ≒ -2.7 V
Turn-off Time	toff		1.1		μ <b>s</b>	Ic = 200 mA, I <sub>B1</sub> = -I <sub>B2</sub> = 4 mA

<sup>\*\*\*</sup>Pulsed: PW  $\leq$  350  $\mu$ s, Duty Cycle  $\leq$  2 %


#### h<sub>FE</sub> Classification


MARKING	· UM	UL	UK
hFE1	800 to 1600	1200 to 2400	2000 to 3200


The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version. Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.


<sup>\*\*</sup>When mounted on ceramic substrate of 16 cm<sup>2</sup> x 0.7 mm


## TYPICAL CHARACTERISTICS (TA = 25°C)











3

Data Sheet D17971EJ3V0DS

- The information in this document is current as of March, 2006. The information is subject to change
  without notice. For actual design-in, refer to the latest publications of NEC Electronics data sheets or
  data books, etc., for the most up-to-date specifications of NEC Electronics products. Not all
  products and/or types are available in every country. Please check with an NEC Electronics sales
  representative for availability and additional information.
- No part of this document may be copied or reproduced in any form or by any means without the prior
  written consent of NEC Electronics. NEC Electronics assumes no responsibility for any errors that may
  appear in this document.
- NEC Electronics does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC Electronics products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Electronics or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative
  purposes in semiconductor product operation and application examples. The incorporation of these
  circuits, software and information in the design of a customer's equipment shall be done under the full
  responsibility of the customer. NEC Electronics assumes no responsibility for any losses incurred by
  customers or third parties arising from the use of these circuits, software and information.
- While NEC Electronics endeavors to enhance the quality, reliability and safety of NEC Electronics products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC Electronics products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment and anti-failure features.
- NEC Electronics products are classified into the following three quality grades: "Standard", "Special" and "Specific".
  - The "Specific" quality grade applies only to NEC Electronics products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of an NEC Electronics product depend on its quality grade, as indicated below. Customers must check the quality grade of each NEC Electronics product before using it in a particular application.
  - "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots.
  - "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support).
  - "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.

The quality grade of NEC Electronics products is "Standard" unless otherwise expressly specified in NEC Electronics data sheets or data books, etc. If customers wish to use NEC Electronics products in applications not intended by NEC Electronics, they must contact an NEC Electronics sales representative in advance to determine NEC Electronics' willingness to support a given application.

#### (Note)

- (1) "NEC Electronics" as used in this statement means NEC Electronics Corporation and also includes its majority-owned subsidiaries.
- (2) "NEC Electronics products" means any product developed or manufactured by or for NEC Electronics (as defined above).