



Use JS-V-2510HP-T Terminal

Dimensions in mm				
Pos.	A +/- .008, 0.20		B +/- .008 0.20	
1			0.120	3.06
2	0.100	2.54	0.220	5.60
3	0.200	5.08	0.320	8.14
4	0.300	7.62	0.420	10.68
5	0.400	10.16	0.520	13.22
6	0.500	12.70	0.620	15.76
7	0.600	15.24	0.720	18.30
8	0.700	17.78	0.820	20.84
9	0.800	20.32	0.920	23.38
10	0.900	22.86	1.020	25.92
11	1.000	25.40	1.120	28.46
12	1.100	27.94	1.220	31.00
13	1.200	30.48	1.320	33.54
14	1.300	33.02	1.420	36.08
15	1.400	35.56	1.520	38.62
16	1.500	38.10	1.620	41.16
17	1.600	40.64	1.720	43.70
18	1.700	43.18	1.820	46.24
19	1.800	45.72	1.920	48.78
20	1.900	48.26	2.020	51.32
21	2.000	50.80	2.120	53.86
22	2.100	53.34	2.220	56.40
23	2.200	55.88	2.320	58.94
24	2.300	58.42	2.420	61.48
25	2.400	60.96	2.520	64.02

SPECIFICATIONS

Mates with .025" [0.64mm] pins
 Terminal retention to housing 6.6lbs [3.0Kg min.
 Accepts double cantilever crimp terminal [2510HP-T]
 Terminal retention to housing 6.6lbs [3.0Kg] minimum

Current Rating: 3A AC, DC
 Voltage Rating: 250V AC max.
 Contact Resistance: 10mΩ max.
 Material: Nylon, UL94V-0
 Insulation Resistance: 1000 MΩ min
 Withstanding: 1500V AC/min
 Temperature range: -40°C ~ +100°C

RoHS compliant

Series	Type	Positions	Options
JS-V	2510HP	XX	XX
Pluggable Connector	Center Crimp Terminal Housing	02 ~ 25	NR=No Rib NPR=No Rib on Ramp

Rev.	Description	Date	Approved	Drawing	Name	Date
A	Spec, PNT	6/01/09	Greg	Approved	Howard	09/27/07
				Checked	Lizzy	09/27/07
				Drawn	Tina	09/27/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-V-2510HP-XX-XX**

Description: .100" (2/54mm) Center Crimp Terminal Housing