



SPECIFICATIONS

Current rating: 1 amp
 Contact material: Phosphor bronze
 Contact resistance: 30 milliohms max.
 Insulator material: PBT, glass reinforced, UL94V-0, black
 Insulation resistance: 3,000 megohms min.
 Withstanding: 500VAC for 1 min.
 Wire: 1.00mm pitch flat ribbon cable
 Operating temperature: -40°C to +105°C

Pos.	A	B	C
6	6.4	4.0	11.17
8	8.4	6.0	13.17
10	10.4	8.0	15.17
12	12.4	10.0	17.17
14	14.4	12.0	19.17
16	16.4	14.0	21.17
20	20.4	18.0	25.17
22	22.4	20.0	27.17
24	24.4	22.0	29.17
26	26.4	24.0	31.17
30	30.4	28.0	35.17
34	34.4	32.0	39.17
40	40.4	38.0	45.17
44	44.4	42.0	49.17
50	50.4	48.0	55.17
68	68.4	66.0	73.17

Series	Type	Positions	Polarization	Plating
BFC	A	XX	XX	XX
2mm flat cable socket	A=Slim profile	08-68 (see chart)	P=Polarized NP=No polarization	TN=Tin SGXX=Selective gold GDXX=Gold XX=Flash if blank; 05, 10, 15, 30µ" gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BFC-A-XX-XX-XX**

Description: Slim profile IDC socket