



SPECIFICATIONS
Voltage rating: 125VAC/VDC
Current rating: 1 amp, AC/DC
Withstanding voltage: 250VAC for 1 min.
Insulation resistance: 100 megohms min.
Temperature range: -40°C~+85°C
Contact resistance: 20mΩ max

WAFER
Part no.: JS-1147V-XX
Poles: 2-15
Material: Contact: Brass, tin plated
Base: PA46 UL94V-0
Quantity: 1,000pcs/tape & reel

Dimensions				
Pos.	A	B	C	D
2	1.25	4.25	3.05	7.65
3	2.50	5.50	4.30	8.90
4	3.75	6.75	5.55	10.15
5	5.00	8.00	6.80	11.40
6	6.25	9.25	8.05	12.65
7	7.50	10.50	9.30	13.90
8	8.75	11.75	10.55	15.15
9	10.00	13.00	11.80	16.40
10	11.25	14.25	13.05	17.65
11	12.50	15.50	14.30	18.90
12	13.75	16.75	15.55	20.15
13	15.00	18.00	16.80	21.40
14	16.25	19.25	18.05	22.65
15	17.50	20.50	19.30	23.90

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/19/06
				Checked	Lizzy	06/19/06
				Drawn	Tina	06/19/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-1147V-XX**
Description: Disconnectable crimp style wafer, 1.25mm pitch