

15.0 KiloWatt TRANSIENT VOLTAGE SUPPRESSORS - UNIPOLAR

15 KW ISI PART NUMBER	REVERSE STAND- OFF VOLTAGE V _r (Volts)	BREAKDOWN VOLTAGE			MAXIMUM CLAMPING VOLTAGE @ IPP & 1 msec V _c (Volts)	MAXIMUM REVERSE LEAKAGE @ V _r I _r (µA)	MAXIMUM PEAK PULSE CURRENT I _p (Amps)	MAXIMUM VOLTAGE TEMPERATURE VARIATION of V _r (mV/°C)	OUTLINE Inches/Millimeters
		Min V _{BR} (Volts)	Max V _{BR} (Volts)	@ I _r mA					
15KP17	17	18.9	23.1	50	32.3	5000	464	19	<p>All Dimensions in $\frac{\text{inches}}{\text{millimeters}}$</p>
15KP17A	17	18.9	20.9	50	29.3	5000	512	17	
15KP18	18	20.0	24.4	50	34.2	5000	439	20	
15KP18A	18	20.0	22.1	50	30.9	5000	485	18	
15KP20	20	22.2	27.1	20	37.9	1500	396	24	
15KP20A	20	22.2	24.5	20	34.3	1500	437	21	
15KP22	22	24.4	29.8	10	41.1	500	365	27	
15KP22A	22	24.4	26.9	10	37.1	500	404	24	
15KP24	24	26.7	32.6	5	45.0	150	333	30	
15KP24A	24	26.7	29.5	5	40.7	150	369	27	
15KP26	26	28.9	35.3	5	48.7	50	308	32	
15KP26A	26	28.9	31.9	5	44.0	50	341	29	
15KP28	28	31.1	38.0	5	52.4	25	286	35	
15KP28A	28	31.1	34.4	5	47.5	25	316	31	
15KP30	30	33.3	40.7	5	56.2	15	267	27	
15KP30A	30	33.3	36.8	5	50.7	15	296	34	
15KP33	33	36.7	44.9	5	60.6	10	248	42	
15KP33A	33	36.7	40.6	5	54.8	10	274	38	
15KP36	36	40.0	48.9	5	66.0	10	227	46	
15KP36A	36	40.0	44.2	5	59.7	10	251	41	
15KP40	40	44.4	54.3	5	72.8	10	206	51	
15KP40A	40	44.4	49.1	5	65.8	10	228	46	
15KP43	43	47.8	58.4	5	77.1	10	195	55	
15KP43A	43	47.8	52.8	5	69.7	10	215	50	
15KP45	45	50.0	61.1	5	80.7	10	186	57	
15KP45A	45	50.0	55.3	5	73.0	10	205	52	
15KP48	48	53.3	65.1	5	85.9	10	175	62	
15KP48A	48	53.3	58.9	5	77.7	10	193	56	
15KP51	51	56.7	69.3	5	91.5	10	164	66	
15KP51A	51	56.7	62.7	5	82.8	10	181	60	
15KP54	54	60.0	73.3	5	96.8	10	155	70	
15KP54A	54	60.0	66.3	5	87.5	10	171	63	
15KP58	58	64.4	71.7	5	104.0	10	144	76	
15KP58A	58	64.4	71.2	5	94.0	10	160	68	
15KP60	60	66.7	81.5	5	107.0	10	140	78	
15KP60A	60	66.7	73.7	5	97.3	10	154	71	
15KP64	64	71.1	86.9	5	115	10	130	84	
15KP64A	64	71.1	78.6	5	104	10	144	76	
15KP70	70	77.8	95.1	5	126	10	119	92	
15KP70A	70	77.8	86.0	5	114	10	132	83	
15KP75	75	83.3	102.0	5	135	10	111	100	
15KP75A	75	83.3	92.1	5	122	10	123	89	
15KP78	78	86.7	106.0	5	140	10	107	104	
15KP78A	78	86.7	95.8	5	126	10	119	93	
15KP85	85	94.4	115	5	152	10	99	113	
15KP85A	85	94.4	104	5	137	10	109	102	
15KP90	90	100	122	5	160	10	94	120	
15KP90A	90	100	111	5	146	10	103	109	
15KP100	100	111	136	5	179	10	84	134	
15KP100A	100	111	123	5	162	10	93	121	
15KP110	110	122	149	5	196	10	77	147	
15KP110A	110	122	135	5	178	10	84	133	
15KP120	120	133	163	5	214	10	70	161	
15KP120A	120	133	147	5	193	10	78	145	
15KP130	130	144	176	5	231	10	65	174	
15KP130A	130	144	159	5	209	10	72	157	
15KP150	150	167	204	5	268	10	56	202	
15KP150A	150	167	185	5	243	10	62	183	
15KP160	160	178	218	5	287	10	52	216	
15KP160A	160	178	197	5	159	10	58	195	
15KP170	170	189	231	5	304	10	49	229	
15KP170A	170	189	209	5	275	10	55	207	
15KP180	180	200	244	5	321	10	47	242	
15KP180A	180	200	221	5	291	10	52	219	
15KP200	200	222	271	5	356	10	42	269	
15KP200A	200	222	245	5	322	10	47	243	
15KP220	220	245	299	5	393	10	38	297	
15KP220A	220	245	271	5	356	10	42	269	
15KP240	240	267	326	5	428	10	35	324	
15KP240A	240	267	295	5	388	10	39	293	
15KP260	260	289	353	5	464	10	32	352	
15KP260A	260	289	319	5	419	10	36	317	
15KP280	280	311	380	5	500	10	30	378	
15KP280A	280	311	344	5	452	10	33	342	