



**SPECIFICATIONS**

Voltage Rating: AC 250V  
 Current Rating: AC,DC,2A  
 Contact Resistance: Initial value /10 mΩ max  
 After environmental testing / 20 mΩ max.  
 Material: Nylon 66, UL94V-0  
 Insulation resistance: 1000MΩ min.  
 PC Board Thickness: 0.8~1.6mm  
 Poles: 2-12, and 18  
 Withstanding: AC 800 V/min.  
 Temperature Range: -25°C ~ +85°C

Dimensions (mm)		
Poles	A	B
2	2.5	5.5
3	5.0	8.0
4	0.295	0.402
5	0.394	0.512
6	0.492	0.610
7	0.591	0.709
8	0.689	0.807
9	0.787	0.906
10	0.886	1.004
11	0.984	1.102
12	1.083	1.201
18	1.673	1.791

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	09/04/08
				Checked	Lizzy	09/04/08
				Drawn	Tina	09/04/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **2602-H-XX**

Description: Pitch 2.5mm Housing

