




- 1 THE NOTED DIMENSION APPLIES AT THE INTERSECTION OF THE POST AND HOUSING
- 2 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 3 SELECTIVE POSTS ARE FORMED TO PROVIDE CONNECTOR RETENTION TO PC BOARD UNTIL SOLDERED. RETENTION FEATURE IS FOR .055 MINIMUM PC BOARD THICKNESS SEE DETAIL Z FOR FORM AND TABLE FOR LOCATIONS.
- 4 BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- 5 FINISH: POSTS, .000015 GOLD ON THE CONTACT AREA, .000100-.000200 MATTE TIN-LEAD ON THE SOLDER TAIL, ALL OVER .000050 NICKEL
- 6 FINISH: POSTS, .000015 GOLD ON THE CONTACT AREA, .000100-.000200 MATTE TIN ON THE SOLDER TAIL, ALL OVER .000050 NICKEL
- 7 HIGH TEMPERATURE CONFIGURATION



PLATING	HOLD-DOWN POST CONFIGURATION LOCATION	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER
6	1,2,3,4,37,38,39,40	3.984	3.900	39	40	7-104348-7
6	1,2,3,4,32,33,34,35	3.484	3.400	34	35	7-104348-6
6	1,2,3,4,27,28,29,30	2.984	2.900	29	30	7-104348-5
6	1,2,3,4,23,24,25,26	2.584	2.500	25	26	7-104348-4
6	1,2,3,4,22,23,24,25	2.484	2.400	24	25	7-104348-3
6	1,2,3,4,21,22,23,24	2.384	2.300	23	24	7-104348-2
6	1,2,3,4,20,21,22,23	2.284	2.200	22	23	7-104348-1
6	1,2,3,4,19,20,21,22	2.184	2.100	21	22	6-104348-0
6	1,2,3,4,18,19,20,21	2.084	2.000	20	21	6-104348-9
6	1,2,3,4,17,18,19,20	1.984	1.900	19	20	6-104348-8
6	1,2,3,4,16,17,18,19	1.884	1.800	18	19	6-104348-7
6	1,2,3,4,15,16,17,18	1.784	1.700	17	18	6-104348-6
6	1,2,3,4,14,15,16,17	1.684	1.600	16	17	6-104348-5
6	1,2,3,4,13,14,15,16	1.584	1.500	15	16	6-104348-4
6	1,2,3,4,12,13,14,15	1.484	1.400	14	15	6-104348-3
6	1,2,3,4,11,12,13,14	1.384	1.300	13	14	6-104348-2
6	1,2,3,4,10,11,12,13	1.284	1.200	12	13	6-104348-1
6	1,2,3,4,9,10,11,12	1.184	1.100	11	12	6-104348-0
6	1,2,3,4,8,9,10,11	1.084	1.000	10	11	5-104348-9
6	1,2,3,4,7,8,9,10	.984	.900	9	10	5-104348-8
6	1,2,3,4,6,7,8,9	.884	.800	8	9	5-104348-7
6	ALL	.784	.700	7	8	5-104348-6
6	ALL	.684	.600	6	7	5-104348-5
6	ALL	.584	.500	5	6	5-104348-4
6	ALL	.484	.400	4	5	5-104348-3
6	ALL	.384	.300	3	4	5-104348-2
6	ALL	.284	.200	2	3	5-104348-1
5	1,2,3,4,37,38,39,40	3.984	3.900	39	40	2-104348-7
5	1,2,3,4,32,33,34,35	3.484	3.400	34	35	2-104348-6
5	1,2,3,4,27,28,29,30	2.984	2.900	29	30	2-104348-5
5	1,2,3,4,23,24,25,26	2.584	2.500	25	26	2-104348-4
5	1,2,3,4,22,23,24,25	2.484	2.400	24	25	2-104348-3
5	1,2,3,4,21,22,23,24	2.384	2.300	23	24	2-104348-2
5	1,2,3,4,20,21,22,23	2.284	2.200	22	23	2-104348-1
5	1,2,3,4,19,20,21,22	2.184	2.100	21	22	2-104348-0
5	1,2,3,4,18,19,20,21	2.084	2.000	20	21	1-104348-9
5	1,2,3,4,17,18,19,20	1.984	1.900	19	20	1-104348-8
5	1,2,3,4,16,17,18,19	1.884	1.800	18	19	1-104348-7
5	1,2,3,4,15,16,17,18	1.784	1.700	17	18	1-104348-6
5	1,2,3,4,14,15,16,17	1.684	1.600	16	17	1-104348-5
5	1,2,3,4,13,14,15,16	1.584	1.500	15	16	1-104348-4
5	1,2,3,4,12,13,14,15	1.484	1.400	14	15	1-104348-3
5	1,2,3,4,11,12,13,14	1.384	1.300	13	14	1-104348-2
5	1,2,3,4,10,11,12,13	1.284	1.200	12	13	1-104348-1
5	1,2,3,4,9,10,11,12	1.184	1.100	11	12	1-104348-0
5	1,2,3,4,8,9,10,11	1.084	1.000	10	11	104348-9
5	1,2,3,4,7,8,9,10	.984	.900	9	10	104348-8
5	1,2,3,4,6,7,8,9	.884	.800	8	9	104348-7
5	ALL	.784	.700	7	8	104348-6
5	ALL	.684	.600	6	7	104348-5
5	ALL	.584	.500	5	6	104348-4
5	ALL	.484	.400	4	5	104348-3
5	ALL	.384	.300	3	4	104348-2
5	ALL	.284	.200	2	3	104348-1

THIS DRAWING IS A CONTROLLED DOCUMENT. DWG NO: M PASTAL 04FEB88  
 CHK: R FEIDT 09FEB88  
 APPO: R FEIDT 09FEB88  
 PRODUCT SPEC: ---  
 APPLICATION SPEC: ---  
 MATERIAL: FLAME RETARDANT THERMOPLASTIC, COLOUR BLACK, POSTS: PHOS BRONZE  
 FINISH: SEE TABLE  
 WEIGHT: ---  
 CUSTOMER DRAWING: ---  
 Tyco Electronics Corporation, Harrisburg, Pa 17105-3608  
 NAME: HEADER ASSY, MOD II, BREAKAWAY, RIGHT ANGLE, SINGLE ROW, .100 C/L, .025 SQ POSTS, W/HOLD-DOWN CONFIG  
 SIZE: A1  
 CAGE CODE: 00779  
 DRAWING NO: 104348  
 SCALE: 4:1  
 SHEET: 1 OF 1  
 REV: E