


PC/104 Connectors

2.54mm Pitch Vertical Bus Connectors

- 32+32 contacts supports an 8-bit system.
- 20+20 contacts combined with 32+32 contacts supports a 16-bit system.
- Press-fit connectors can be assembled direct to the PCB without soldering, using plated-through holes.
- Stackthrough connectors act as both male and female connectors.



PC/104, PC/104 PLUS

SOLDER TAIL		CALCULATION		PRESS-FIT TAIL		CALCULATION	
		A	$B + 3.2$			A	$B + 3.56$
		B	$2.54 \times (\text{No. of contacts per row} - 1)$			B	$2.54 \times (\text{No. of contacts per row} - 1)$
<p>Recommended PC Board Pattern</p>						<p>Press-Fit connector M20-615 supplied with spacer moulding</p> <p>Recommended PC Board Pattern</p>	

HOW TO ORDER

M20 - 61 X XX XX

SERIES CODE

TYPE	
0	Stackthrough, 12.20mm Solder Tail
1	Non-Stackthrough, 2.30mm Solder Tail
5	Stackthrough, 12.10mm Press-Fit Tail
6	Non-Stackthrough, 3.40mm Press-Fit Tail

FINISH

05	Gold (M20-615, 616)
45	Gold (M20-610, 611)

NO. OF CONTACTS PER ROW

20, 32

All dimensions in mm.