



Recommended PCB Layout
(Top View)

Part Number	Contact Area Plating Finish
K22XHT-A15P-N	Gold Flash (Standard)
K22XHT-A15P-N15	15u" Gold (15 Option)
K22XHT-A15P-N30	30u" Gold (30 Option)

Material and Finish

Insulator: High Temperature Thermoplastic with Glass-fiber Reinforcement, UL 94V-0 Rated, Color: Black

Shell: Steel, Nickel Plated

Contact Material:
Plug - Brass

Contact Plating Options:
Standard: Gold Flash on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

15 Option: 15u" Gold on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

30 Option: 30u" Gold on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

Electrical Specifications

Rated Current: 2A
Rated Voltage: 30V RMS
Insulation Resistance: 1000 Megohms Min. at 500V DC
Contact Resistance: 13 milliohms Max.
Dielectric Withstanding Voltage: 1000V for 1 Minute

Mechanical Specifications

Operating Temperature: -55°C to +105°C



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	04/29/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	4/29/05
A2	10/17/05	ECO #05-056	R. Aguirre	H. MA		
A3	02/21/08	ECO #07-049	S. Vien	H. MA		
A4	07/30/13	ECO #12-018	S. Vien	P. DalCanto		

K22XHT-A15P-Nxx

Right Angle D-Sub, Male, RoHS Compliant

0.318" Footprint, With Boardlocks

