



Restricted part. Only available on cables.

Pins	Dimensions	
	A	B
10	11.45	5.08
14	13.99	7.62
16	15.26	8.89
20	17.80	11.43
26	21.61	15.24
30	24.15	17.78
34	26.69	20.32
40	30.50	24.15
50	36.85	30.48
60	43.20	36.83
68	48.28	41.91
70	49.55	43.18
80	55.90	49.53
90	62.25	55.88
100	68.60	62.23

SPECIFICATIONS

- Current rating: 1 amp
- Contact material: Phosphor bronze
- Insulator material: PBT, glass reinforced, UL94V-0
- Withstanding: 250VAC for 1 min.
- Contact resistance: 30 milliohms max.
- Insul. resistance: 1,000 megohms min.
- Operating temp.: -40°C to +105°C
- Terminates with: 0.635mm pitch flat ribbon cable

Series	Contacts	Plating	Polarity
CFCA-LPHD	XX	XX	XX
1.27mm pitch IDC socket, low profile, high density	10, 14, 16, 20, 26, 30, 34, 40, 50, 60, 68, 70, 80, 90, 100	TN=Tin; SG=Selective gold; GD=Gold flash; GD05=5µ" gold plate; GD10=10µ" gold plate; GD15=15µ" gold plate; GD30=30µ" gold plate	P=With polarity NP=No polarity

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	8/10/99
				Checked	Lizzy	8/10/99
				Drawn	Tina	8/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CFCA-LPHD-XX-XX-XX**

Description: 1.27mm pitch IDC socket, low profile, high density