


2SC4876 (TP30S4)

30A NPN

OUTLINE DIMENSIONS



RATINGS

● Absolute Maximum Ratings


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T_{stg}		-55~150	°C
Junction Temperature	T_j		150	°C
Collector to Base Voltage	V_{CBO}		60	V
Collector to Emitter Voltage	V_{CEO}		40	V
Emitter to Base Voltage	V_{EBO}		7	V
Collector Current DC	I_C		30	A
Collector Current Peak	I_{CP}		60	A
Base Current DC	I_B		4	A
Base Current Peak	I_{BP}		6	A
Total Transistor Dissipation	P_T	$T_c = 25^\circ\text{C}$	45	W
Dielectric Strength	V_{dis}	Terminal to case, AC 1 minute	2	kV
Mounting Torque	TOR	(Recommended torque : 0.3N·m)	0.5	N·m

● Electrical Characteristics ($T_c=25^\circ\text{C}$)

Item	Symbol	Conditions	Ratings	Unit
Collector to Emitter Sustaining Voltage	$V_{CEO(sus)}$	$I_C = 0.1A$	Min 40	V
Collector Cutoff Current	I_{CBO}	At rated Voltage	Max 0.1	mA
	I_{CEO}		Max 0.1	
Emitter Cutoff Current	I_{EBO}	At rated Voltage	Max 0.1	mA
DC Current Gain	h_{FE}	$V_{CE} = 2V, I_C = 15A$	Min 100	
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 15A$	Max 0.3	V
Base to Emitter Saturation Voltage	$V_{BE(sat)}$	$I_B = 0.75A$	Max 1.2	V
Thermal Resistance	θ_{jc}	Junction to case	Max 2.78	°C/W
Transition Frequency	f_T	$V_{CE} = 10V, I_C = 3A$	TYP 50	MHz
Turn on Time	t_{on}	$I_C = 15A$ $I_{B1} = 1.5A, I_{B2} = 1.5A$ $R_L = 2\Omega, V_{BB2} = 4V$	Max 0.3	μs
Storage Time	t_s		Max 1.5	
Fall Time	t_f		Max 0.5	


2SC4876

$h_{FE} - I_C$




2SC4876

Switching Time - I_C




2SC4876

Switching Time - Tc




2SC4876 Transient Thermal Impedance




2SC4876

Forward Bias SOA



2SC4876 Collector Current Derating



2SC4876

Reverse Bias SOA

