


# DM74LS13

## Dual 4-Input Schmitt Trigger

### General Description

This device contains two independent gates each of which perform the logic NAND function. Each input has hysteresis which increases the noise immunity and transforms a slowly changing input signal to a fast changing jitter free output.

### Connection Diagram



**Order Number DM74LS13M or DM74LS13N**  
**See NS Package Number M14A or N14A**

### Function Table

$$Y = \overline{ABCD}$$

| Inputs |   |   |   | Output |
|--------|---|---|---|--------|
| A      | B | C | D | Y      |
| X      | X | X | L | H      |
| X      | X | L | X | H      |
| X      | L | X | X | H      |
| L      | X | X | X | H      |
| H      | H | H | H | L      |

H = High Level Logic

L = Low Level Logic

X = Either Low or High Level Logic

## Absolute Maximum Ratings (Note)

|  |                 |
|--|-----------------|
| Supply Voltage                                 | 7V              |
| Input Voltage                                  | 7V              |
| Operating Free Air Temperature Range<br>DM74LS | 0°C to +70°C    |
| Storage Temperature Range                      | -65°C to +150°C |

Note: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the "Electrical Characteristics" table are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

## Recommended Operating Conditions

| Symbol          | Parameter                      | DM74LS13 |     |      | Units |
|-----------------|--------------------------------|----------|-----|------|-------|
|                 |                                | Min      | Nom | Max  |       |
| V <sub>CC</sub> | Supply Voltage                 | 4.75     | 5   | 5.25 | V     |
| V <sub>IH</sub> | High Level Input Voltage       | 2        |     |      | V     |
| V <sub>IL</sub> | Low Level Input Voltage        |          |     | 0.8  | V     |
| I <sub>OH</sub> | High Level Output Current      |          |     | -0.4 | mA    |
| I <sub>OL</sub> | Low Level Output Current       |          |     | 8    | mA    |
| T <sub>A</sub>  | Free Air Operating Temperature | 0        |     | 70   | °C    |

## Electrical Characteristics over recommended operating free air temperature range (unless otherwise noted)

| Symbol                            | Parameter                                 | Conditions   | Min | Typ<br>(Note 1) | Max  | Units |
|-----------------------------------|---|--|-----|-----------------|------|-------|
| V <sub>I</sub>                    | Input Clamp Voltage                       | V <sub>CC</sub> = Min, I <sub>I</sub> = -18 mA                         |     |                 | -1.5 | V     |
| V <sub>OH</sub>                   | High Level Output Voltage                 | V <sub>CC</sub> = Min, I <sub>OH</sub> = Max,<br>V <sub>IL</sub> = Max | 2.7 |                 |      | V     |
| V <sub>OL</sub>                   | Low Level Output Voltage                  | V <sub>CC</sub> = Min, I <sub>OL</sub> = Max,<br>V <sub>IH</sub> = Min |     |                 | 0.5  | V     |
|                                   |   | I <sub>OL</sub> = 4 mA, V <sub>CC</sub> = Min                          |     |                 | 0.4  |       |
| I <sub>I</sub>                    | Input Current @ Max Input Voltage         | V <sub>CC</sub> = Max, V <sub>I</sub> = 7V                             |     |                 | 0.1  | mA    |
| I <sub>IH</sub>                   | High Level Input Current                  | V <sub>CC</sub> = Max, V <sub>I</sub> = 2.7V                           |     |                 | 20   | μA    |
| I <sub>IL</sub>                   | Low Level Input Current                   | V <sub>CC</sub> = Max, V <sub>I</sub> = 0.4V                           |     |                 | -0.4 | mA    |
| I <sub>OS</sub>                   | Short Circuit Output Current              | V <sub>CC</sub> = Max<br>(Note 2)                                      | -20 |                 | -100 | mA    |
| I <sub>CCH</sub>                  | Supply Current with Outputs High          | V <sub>CC</sub> = Max<br>V <sub>IN</sub> = GND                         |     |                 | 6.0  | mA    |
| I <sub>CCL</sub>                  | Supply Current with Outputs Low           | V <sub>CC</sub> = Max<br>V <sub>IN</sub> = OPEN                        |     |                 | 7.0  | mA    |
| V <sub>T+</sub>                   | Positive-Going Threshold Voltage          | V <sub>CC</sub> = +5.0V  | 1.5 |                 | 2.0  | V     |
| V <sub>T-</sub>                   | Negative-Going Threshold Voltage          | V <sub>CC</sub> = +5.0V  | 0.6 |                 | 1.1  | V     |
| V <sub>T+</sub> - V <sub>T-</sub> | Hysteresis Voltage                        | V <sub>CC</sub> = +5.0V  | 0.4 |                 |      | V     |
| I <sub>T+</sub>                   | Input Current at Positive-Going Threshold | V <sub>CC</sub> = +5.0V, V <sub>IN</sub> = V <sub>T+</sub>             |     | -0.14*          |      | mA    |
| I <sub>T-</sub>                   | Input Current at Negative-Going Threshold | V <sub>CC</sub> = +5.0V, V <sub>IN</sub> = V <sub>T-</sub>             |     | -0.18*          |      | mA    |

\*Typical Value

Note 1: All typicals are at V<sub>CC</sub> = 5V, T<sub>A</sub> = 25°C.


Note 2: Not more than one output should be shorted at a time, and the duration should not exceed one second.

## Switching Characteristics

$V_{CC} = +5.0V, T_A = +25^\circ C$


| Symbol    | Parameter  | $R_L = 2\text{ k}\Omega,$<br>$C_L = 15\text{ pF}$<br><b>DM74LS13</b> |  | Units |
|-----------|--|--|--|-------|
|           |  | Min  | Max  |       |
|           |  | $t_{PLH}$  | Propagation Delay Time<br>Low to High Level Output |       |
| $t_{PHL}$ | Propagation Delay Time<br>High to Low Level Output |  | 27   | ns    |

## Physical Dimensions inches (millimeters)



**14-Lead Small Outline Molded Package (M)**  
**Order Number DM74LS13M**  
**NS Package Number M14A**

**Physical Dimensions** inches (millimeters) (Continued)



**14-Lead Molded Dual-In-Line Package (N)**  
**Order Number DM74LS13N**  
**NS Package Number N14A**

**LIFE SUPPORT POLICY**

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



**National Semiconductor Corporation**  
 1111 West Bardin Road  
 Arlington, TX 76017  
 Tel: 1(800) 272-9959  
 Fax: 1(800) 737-7018

**National Semiconductor Europe**  
 Fax: (+49) 0-180-530 85 86  
 Email: onjwge@tevm2.nsc.com  
 Deutsch Tel: (+49) 0-180-530 85 85  
 English Tel: (+49) 0-180-532 78 32  
 Français Tel: (+49) 0-180-532 93 58  
 Italiano Tel: (+49) 0-180-534 16 80

**National Semiconductor Hong Kong Ltd.**  
 13th Floor, Straight Block,  
 Ocean Centre, 5 Canton Rd.  
 Tsimshatsui, Kowloon  
 Hong Kong  
 Tel: (852) 2737-1600  
 Fax: (852) 2736-9960

**National Semiconductor Japan Ltd.**  
 Tel: 81-043-299-2309  
 Fax: 81-043-299-2408

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.