




## 3.0A Super-Fast Glass Passivated Rectifiers

### Features

- Glass passivated die construction
- Diffused junction
- Super-fast switching for high efficiency
- High current capability and low forward voltage drop
- Surge overload rating to 150A peak
- Low reverse leakage current
- Plastic material – UL Recognition flammability classification 94V-0



14 423

### Absolute Maximum Ratings

$T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Type	Symbol	Value	Unit
Repetitive peak reverse voltage =Working peak reverse voltage =DC Blocking voltage		SF30AG	$V_{RRM}$ = $V_{RWM}$ = $V_R$	50	V
		SF30BG		100	V
		SF30CG		150	V
		SF30DG		200	V
		SF30FG		300	V
		SF30GG		400	V
		SF30HG		500	V
		SF30JG		600	V
Peak forward surge current			$I_{FSM}$	150	A
Average forward current	$T_A=55^\circ\text{C}$		$I_{FAV}$	3	A
Junction and storage temperature range			$T_j=T_{stg}$	-65...+150	$^\circ\text{C}$


### Electrical Characteristics

$T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Type	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_F=3\text{A}$	SF30AG–DG	$V_F$			0.95	V
		SF30FG–GG	$V_F$			1.3	V
		SF30HG–JG	$V_F$			1.5	V
Reverse current	$T_A=25^\circ\text{C}$		$I_R$			10	$\mu\text{A}$
	$T_A=100^\circ\text{C}$		$I_R$			100	$\mu\text{A}$
Reverse recovery time	$I_F=1\text{A}, I_R=0.5\text{A}, I_{rr}=0.25\text{A}$	SF30AG–DG	$t_{rr}$			35	ns
		SF30FG–GG	$t_{rr}$			40	ns
		SF30HG–JG	$t_{rr}$			50	ns
Diode capacitance	$V_R=4\text{V}, f=1\text{MHz}$	SF30AG–GG	$C_D$		75		pF
		SF30HG–JG	$C_D$		50		pF
Thermal resistance junction to ambient			$R_{thJA}$		32		K/W




### Characteristics ( $T_j = 25^\circ\text{C}$ unless otherwise specified)




15434

Figure 1. Max. Average Forward Current vs. Ambient Temperature




15436

Figure 3. Max. Peak Forward Surge Current vs. Number of Cycles



15435

Figure 2. Typ. Forward Current vs. Forward Voltage




15437


Figure 4. Typ. Diode Capacitance vs. Reverse Voltage



### Dimensions in mm



D0-201AD		
Dim	Min	Max
A	25.40	-
B	7.20	9.50
C	1.20	1.30
D	4.80	5.30
All Dimensions in mm		



technical drawings  
according to DIN  
specifications

14445

Case: molded plastic  
Polarity: cathode band  
Approx. weight: 1.12 grams  
Mounting position: any  
Marking: type number



### Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol ( 1987 ) and its London Amendments ( 1990 ) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

**Vishay Semiconductor GmbH** has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

**Vishay Semiconductor GmbH** can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

**We reserve the right to make changes to improve technical design and may do so without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay-Telefunken products for any unintended or unauthorized application, the buyer shall indemnify Vishay-Telefunken against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423