

**Features**

- 131072 x 8 bit static CMOS RAM
- 70 ns Access Time
- Common data inputs and data outputs
- Three-state outputs
- Typ. operating supply current  
70 ns: 15 mA
- Standby current < 1 mA at 85°C
- TTL/CMOS-compatible
- Power supply voltage 5 V
- Operating temperature range  
0 °C to 70 °C  
-40 °C to 85 °C
- QS 9000 Quality Standard
- ESD protection > 750 V  
(MIL STD 883C M3015.7)
- Latch-up immunity >100 mA
- Package: PDIP32 (600 mil)  
SOP32 (450 mil)  
TSOP I 32  
sTSOP I 32

**Description**


The U621708 is a static RAM manufactured using a CMOS process technology with the following operating modes:

- Read - Standby
- Write - Data Retention


The memory array is based on a 6-Transistor cell.

The circuit is activated by the rising edge of E2 (at  $\bar{E}1 = L$ ), or the falling edge of  $\bar{E}1$  (at  $E2 = H$ ). The address and control inputs open simultaneously. According to the information of  $\bar{W}$  and  $\bar{G}$ , the data inputs, or outputs, are active. During the active state ( $\bar{E}1 = L$  and  $E2 = H$ ) each address change leads to a new Read cycle. In a Read cycle, the data outputs are activated by the falling edge of  $\bar{G}$ , afterwards the data word will be

available at the outputs DQ0-DQ7. After the address change, the data outputs go High-Z until the new information is available. The data outputs have no preferred state. If the memory is driven by CMOS levels in the active state, and if there is no change of the address, data input and control signals  $\bar{W}$  or  $\bar{G}$ , the operating current ( $I_O = 0$  mA) drops to the value of the operating current in the Standby mode. The Read cycle is finished by the falling edge of  $E2$  or  $W$ , or by the rising edge of  $\bar{E}1$ , respectively. Data retention is guaranteed down to 2 V. With the exception of E1 and E2, all inputs consist of NOR gates, so that no pull-up/pull-down resistors are required.

**Pin Configuration****Pin Description**


Top View



Top View

Signal Name	Signal Description
A0 - A16	Address Inputs
DQ0 - DQ7	Data In/Out
$\bar{E}1$	Chip Enable 1
E2	Chip Enable 2
$\bar{G}$	Output Enable
$\bar{W}$	Write Enable
VCC	Power Supply Voltage
VSS	Ground
n.c.	not connected

## Block Diagram



## Truth Table

Operating Mode	E1	E2	W	G	DQ0 - DQ7
Standby/not selected	*	L	*	*	High-Z
	H	*	*	*	High-Z
Internal Read	L	H	H	H	High-Z
Read	L	H	H	L	Data Outputs Low-Z
Write	L	H	L	*	Data Inputs High-Z

\* H or L

## Characteristics

All voltages are referenced to  $V_{SS} = 0$  V (ground).

All characteristics are valid in the power supply voltage range and in the operating temperature range specified.

Dynamic measurements are based on a rise and fall time of  $\leq 5$  ns, measured between 10 % and 90 % of  $V_I$ , as well as input levels of  $V_{IL} = 0$  V and  $V_{IH} = 3$  V. The timing reference level of all input and output signals is 1.5 V, with the exception of the  $t_{dis}$ -times and  $t_{en}$ -times, in which cases transition is measured  $\pm 200$  mV from steady-state voltage.

Absolute Maximum Ratings <sup>a</sup>	Symbol	Min.	Max.	Unit
Power Supply Voltage	$V_{CC}$	-0.5	7	V
Input Voltage	$V_I$	-0.5	$V_{CC} + 0.5$ <sup>b</sup>	V
Output Voltage	$V_O$	-0.5	$V_{CC} + 0.5$ <sup>b</sup>	V
Power Dissipation	$P_D$	-	1	W
Operating Temperature C-Type K-Type	$T_a$	0 -40	70 85	°C
Storage Temperature	$T_{stg}$	-65	150	°C
Output Short-Circuit Current at $V_{CC} = 5$ V and $V_O = 0$ V <sup>c</sup>	$ I_{os} $		200	mA

<sup>a</sup> Stresses greater than those listed under „Absolute Maximum Ratings“ may cause permanent damage to the device. This is a stress rating only, and functional operation of the device at condition above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability

<sup>b</sup> Maximum voltage is 7 V

<sup>c</sup> Not more than 1 output should be shorted at the same time. Duration of the short circuit should not exceed 30 s.

Recommended Operating Conditions	Symbol	Conditions	Min.	Max.	Unit
Power Supply Voltage	$V_{CC}$		4.5	5.5	V
Input Low Voltage*	$V_{IL}$		-0.3	0.8	V
Input High Voltage	$V_{IH}$		2.2	$V_{CC} + 0.3$	V

<sup>d</sup> -2 V at Pulse Width 10 ns

# U621708

---

<b>Electrical Characteristics</b>	<b>Symbol</b>	<b>Conditions</b>	<b>Min.</b>	<b>Max.</b>	<b>Unit</b>
Supply Current - Operating Mode	$I_{CC(OP)}$	$V_{CC} = 5.5\text{ V}$ $V_{IL} = 0.8\text{ V}$ $V_{IH} = 2.2\text{ V}$		30	mA
Supply Current - Standby Mode (CMOS level)	$I_{CC(SB)}$	$V_{CC} = 5.5\text{ V}$ $V_{E1} = V_{E2} = V_{CC} - 0.2\text{ V}$		1	mA
Supply Current - Standby Mode (TTL level)	$I_{CC(SB)1}$	$V_{CC} = 5.5\text{ V}$ $V_{E1} = V_{E2} = 2.2\text{ V}$		10	mA
Output High Voltage	$V_{OH}$	$V_{CC} = 4.5\text{ V}$ $I_{OH} = -4.0\text{ mA}$	2.4		V
Output Low Voltage	$V_{OL}$	$V_{CC} = 4.5\text{ V}$ $I_{OL} = 8.0\text{ mA}$		0.4	V
Input High Leakage Current	$I_{IH}$	$V_{CC} = 5.5\text{ V}$ $V_{IH} = 5.5\text{ V}$		2	$\mu\text{A}$
Input Low Leakage Current	$I_{IL}$	$V_{CC} = 5.5\text{ V}$ $V_{IL} = 0\text{ V}$	-2		$\mu\text{A}$
Output High Current	$I_{OH}$	$V_{CC} = 4.5\text{ V}$ $V_{OH} = 2.4\text{ V}$		-4	mA
Output Low Current	$I_{OL}$	$V_{CC} = 4.5\text{ V}$ $V_{OL} = 0.4\text{ V}$	8		mA
Output Leakage Current High at Three-State Outputs	$I_{OHZ}$	$V_{CC} = 5.5\text{ V}$ $V_{OH} = 5.5\text{ V}$		2	$\mu\text{A}$
Low at Three-State Outputs	$I_{OLZ}$	$V_{CC} = 5.5\text{ V}$ $V_{OL} = 0\text{ V}$	-2		$\mu\text{A}$


<b>Switching Characteristics Read Cycle</b>	<b>Symbol</b>		<b>70</b>		<b>Unit</b>
	<b>Alt.</b>	<b>IEC</b>	<b>Min.</b>	<b>Max.</b>	
Read Cycle Time	$t_{RC}$	$t_{cR}$	70		ns
Address Access Time to Data Valid	$t_{AA}$	$t_{a(A)}$		70	ns
Chip Enable Access Time to Data Valid	$t_{ACE}$	$t_{a(E)}$		70	ns
$\bar{G}$ LOW to Data Valid	$t_{OE}$	$t_{a(G)}$		25	ns
$\bar{E}_1$ HIGH or $E_2$ LOW to Output in High-Z	$t_{HZCE}$	$t_{dis(E)}$		15	ns
$\bar{G}$ HIGH to Output in High-Z	$t_{HZOE}$	$t_{dis(G)}$		15	ns
$\bar{E}_1$ LOW or $E_2$ HIGH to Output in Low-Z	$t_{LZCE}$	$t_{en(E)}$	10		ns
$\bar{G}$ LOW to Output in Low-Z	$t_{LZOE}$	$t_{en(G)}$	5		ns
Output Hold Time from Address Change	$t_{OH}$	$t_{v(A)}$	10		ns
$\bar{E}_1$ LOW or $E_2$ HIGH to Power-Up Time	$t_{PU}$		0		ns
$\bar{E}_1$ HIGH or $E_2$ LOW to Power-Down Time	$t_{PD}$			70	ns

<b>Switching Characteristics Write Cycle</b>	<b>Symbol</b>		<b>70</b>		<b>Unit</b>
	<b>Alt.</b>	<b>IEC</b>	<b>Min.</b>	<b>Max.</b>	
Write Cycle Time	$t_{WC}$	$t_{cW}$	70		ns
Write Pulse Width	$t_{WP}$	$t_{w(W)}$	35		ns
Write Setup Time	$t_{WP}$	$t_{su(W)}$	35		ns
Address Setup Time	$t_{AS}$	$t_{su(A)}$	0		ns
Address Valid to End of Write	$t_{AW}$	$t_{su(A-WH)}$	35		ns
Chip Enable Setup Time	$t_{CW}$	$t_{su(E)}$	40		ns
Pulse Width Chip Enable to End of Write	$t_{CW}$	$t_{w(E)}$	40		ns
Data Setup Time	$t_{DS}$	$t_{su(D)}$	25		ns
Data Hold Time	$t_{DH}$	$t_{h(D)}$	0		ns
Address Hold from End of Write	$t_{AH}$	$t_{h(A)}$	0		ns
$\bar{W}$ LOW to Output in High-Z	$t_{HZWE}$	$t_{dis(W)}$		20	ns
$\bar{G}$ HIGH to Output in High-Z	$t_{HZOE}$	$t_{dis(G)}$		15	ns
$\bar{W}$ HIGH to Output in Low-Z	$t_{LZWE}$	$t_{en(W)}$	5		ns
$\bar{G}$ LOW to Output in Low-Z	$t_{LZOE}$	$t_{en(G)}$	5		ns
$\bar{W}$ to Chip Enable Setup Time	$t_{WE}$	$t_{su(W-E)}$	10		ns

## Data Retention Mode


Data Retention Characteristics	Symbol		Conditions	Min.	Typ.	Max.	Unit
	Alt.	IEC					
Data Retention Supply Voltage		$V_{CC(DR)}$		2		5.5	V
Data Retention Supply Current		$I_{CC(DR)}$	$V_{CC(DR)} = 3 \text{ V}$ $V_{E1} = V_{E2} = V_{CC(DR)} - 0.2 \text{ V}$			0.6	mA
Data Retention Setup Time	$t_{CDR}$	$t_{su(DR)}$	See Data Retention Waveforms (below)	0			ns
Operating Recovery Time	$t_R$	$t_{rec}$		$t_{cR}$			ns

### Data Retention Mode $\overline{E1}$ - controlled




$$\begin{aligned} V_{E2(DR)} &\geq V_{CC(DR)} - 0.2 \text{ V} \text{ or } V_{E2(DR)} \leq 0.2 \text{ V} \\ V_{CC(DR)} - 0.2 \text{ V} &\leq V_{\overline{E1}(DR)} \leq V_{CC(DR)} + 0.3 \text{ V} \end{aligned}$$

### Data Retention Mode E2 - controlled



$$\begin{aligned} V_{E1(DR)} &\geq V_{CC(DR)} - 0.2 \text{ V} \text{ or } V_{E1(DR)} \leq 0.2 \text{ V} \\ V_{E2(DR)} &\leq 0.2 \text{ V} \end{aligned}$$

**Test Configuration for Functional Check**


<sup>e</sup> In measurement of  $t_{dis(E)}$ ,  $t_{dis(W)}$ ,  $t_{en(E)}$ ,  $t_{en(W)}$ ,  $t_{en(G)}$  the capacitance is 5 pF.

Capacitance	Conditions	Symbol	Min.	Max.	Unit
Input Capacitance	$V_{CC} = 5.0 \text{ V}$ $V_I = V_{SS}$	$C_I$		7	pF
Output Capacitance	$f = 1 \text{ MHz}$ $T_a = 25^\circ \text{C}$	$C_o$		7	pF

All pins not under test must be connected with ground by capacitors.

**Ordering Code**

Example



Type \_\_\_\_\_

**Leadfree Option**

blank = Standard Package

G1 = Leadfree Green Package <sup>f</sup>

Package \_\_\_\_\_

D = PDIP32 (600 mil)

S = SOP32 (450 mil)

T = TSOP I 32


T1 = sTSOP I 32

**Operating Temperature Range**

C = 0 to 70 °C

K = -40 to 85 °C


<sup>f</sup> on special request

**Device Marking (example)**


Date of manufacture  
(The first 2 digits indicating the year, and the last 2 digits the calendar week.)

Leadfree Green Package

**Read Cycle 1:  $A_i$ -controlled (during Read Cycle :  $\overline{E1} = \overline{G} = V_{IL}$ ,  $\overline{W} = E2 = V_{IH}$ )**




**Read Cycle 2:  $\overline{G}$ ,  $\overline{E1}$ ,  $E2$ -controlled (during Read Cycle:  $\overline{W} = V_{IH}$ )**




\* The same applies to  $\overline{E1}$


**Write Cycle1:  $\overline{W}$ -controlled**



### Write Cycle 2: E1-controlled



### Write Cycle 3 (E2-controlled)



undefined      L- to H-level      H- to L-level

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved.

**LIFE SUPPORT POLICY**

ZMD products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the ZMD product could create a situation where personal injury or death may occur. Components used in life-support devices or systems must be expressly authorized by ZMD for such purpose.

**LIMITED WARRANTY**

The information in this document has been carefully checked and is believed to be reliable. However Zentrum Mikroelektronik Dresden AG (ZMD) makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon it. The information in this document describes the type of component and shall not be considered as assured characteristics.

ZMD does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright, mask work right or other rights of third parties, and no patent or licence is implied hereby. This document does not in any way extent ZMD's warranty on any product beyond that set forth in its standard terms and conditions of sale.

ZMD reserves terms of delivery and reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.