



Features

- Frequency Range 1.0 to 150MHz
- Frequency Stability ± 25 or ± 50 ppm
- Operating Voltage: 1.8V to 3.3V
- Operating Temperature Range
 - Commercial: 0° to +70°C
 - Ext. Commercial: -20 to +70°C
 - Industrial: -40° to +85°C
- Low Operating and Standby Current
 - 3mA operating (40MHz)
 - 1µA Standby
- Ultra-Miniature Footprint
 - 2.5 x 2.0 x 0.85mm
 - 3.2 x 2.5 x 0.85mm
 - 5.0 x 3.2 x 0.85mm
 - 7.0 x 5.0 x 0.85mm
- Excellent Shock & Vibration Resistance
- Pb free, RoHS, REACH SVHC Compliant
- ISO9001 (2008) Qualified



Description

The Euroquartz EMEM8002 oscillator range are programmable MEMS (Micro Electro-Mechanical System) devices offering excellent jitter and stability performance over a wide range of supply voltages and temperature ranges (up to -40° to +105°C). EMEM8002 parts incorporate an all-silicon resonator that is robust and performs well in high shock and vibration environments.

EMEM8002 oscillators are available in four, industry-standard SMD packages: 7 x 5mm, 5 x 3.2mm, 3.2 x 2.5mm and 2.5 x 2.0mm. The part may be 'dropped in' to most PCB footprints as standard crystal oscillators.

The programmable EMEM8002 series are available on very short leadtimes.

Electrical Specifications

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Frequency	f_0	Single frequency	1		150	MHz
Frequency Tolerance Option 1 Option 2 Option 3	Δf	-40° to +85°C -20° to +70°C 0° to +70°C			$\pm 25, \pm 50$ $\pm 25, \pm 50$ $\pm 25, \pm 50$	ppm
Supply Current, no load	I_{DD}	$C_L = 0p$ $R_L = \infty$ $T = 25^\circ C$		3 4 5 6	10	mA
Supply Current, Standby	I_{DD}	$T = 25^\circ C$			1	µA
Output Logic Levels Output Logic High Output Logic Low	V_{OH} V_{OL}	$C_L = 15p$	0.8* V_{DD}		- 0.2* V_{DD}	Volts
Output Startup Time ²	T_{SU}	$T = 25^\circ C$		3	10	ms
Output Disable Time	T_{DA}			20	100	ns
Output Duty Cycle	SYM		45		55	%
Input Logic Levels Input Logic High Input Logic Low	V_{IH} V_{IL}		0.75* V_{DD}		0.25* V_{DD}	Volts
Jitter, Cycle to Cycle	J_{CC}	$F = 100MHz^3$		95		ps

1. Absolute maximum ratings are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated beyond these limits.
2. Output frequency to within 100ppm of final stable output frequency.
3. See typical cycle to cycle jitter graph for frequency dependence.

Absolute Maximum Ratings

Item	Min.	Max.	Unit	Condition
Supply Voltage	-0.3	+4.0	V	
Input Voltage	-0.3	VDD+0.3	V	
Junction Temp.	-	+150	°C	
Storage Temp.	-55	+150	°C	
Soldering Temp.	-	+260	°C	40 sec. max.
ESD HBM MM CDM	-	4000 200 1500	V	


Standby Function

Standby# (Pin 1)	Output (Pin 3)
High Level	Output ON
Open (not connected)	Output ON
Low Level	High Impedance

Recommended Operating Conditions

Parameter	Symbol	Range
Supply Voltage	V _{DD}	1.65 ~ 3.60V
Output Load	Z _L	R > 10kΩ, C ≤ 15pF
Operating Temperature Option 1 Option 2 Option 3	T	-40 to +85°C -20 to +70°C 0 to +70°C

Ordering Code



* See Ordering Information for details

Ordering Information

Package (Plastic QFN)	Temperature	Stability	Frequency	Packing Option
P=A: 7.0 x 5.0mm P=B: 5.0 x 3.2mm P=C: 3.2 x 2.5mm P=D: 2.5 x 2.0mm	T=C: 0° ~ +70°C T=E: -20° ~ +70°C T=I: -40° ~ +85°C T=L: -40° ~ +105°C	S=1: ±50ppm S=2: ±25ppm S=3: ±10ppm	XXX.XXX	Blank: Tubes T: Tape & Reel

Order in the form: **EMEM8001PTS-FREQUENCY-SUPPLY FORMAT**


Example: **EMEM8002CE1-123.000T**

This is an 123.000MHz Oscillator in a plastic 3.2 x 2.5mm package; stability ±50ppm over -20° to +70°C, shipped in tape and reel.


Nominal Performance Characteristics

1.8 Volt Supply Voltage Characteristics


Supply Current




Standby Current




Rise Time




Fall Time



Period Jitter




Cycle to Cycle Jitter




Nominal Performance Characteristics

3.3 Volt Supply Voltage Characteristics


Supply Current




Standby Current




Rise Time




Fall Time




Period Jitter




Cycle to Cycle Jitter



Board Layout (Recommended)




Solder Reflow Profile




MSL1 @ 260°C refer to JSTD-020C	
Ramp-up Rate (200°C to Peak Temp.)	3°C/s max.
Preheat Time 150°C to 200°C	60-180s
Time maintained above 217°C	60-150s
Peak Temperature	255-260°C
Time within 5°C of actual peak	20-40s
Ramp-Down Rate	6°C/s max.
Time 25°C to Peak Temperature	8 min max.

PACKAGE DIMENSIONS


7.0 x 5.0mm Plastic Package



5.0 x 3.2mm Plastic Package



3.2 x 2.5mm Plastic Package



2.5 x 2.0mm Plastic Package

