

54FCT373

Octal Transparent Latch with TRI-STATE® Outputs

General Description

The 'FCT373 consists of eight latches with TRI-STATE outputs for bus organized system applications. The flip-flops appear transparent to the data when Latch Enable (LE) is HIGH. When LE is LOW, the data that meets the setup times is latched. Data appears on the bus when the Output Enable (\overline{OE}) is LOW. When \overline{OE} is HIGH the bus output is in the high impedance state.



Features

- TRI-STATE outputs for bus interfacing
- TTL input and output level compatible
- CMOS power consumption
- Output sink capability of 32 mA, source capability of 12 mA
- Standard Microcircuit Drawing (SMD) 5962-8764401

Ordering Code

| Military | Package Number | Package Description |
|--------------|----------------|---|
| 54FCT373DMQB | J20A | 20-Lead Ceramic Dual-In-Line |
| 54FCT373FMQB | W20A | 20-Lead Cerpack |
| 54FCT373LMQB | E20A | 20-Lead Ceramic Leadless Chip Carrier, Type C |

Connection Diagrams



| Pin Names | Description |
|-----------------|-------------------------------------|
| D_0 – D_7 | Data Inputs |
| LE | Latch Enable Input (Active HIGH) |
| \overline{OE} | Output Enable Input (Active LOW) |
| O_0 – O_7 | TRI-STATE Latch Outputs |

TRI-STATE® is a registered trademark of National Semiconductor Corporation.


Functional Description

The 54FCT373 contains eight D-type latches with TRI-STATE output buffers. When the Latch Enable (LE) input is HIGH, data on the D_n inputs enters the latches. In this condition the latches are transparent, i.e., a latch output will change state each time its D input changes. When LE is LOW, the latches store the information that was present on the D inputs a setup time preceding the HIGH-to-LOW transition of LE. The TRI-STATE buffers are controlled by the Output Enable (\overline{OE}) input. When \overline{OE} is LOW, the buffers are in the bi-state mode. When \overline{OE} is HIGH the buffers are in the high impedance mode but this does not interfere with entering new data into the latches.

| Inputs | | | Output |
|--------|-----------------|-------|-------------------|
| LE | \overline{OE} | D_n | O_n |
| H | L | H | H |
| H | L | L | L |
| L | L | X | O_n (no change) |
| X | H | X | Z |

H = HIGH Voltage Level
 L = LOW Voltage Level
 X = Immaterial
 Z = High Impedance State

Logic Diagram



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

| | |
|--|-------------------|
| Storage Temperature | -65°C to +150°C |
| Ambient Temperature under Bias | -55°C to +125°C |
| Junction Temperature under Bias Ceramic | -55°C to +175°C |
| V _{CC} Pin Potential to Ground Pin | -0.5V to +7.0V |
| Input Voltage (Note 2) | -0.5V to +7.0V |
| Input Current (Note 2) | -30 mA to +5.0 mA |
| Voltage Applied to Any Output in the Disabled or Power-Off State | -0.5V to +5.5V |

in the HIGH State -0.5V to V_{CC}
Current Applied to Output
in LOW State (Max) twice the rated I_{OL} (mA)

Recommended Operating Conditions

| | |
|--|-----------------|
| Free Air Ambient Temperature Military | -55°C to +125°C |
| Supply Voltage Military | +4.5V to +5.5V |

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

DC Electrical Characteristics

| Symbol | Parameter | FCT240 | | Units | V _{CC} | Conditions |
|------------------|-------------------------------|--------|------|--------|-----------------|---|
| | | Min | Max | | | |
| V _{IH} | Input HIGH Voltage | 2.0 | | V | | Recognized HIGH Signal |
| V _{IL} | Input LOW Voltage | | 0.8 | V | | Recognized LOW Signal |
| V _{CD} | Input Clamp Diode Voltage | | -1.2 | V | Min | I _{IN} = -18 mA |
| V _{OH} | Output HIGH Voltage | 54FCT | 4.3 | V | Min | I _{OH} = -300 µA |
| | | 54FCT | 2.4 | V | Min | I _{OH} = -12 mA |
| V _{OL} | Output LOW Voltage | 54FCT | 0.2 | V | Min | I _{OL} = 300 µA |
| | | 54FCT | 0.5 | V | Min | I _{OL} = 32 mA |
| I _{IH} | Input HIGH Current | | 5 | µA | Max | V _{IN} = 5.5V |
| I _{IL} | Input LOW Current | | -5 | µA | Max | V _{IN} = 0.0V |
| I _{OZH} | High Impedance Output Current | | 10 | µA | Max | V _{IN} = 5.5V |
| I _{OZL} | High Impedance Output Current | | -10 | µA | Max | V _{IN} = 0.0V |
| I _{OS} | Output Short-Circuit Current | | -60 | mA | Max | V _{OUT} = 0.0V |
| I _{CCQ} | Power Supply Current | | 1.5 | mA | Max | V _{IN} = 0.2V or V _{IN} = 5.3V |
| ΔI _{CC} | Power Supply Current | | 2.0 | mA | Max | V _{IN} = 3.4V |
| I _{CCT} | Total Power Supply Current | | 5.6 | mA | Max | V _{IN} = 3.4V or V _{IN} = GND, \overline{OE} = GND, f _i = 10Mhz, outputs open, one bit toggling, 50% duty cycle |
| | | | 4.0 | mA | Max | V _{IN} = 5.3V or V _{IN} = 0.2V, \overline{OE} = GND, f _i = 10Mhz, outputs open, one bit toggling, 50% duty cycle |
| I _{CCD} | Dynamic I _{CC} | | 0.25 | mA/MHz | Max | Outputs Open, \overline{OE} = GND, one bit toggling, 50% duty Cycle |


| AC Electrical Characteristics | | | | | |
|-------------------------------|---------------------|--|------|-------|----------|
| Symbol | Parameter | 54FCT | | Units | Fig. No. |
| | | $T_A = -55^\circ\text{C to }+125^\circ\text{C}$ $V_{CC} = 4.5\text{V to }5.5\text{V}$ $C_L = 50\text{ pF}$ | | | |
| | | Min | Max | | |
| t_{PLH} | Propagation Delay | 1.5 | 8.5 | ns | Figure 4 |
| t_{PHL} | D_n to O_n | 1.5 | 8.5 | | |
| t_{PLH} | Propagation Delay | 2.0 | 15.0 | ns | Figure 4 |
| t_{PHL} | LE to O_n | 2.0 | 15.0 | | |
| t_{PZH} | Output Enable Time | 1.5 | 13.5 | ns | Figure 6 |
| t_{PZL} | | 1.5 | 13.5 | | |
| t_{PHZ} | Output Disable Time | 1.5 | 12.5 | ns | Figure 6 |
| t_{PLZ} | | 1.5 | 12.5 | | |

| AC Operating Requirements | | | | | |
|---------------------------|-------------------------|--|-----|-------|----------|
| Symbol | Parameter | 54FCT | | Units | Fig. No. |
| | | $T_A = -55^\circ\text{C to }+125^\circ\text{C}$ $V_{CC} = 4.5\text{V to }5.5\text{V}$ $C_L = 50\text{ pF}$ | | | |
| | | Min | Max | | |
| $t_s(H)$ | Setup Time, HIGH | 2.0 | | ns | Figure 7 |
| $t_s(L)$ | or LOW D_n to LE | 2.0 | | | |
| $t_h(H)$ | Hold Time, HIGH | 3.0 | | ns | Figure 7 |
| $t_h(L)$ | or LOW D_n to LE | 3.0 | | | |
| $t_w(H)$ | Pulse Width, LE HIGH | 6.0 | | ns | Figure 5 |

| Capacitance | | | | | |
|--------------------|--------------------|-----|-------|------------------------|--|
| Symbol | Parameter | Max | Units | Conditions | |
| C_{IN} | Input Capacitance | 10 | pF | $V_{CC} = 0\text{V}$ | |
| C_{OUT} (Note 3) | Output Capacitance | 12 | pF | $V_{CC} = 5.0\text{V}$ | |

Note 3: C_{OUT} is measured at frequency $f = 1\text{ MHz}$, per MIL-STD-883B, Method 3012.

AC Loading



*Includes jig and probe capacitance

FIGURE 1. Standard AC Test Load




FIGURE 2. Test Input Signal Levels

| Amplitude | Rep. Rate | t_w | t_r | t_f |
|-----------|-----------|--------|--------|--------|
| 3.0V | 1 MHz | 500 ns | 2.5 ns | 2.5 ns |

FIGURE 3. Test Input Signal Requirements




FIGURE 4. Propagation Delay Waveforms for Inverting and Non-Inverting Functions




FIGURE 5. Propagation Delay, Pulse Width Waveforms




FIGURE 6. TRI-STATE Output HIGH and LOW Enable and Disable Times





FIGURE 7. Setup Time, Hold Time and Recovery Time Waveforms


Physical Dimensions inches (millimeters) unless otherwise noted




20-Terminal Ceramic Chip Carrier (L)
NS Package Number E20A

E20A (REV. 01)

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



20-Lead Ceramic Dual-In-Line (D)
NS Package Number J20A



20-Lead Ceramic Flatpak (F)
NS Package Number W20A

Notes

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
Americas
Tel: 1-800-272-9959
Fax: 1-800-737-7018
Email: support@nsc.com

www.national.com

National Semiconductor Europe

Fax: +49 (0) 1 80-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 1 80-530 85 85
English Tel: +49 (0) 1 80-532 78 32
Français Tel: +49 (0) 1 80-532 93 58
Italiano Tel: +49 (0) 1 80-534 16 80

National Semiconductor Asia Pacific Customer Response Group

Tel: 65-2544466
Fax: 65-2504466
Email: sea.support@nsc.com

National Semiconductor Japan Ltd.

Tel: 81-3-5639-7560
Fax: 81-3-5639-7507