

To our customers,

Old Company Name in Catalogs and Other Documents

On April 1st, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: <http://www.renesas.com>

April 1st, 2010
Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (<http://www.renesas.com>)

Send any inquiries to <http://www.renesas.com/inquiry>.

Notice

1. All information included in this document is current as of the date this document is issued. Such information, however, is subject to change without any prior notice. Before purchasing or using any Renesas Electronics products listed herein, please confirm the latest product information with a Renesas Electronics sales office. Also, please pay regular and careful attention to additional and different information to be disclosed by Renesas Electronics such as that disclosed through our website.
2. Renesas Electronics does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of Renesas Electronics products or technical information described in this document. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
3. You should not alter, modify, copy, or otherwise misappropriate any Renesas Electronics product, whether in whole or in part.
4. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation of these circuits, software, and information in the design of your equipment. Renesas Electronics assumes no responsibility for any losses incurred by you or third parties arising from the use of these circuits, software, or information.
5. When exporting the products or technology described in this document, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You should not use Renesas Electronics products or the technology described in this document for any purpose relating to military applications or use by the military, including but not limited to the development of weapons of mass destruction. Renesas Electronics products and technology may not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations.
6. Renesas Electronics has used reasonable care in preparing the information included in this document, but Renesas Electronics does not warrant that such information is error free. Renesas Electronics assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.
7. Renesas Electronics products are classified according to the following three quality grades: “Standard”, “High Quality”, and “Specific”. The recommended applications for each Renesas Electronics product depends on the product’s quality grade, as indicated below. You must check the quality grade of each Renesas Electronics product before using it in a particular application. You may not use any Renesas Electronics product for any application categorized as “Specific” without the prior written consent of Renesas Electronics. Further, you may not use any Renesas Electronics product for any application for which it is not intended without the prior written consent of Renesas Electronics. Renesas Electronics shall not be in any way liable for any damages or losses incurred by you or third parties arising from the use of any Renesas Electronics product for an application categorized as “Specific” or for which the product is not intended where you have failed to obtain the prior written consent of Renesas Electronics. The quality grade of each Renesas Electronics product is “Standard” unless otherwise expressly specified in a Renesas Electronics data sheets or data books, etc.
 - “Standard”: Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; and industrial robots.
 - “High Quality”: Transportation equipment (automobiles, trains, ships, etc.); traffic control systems; anti-disaster systems; anti-crime systems; safety equipment; and medical equipment not specifically designed for life support.
 - “Specific”: Aircraft; aerospace equipment; submersible repeaters; nuclear reactor control systems; medical equipment or systems for life support (e.g. artificial life support devices or systems), surgical implantations, or healthcare intervention (e.g. excision, etc.), and any other applications or purposes that pose a direct threat to human life.
8. You should use the Renesas Electronics products described in this document within the range specified by Renesas Electronics, especially with respect to the maximum rating, operating supply voltage range, movement power voltage range, heat radiation characteristics, installation and other product characteristics. Renesas Electronics shall have no liability for malfunctions or damages arising out of the use of Renesas Electronics products beyond such specified ranges.
9. Although Renesas Electronics endeavors to improve the quality and reliability of its products, semiconductor products have specific characteristics such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Further, Renesas Electronics products are not subject to radiation resistance design. Please be sure to implement safety measures to guard them against the possibility of physical injury, and injury or damage caused by fire in the event of the failure of a Renesas Electronics product, such as safety design for hardware and software including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult, please evaluate the safety of the final products or system manufactured by you.
10. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. Please use Renesas Electronics products in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. Renesas Electronics assumes no liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
11. This document may not be reproduced or duplicated, in any form, in whole or in part, without prior written consent of Renesas Electronics.
12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products, or if you have any other inquiries.

(Note 1) “Renesas Electronics” as used in this document means Renesas Electronics Corporation and also includes its majority-owned subsidiaries.

(Note 2) “Renesas Electronics product(s)” means any product developed or manufactured by or for Renesas Electronics.

NPN SILICON RF TRANSISTOR
2SC5337

NPN SILICON RF TRANSISTOR FOR
 HIGH-FREQUENCY LOW DISTORTION AMPLIFIER
 4-PIN POWER MINIMOLD

FEATURES

- Low distortion: $IM_2 = 59.0$ dB TYP., $IM_3 = 82.0$ dB TYP. @ $V_{CE} = 10$ V, $I_c = 50$ mA
- Low noise
 $NF = 1.5$ dB TYP. @ $V_{CE} = 10$ V, $I_c = 50$ mA, $f = 500$ MHz
 $NF = 2.0$ dB TYP. @ $V_{CE} = 10$ V, $I_c = 50$ mA, $f = 1$ GHz
- 4-pin power minimold package with improved gain from the 2SC4536

★ **ORDERING INFORMATION**

Part Number	Quantity	Supplying Form
2SC5337	25 pcs (Non reel)	• Magazine case
2SC5337-T1	1 kpcs/reel	• 12 mm wide embossed taping • Collector face the perforation side of the tape

Remark To order evaluation samples, consult your NEC sales representative.
 Unit sample quantity is 25 pcs.

ABSOLUTE MAXIMUM RATINGS ($T_A = +25^\circ\text{C}$)

Parameter	Symbol	Ratings	Unit
Collector to Base Voltage	V_{CBO}	30	V
Collector to Emitter Voltage	V_{CEO}	15	V
Emitter to Base Voltage	V_{EBO}	3.0	V
Collector Current	I_c	250	mA
Total Power Dissipation	P_{tot} ^{Note}	2.0	W
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-65 to +150	$^\circ\text{C}$

Note Mounted on $16\text{ cm}^2 \times 0.7$ mm (t) ceramic substrate (Copper plating)

Because this product uses high-frequency technology, avoid excessive static electricity, etc.

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
 Not all devices/types available in every country. Please check with local NEC representative for availability and additional information.

ELECTRICAL CHARACTERISTICS (T_A = +25°C)

Parameter	Symbol	Test Conditions	MIN.	TYP.	MAX.	Unit
DC Characteristics						
Collector Cut-off Current	I _{CBO}	V _{CB} = 20 V, I _E = 0 mA	–	0.01	5.0	μA
Emitter Cut-off Current	I _{EBO}	V _{BE} = 2 V, I _C = 0 mA	–	0.03	5.0	μA
DC Current Gain	h _{FE} ^{Note 1}	V _{CE} = 10 V, I _C = 50 mA	40	120	200	–
RF Characteristics						
Insertion Power Gain	S _{21e} ²	V _{CE} = 10 V, I _C = 50 mA, f = 1 GHz	7.0	8.3	–	dB
Noise Figure (1)	N _F ^{Note 2}	V _{CE} = 10 V, I _C = 50 mA, f = 500 MHz	–	1.5	3.5	dB
Noise Figure (2)	N _F ^{Note 2}	V _{CE} = 10 V, I _C = 50 mA, f = 1 GHz	–	2.0	3.5	dB
2nd Order Intermodulation Distortion	IM ₂	V _{CE} = 10 V, I _C = 50 mA, R _S = R _L = 75 Ω, V _{in} = 105 dBμV/75 Ω, f ₁ = 190 MHz, f ₂ = 90 MHz, f = f ₁ – f ₂	–	59.0	–	dB
3rd Order Intermodulation Distortion	IM ₃	V _{CE} = 10 V, I _C = 50 mA, R _S = R _L = 75 Ω, V _{in} = 105 dBμV/75 Ω, f ₁ = 190 MHz, f ₂ = 200 MHz, f = 2 × f ₁ – f ₂	–	82.0	–	dB

Notes 1. Pulse measurement: PW ≤ 350 μs, Duty Cycle ≤ 2%


2. R_S = R_L = 50 Ω, tuned

h_{FE} CLASSIFICATION


Rank	QQ	QR	QS
Marking	QQ	QR	QS
h _{FE} Value	40 to 80	60 to 120	100 to 200

★ TYPICAL CHARACTERISTICS (Unless otherwise specified, $T_A = +25^\circ\text{C}$)


TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE




REVERSE TRANSFER CAPACITANCE vs. COLLECTOR TO BASE VOLTAGE




COLLECTOR CURRENT vs. COLLECTOR TO EMITTER VOLTAGE




DC CURRENT GAIN vs. COLLECTOR CURRENT




GAIN BANDWIDTH PRODUCT vs. COLLECTOR CURRENT




INSERTION POWER GAIN vs. COLLECTOR CURRENT




INSERTION POWER GAIN, MAG vs. FREQUENCY



NOISE FIGURE vs. COLLECTOR CURRENT



IM3, IM2+, IM2- vs. COLLECTOR CURRENT



Remark The graphs indicate nominal characteristics.

S-PARAMETERS

V_{CE} = 10 V, I_c = 50 mA

Frequency (GHz)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)
0.1	0.592	-136.6	24.447	108.4	0.030	50.5	0.465	-95.2
0.2	0.577	-160.0	12.746	96.5	0.042	57.4	0.335	-123.0
0.3	0.566	-168.5	8.591	91.2	0.055	67.3	0.276	-130.1
0.4	0.558	-174.0	6.438	87.2	0.066	70.8	0.269	-132.7
0.5	0.554	-177.5	5.160	84.1	0.083	68.6	0.262	-134.5
0.6	0.542	-179.4	4.312	82.3	0.095	70.6	0.262	-139.1
0.7	0.527	177.9	3.729	80.9	0.112	71.2	0.251	-133.4
0.8	0.519	175.8	3.292	78.7	0.123	74.6	0.252	-132.9
0.9	0.509	174.4	2.983	77.7	0.136	75.0	0.252	-124.6
1.0	0.514	171.0	2.759	76.6	0.151	75.3	0.257	-125.3
1.1	0.498	166.8	2.648	75.4	0.166	75.8	0.278	-118.4
1.2	0.494	167.3	2.665	71.3	0.180	74.7	0.306	-120.2
1.3	0.487	161.7	2.478	63.0	0.194	75.9	0.314	-124.2
1.4	0.467	160.4	2.177	60.1	0.216	74.7	0.273	-124.0
1.5	0.477	157.4	1.973	57.9	0.230	74.9	0.281	-123.2
1.6	0.471	154.5	1.815	57.2	0.240	73.2	0.291	-120.2
1.7	0.467	152.5	1.754	55.3	0.260	72.9	0.316	-118.7
1.8	0.469	151.3	1.639	54.4	0.273	70.5	0.312	-123.1
1.9	0.465	149.1	1.568	53.4	0.285	69.9	0.316	-125.5
2.0	0.468	147.0	1.475	52.6	0.289	69.3	0.323	-126.3

V_{CE} = 10 V, I_c = 100 mA

Frequency (GHz)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)
0.1	0.564	-146.0	24.857	105.3	0.019	50.2	0.284	-116.1
0.2	0.586	-165.8	12.845	94.5	0.026	59.6	0.204	-129.9
0.3	0.576	-171.9	8.681	89.7	0.041	73.2	0.199	-138.7
0.4	0.561	-176.3	6.541	86.3	0.048	77.8	0.200	-140.1
0.5	0.550	179.9	5.209	83.5	0.060	81.4	0.196	-137.0
0.6	0.540	178.2	4.358	82.2	0.069	82.0	0.182	-137.6
0.7	0.538	175.7	3.772	80.6	0.086	84.2	0.216	-131.0
0.8	0.521	174.6	3.332	78.4	0.099	85.1	0.210	-130.5
0.9	0.510	173.2	3.037	77.0	0.113	85.4	0.222	-122.2
1.0	0.524	168.5	2.780	76.9	0.119	83.5	0.198	-120.1
1.1	0.502	165.2	2.680	75.3	0.136	86.8	0.213	-114.9
1.2	0.489	165.9	2.718	72.3	0.156	83.5	0.246	-114.9
1.3	0.488	161.1	2.578	63.0	0.177	85.5	0.251	-122.8
1.4	0.472	157.9	2.213	58.7	0.184	81.8	0.209	-127.2
1.5	0.480	155.3	2.012	57.8	0.194	85.3	0.252	-114.1
1.6	0.470	153.4	1.846	57.2	0.219	82.2	0.242	-117.6
1.7	0.465	151.1	1.745	56.5	0.235	82.4	0.240	-112.9
1.8	0.464	149.5	1.677	54.9	0.248	79.0	0.263	-121.9
1.9	0.460	147.9	1.571	53.3	0.249	78.6	0.281	-120.0
2.0	0.466	146.0	1.514	52.3	0.264	77.4	0.276	-124.0

[MEMO]

- **The information in this document is current as of September, 2001. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC's data sheets or data books, etc., for the most up-to-date specifications of NEC semiconductor products. Not all products and/or types are available in every country. Please check with an NEC sales representative for availability and additional information.**
 - No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC. NEC assumes no responsibility for any errors that may appear in this document.
 - NEC does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC semiconductor products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC or others.
 - Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
 - While NEC endeavours to enhance the quality, reliability and safety of NEC semiconductor products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC semiconductor products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment, and anti-failure features.
 - NEC semiconductor products are classified into the following three quality grades:
 "Standard", "Special" and "Specific". The "Specific" quality grade applies only to semiconductor products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of a semiconductor product depend on its quality grade, as indicated below. Customers must check the quality grade of each semiconductor product before using it in a particular application.
 "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
 "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
 "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.
- The quality grade of NEC semiconductor products is "Standard" unless otherwise expressly specified in NEC's data sheets or data books, etc. If customers wish to use NEC semiconductor products in applications not intended by NEC, they must contact an NEC sales representative in advance to determine NEC's willingness to support a given application.
- (Note)
- (1) "NEC" as used in this statement means NEC Corporation and also includes its majority-owned subsidiaries.
 - (2) "NEC semiconductor products" means any semiconductor product developed or manufactured by or for NEC (as defined above).