


**CD54/74FCT640, CD54/74FCT640AT
CD54/74FCT643, CD54/74FCT643AT**

July 1990



Octal Bus Transceivers, 3-State

CD54/74FCT640, CD54/74FCT640AT - Inverting

CD54/74FCT643, CD54/74FCT643AT - True-Inverting

Type Features:

- Buffered Inputs
- Typical propagation delay:
6ns @ VCC = 5V, TA = +25°C, CL = 50pF (FCT640, FCT643)

The CD54/74FCT640, 640AT, 643 and 643AT use a small-geometry BiCMOS technology. The output stage is a combination of bipolar and CMOS transistors that limits the output-HIGH level to two diode drops below VCC. This resultant lowering of output swing (0V to 3.7V) reduces power bus ringing (a source of EMI) and minimizes VCC bounce and ground bounce and their effects during simultaneous output switching. The output configuration also enhances switching speed and is capable of sinking 48 to 64 milliamperes.

These octal bus transceivers are designed for asynchronous two-way communication between data buses.

The CD54/74FCT640, 640AT are octal inverting buffers; the CD54/74FCT643, 643AT are octal true/inverting buffers.

The direction of data flow (A to B, B to A) is controlled by the DIR input.

Outputs are enabled by a low on the Output Enable input (\bar{OE}); a high \bar{OE} puts these devices in the high-impedance mode.


The CD54/74FCT640, 640AT, 643 and 643AT are supplied in 20-lead dual-in-line plastic packages (E suffix) and in 20-lead dual-in-line small-outline plastic packages (M suffix). Both package types are operable over two temperature ranges: Commercial (0°C to +70°C) and Extended Industrial (-55°C to +125°C).

The CD54FCT640 and 643 are also available in chip form (H suffix). These unpackaged devices are operable over the -55°C to +125°C temperature range.

Family Features:

- SCR-latchup-resistant BiCMOS process and circuit design
- FCTXXX - Speed of bipolar FAST*/AS/S;
FCTXXXAT - 30% faster than FAST/AS/S with significantly reduced power consumption
- 64/48-mA output sink current (commercial/extended industrial)
- Output voltage swing limited to 3.7V @ VCC = 5V
- Controlled output-edge rates
- Input/output isolation to VCC
- BiCMOS technology with low quiescent power

* FAST is a registered trademark of Fairchild Semiconductor Corp.



TRUTH TABLE

CONTROL INPUTS		FCT640, 640AT		FCT643, 643AT	
		DATA PORT STATUS		DATA PORT STATUS	
OE	DIR	An	Bn	An	Bn
L	L	O	I	O	I
H	H	Z	Z	Z	Z
H	L	Z	Z	Z	Z
L	H	I	O	I	O

To prevent excess currents in the High-Z modes, all I/O terminals should be terminated with $10\text{k}\Omega$ to $1\text{M}\Omega$ resistors.

H = HIGH

L = LOW

I = Input

O = Output (Same Level as Input)

\bar{O} = Output (Inversion of Input Level)

Z = High Impedance

MAXIMUM RATINGS, Absolute-Maximum Values:

DC SUPPLY-VOLTAGE (VCC)	-0.5V to 6V
DC INPUT DIODE CURRENT, IIK (for $VI < -0.5\text{V}$)	-20mA
DC OUTPUT DIODE CURRENT, IOK (for $VO < -0.5\text{V}$)	-50mA
DC OUTPUT SINK CURRENT per Output Pin, IO	+70mA
DC OUTPUT SOURCE CURRENT per Output Pin, IO	-30mA
DC VCC CURRENT (ICC)	140mA
DC GROUND CURRENT (IGND)	528mA

POWER DISSIPATION PER PACKAGE (PD)

For $TA = -55^\circ\text{C}$ to $+100^\circ\text{C}$ (PACKAGE TYPE E)	500mW
For $TA = +100^\circ\text{C}$ to $+125^\circ\text{C}$ (PACKAGE TYPE E)	Derate Linearly at $8\text{mW}/^\circ\text{C}$ to 300mW

For $TA = -55^\circ\text{C}$ to $+70^\circ\text{C}$ (PACKAGE TYPE M)	400mW
For $TA = +70^\circ\text{C}$ to $+125^\circ\text{C}$ (PACKAGE TYPE M)	Derate Linearly at $6\text{mW}/^\circ\text{C}$ to 70mW

OPERATING-TEMPERATURE RANGE (TA):

PACKAGE TYPE E, M	-55°C to +125°C
STORAGE TEMPERATURE (T_{stg})	-65°C to +150°C

LEAD TEMPERATURE (DURING SOLDERING):

At distance $1/16$ in. $\pm 1/32$ in. ($1.59\text{mm} \pm 0.79\text{mm}$) from case for 10s maximum	+265°C
Unit inserted into PC board min. thickness $1/16$ in. (1.59mm) with solder contacting lead tips only	+300°C

RECOMMENDED OPERATING CONDITIONS:

The following are normal operating ranges for these devices. For maximum reliability, devices should always be operated within these ranges.

CHARACTERISTIC	LIMITS		UNITS
	MIN	MAX	
Supply-Voltage Range, VCC*: CD74 Series, TA = 0°C to 70°C	4.75	5.25	V
CD54 Series, TA = -55°C to +125°C	4.5	5.5	V
DC Input Voltage, VI	0	VCC	V
DC Output Voltage, VO	0	\leq VCC	V
Operating Temperature, TA	-55	+125	°C
Input Rise and Fall Slew Rate, dt/dv	0	10	ns/V

* Unless otherwise specified, all voltages are referenced to ground.

STATIC ELECTRICAL CHARACTERISTICS

FCT Series: 74FCT Commercial Temperature Range, 0°C to +70°C; VCC max = 5.25V, VCC min = 4.75V
 54FCT Extended Industrial Temperature Range, -55°C to +125°C; VCC max = 5.5V, VCC min = 4.5V

CHARACTERISTICS		TEST CONDITIONS		VCC (V)	AMBIENT TEMPERATURE (TA)						UNITS
					+25°C		0°C to +70°C		-55°C to +125°C		
VI (V)	IO (mA)	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
High-Level Input Voltage	VIH			4.5 to 5.5	2	-	2	-	2	-	V
Low-Level Input Voltage	VIL			4.5 to 5.5	-	0.8	-	0.8	-	0.8	V
High-Level Output Voltage	VOH	VIH or	-15	MIN	2.4	-	2.4	-	-	-	V
		VIL	-12	MIN	2.4	-	-	-	2.4	-	V
Low-Level Output Voltage	VOL	VIH or	64	MIN	-	0.55	-	0.55	-	-	V
		VIL	48	MIN	-	0.55	-	-	-	0.55	V
High-Level Input Current	I _H	VCC		MAX	-	0.1	-	1	-	1	μA
Low-Level Input Current	I _L	GND		MAX	-	-0.1	-	-1	-	-1	μA
3-State Leakage Current	IOZH	VCC		MAX	-	0.5	-	10	-	10	μA
	IOZL	GND		MAX	-	-0.5	-	-10	-	-10	μA
Short-Circuit Output Current *	IOS	VCC or GND VO = 0		MAX	-60	-	-60	-	-60	-	mA
Input Clamp Voltage	VIK	VCC or GND	-18	MIN	-	-1.2	-	-1.2	-	-1.2	V
Quiescent Supply Current, MSI	ICC	VCC or GND	0	MAX	-	8	-	80	-	500	μA
Additional Quiescent Supply Current per Input Pin TTL Inputs High, 1 Unit Load	ΔICC	3.4V†		MAX	-	1.6	-	1.6	-	2	mA


* Not more than one output should be shorted at one time. Test duration should not exceed 100ms.

† Inputs that are not measured are at VCC or GND.

FCT Input Loading: All inputs are 1 unit load. Unit load is ΔICC limit specified in Static Characteristics Chart, e.g., 1.6mA max. @ +70°C.


CD54/74FCT640, CD54/74FCT640AT TYPES

CD54/74FCT643, CD54/74FCT643AT TYPES



TERMINAL ASSIGNMENT

IEC LOGIC SYMBOL



TERMINAL ASSIGNMENT

IEC LOGIC SYMBOL

SWITCHING CHARACTERISTICS

FCT Series: tr, tf = 2.5ns, CL = 50pF, RL - See Figure 3

CHARACTERISTICS	SYMBOL	V _{CC} (V)	CD54/74FCT640, 643						CD54/74FCT640AT, 643AT						UNITS		
			AMBIENT TEMPERATURE (T _A)														
			+25°C		0°C to +70°C		-55°C to +125°C		+25°C		0°C to +70°C		-55°C to +125°C				
			TYP	MIN	MAX	MIN	MAX	TYP	MIN	MAX	MIN	MAX	MIN	MAX			
Prop. Delays: Data to Outputs	640/AT An→Bn, 640/AT Bn→An, 643/AT An→Bn	tPLH, tPHL	5†	6	2	7	2	8								ns	
	643/AT Bn→An,	tPLH, tPHL	5†	4.9	2	6.5	2	7								ns	
Output Disable to Output	640/AT	tPLZ, tPHZ	5	7	2	10	2	12								ns	
	643/AT	tPLZ, tPHZ	5	7.5	2	10	2	12								ns	
Output Enable to Output	640/AT	tPZL, tPZH	5	11	2	13	2	16								ns	
	643/AT	tPZL, tPZH	5	9.8	2	13	2	16								ns	
Power Dissipation Capacitance	CPD \$	-														pF	
Min. (Valley) VCHV During Switching of Other Outputs (Output Under Not Switching)	VCHV See Test Figure 1	5														V	
Max. (Peak) VOLP During Switching of Other Outputs (Output Under Test Not Switching)	VOLP See Figure 1	5														V	
Input Capacitance	C _I		-	-	10	-	10	-	-	10	-	10	-	10		pF	
Input/Output Capacitance	C _{I/O}		-	-	15	-	15	-	-	15	-	15	-	15		pF	

†5V: min. is @ 5.5V
max. is @ 4.5V5V: min. is @ 5.25V for 0°C to +70°C
max. is @ 4.75V for 0°C to +70°C
typ. is @ 5V

§CPD, measured per function, is used to determine the dynamic power consumption.

PD (per package) = V_{CC} ICC + Σ (V_{CC}² f_i CPD + V_O² f_o CL + V_{CC} ΔICC D) where:V_{CC} = supply voltage


ΔICC = flow through current x unit load

CL = output load capacitance

D = duty cycle of input high

f_o = output frequencyf_i = input frequency

PARAMETER MEASUREMENT INFORMATION



NOTES:

1. VOLP is measured with respect to a ground reference near the output under test. VOHV is measured with respect to VOH.
2. Input pulses have the following characteristics:
PRR \leq 1MHz, tr = 2.5ns, tf = 2.5ns, skew 1ns.
3. R.F. fixture with 700-MHz design rules required. IC should be soldered into test board and bypassed with 0.1 μ F capacitor. Scope and probes require 700-MHz bandwidth.

Figure 1 - Simultaneous switching transient waveforms.






Figure 2 - Propagation delay times.



TEST	SWITCH POSITION
tPLZ, tPZL, OPEN DRAIN	CLOSED
tPHZ, tPZH, tPLH, tPHL	OPEN

Figure 3 - Three-state propagation delay times and test circuit.