

# Z-PACK | Z-PACK 2mm HM

TE Internal #: 5352009-1

Hard Metric Backplane Connectors, PCB Mount Receptacle, ≤1 Gb

/s, 19 Column, 5 Row, Mezzanine, 95 Position, 2.54 mm [.1 in]

Centerline, Z-PACK 2mm HM

View on TE.com >



Connectors > PCB Connectors > Backplane Connectors > Hard Metric Backplane Connectors >


HM Receptacle Connector: Traditional Backplane, Coplanar, 2mm











PCB Connector Assembly Type: PCB Mount Receptacle

Data Rate: ≤1 Gb/s

Number of Columns: 19

Number of Rows: 5

Backplane Architecture: Mezzanine

All HM Receptacle Connector: Traditional Backplane, Coplanar, 2mm (48)

# **Features**

# **Product Type Features**

Backplane Interface Type	2mm HM
PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector & Contact Terminates To	Printed Circuit Board

# **Configuration Features**

Rows Loaded	A, B, C, D, E
Number of Columns	19
Number of Rows	5
Backplane Architecture	Mezzanine
Number of Positions	95
PCB Mount Orientation	Right Angle



# Cianal Clas

Signal Characteristics	
Crosstalk Version	Standard
Data Rate	≤1 Gb/s
Body Features	
Primary Product Color	Gray
Contact Features	
Feedthrough Post Length	3.7 mm
CompactPCI Designation	None
Contact Type	Socket
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold, Gold Flash over Palladium Nickel
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Contact Current Rating (Max)	1.5 A
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Polyester - GF
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Backplane Module Length	38 mm
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Shielded	No

Power & Signal

# **Industry Standards**

Circuit Application

UL Flammability Rating UL 94V-0



### **Packaging Features**

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability


#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts











TE Part # 6392175-1 Z-PACK/B-19 M-HDR 95POS TE Part # 6645305-1
2MM H.M. 5 + 2 ROW 19 COL. TYPE
"B" PIN

TE Part # 6645306-1
2MM H.M. 5 + 2 ROW 19 COL. TYPE
"B" PIN

# Also in the Series | Z-PACK 2mm HM



Backplane Connector Housings(4)



Backplane Power Connectors(6)



Board-to-Board Connector Contacts(2)



Connector Caps & Covers(62)



Connector Hardware(97)



Hard Metric Backplane Connectors (268)



High Speed Backplane Connectors(1)



Insertion & Extraction Tools(2)



# Customers Also Bought





















# **Documents**

# **Product Drawings**

Z-PACK/B19 RAF 95P

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_5352009-1\_A.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5352009-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5352009-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# **Product Specifications**

**Application Specification** 

English

**Product Environmental Compliance** 

MD\_5352009-1\_08092016642\_dmtec

English

MD\_5352009-1\_08092016642\_dmtec

English

Hard Metric Backplane Connectors, PCB Mount Receptacle, ≤1 Gb/s, 19 Column, 5 Row, Mezzanine, 95 Position, 2.54 mm [.1 in] Centerline, Z-PACK 2mm HM

