

# PRELIMINARY DATA SHEET

# NEC

## NPN SILICON EPITAXIAL TWIN TRANSISTOR

## UPA836TF

### FEATURES


- **LOW NOISE:**  
 Q1: NF = 1.5 dB TYP at f = 2 GHz, V<sub>CE</sub> = 3 V, I<sub>c</sub> = 3 mA  
 Q2: NF = 1.7 dB TYP at f = 2 GHz, V<sub>CE</sub> = 1 V, I<sub>c</sub> = 3 mA
- **HIGH GAIN:**  
 Q1: |S<sub>21E</sub>|<sup>2</sup> = 8.5 dB TYP at f = 2 GHz, V<sub>CE</sub> = 3 V, I<sub>c</sub> = 10 mA  
 Q2: |S<sub>21E</sub>|<sup>2</sup> = 3.5 dB TYP at f = 2 GHz, V<sub>CE</sub> = 1 V, I<sub>c</sub> = 3 mA
- **6-PIN THIN-TYPE SMALL MINI MOLD PACKAGE**
- **2 DIFFERENT BUILT-IN TRANSISTORS**  
 (Q1: NE685, Q2: NE688)

### DESCRIPTION

The UPA836TF has two different built-in transistors for low cost amplifier and oscillator applications up to L and S band. Low noise figures, high gain, high current capability, and medium output give this device high dynamic range and excellent linearity for two-stage amplifiers. This device is also ideally suited for use in a VCO/buffer amplifier application. The thinner package style allows for higher density designs.

### OUTLINE DIMENSIONS (Units in mm)

Package Outline TS06 (Top View)



#### PIN CONNECTIONS

1. Collector (Q1)
2. Emitter (Q1)
3. Collector (Q2)
4. Base (Q2)
5. Emitter (Q2)
6. Base (Q1)

#### Note:

Pin 1 is the lower left most pin as the package lettering is oriented and read left to right.

### ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C)

PART NUMBER PACKAGE OUTLINE				UPA836TF TS06		
	SYMBOLS	PARAMETERS AND CONDITIONS	UNITS	MIN	TYP	MAX
Q1	I <sub>CBO</sub>	Collector Cutoff Current at V <sub>CB</sub> = 5 V, I <sub>E</sub> = 0	μA			0.1
	I <sub>EBO</sub>	Emitter Cutoff Current at V <sub>EB</sub> = 1 V, I <sub>C</sub> = 0	μA			0.1
	h <sub>FE</sub>	DC Current Gain <sup>1</sup> at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 10 mA		75		150
	f <sub>r</sub>	Gain Bandwidth at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 10 mA, f = 2 GHz	GHz		12	
	C <sub>re</sub>	Feedback Capacitance <sup>2</sup> at V <sub>CB</sub> = 3 V, I <sub>E</sub> = 0, f = 1 MHz	pF		0.4	0.7
	S <sub>21E</sub>   <sup>2</sup>	Insertion Power Gain at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 10 mA, f = 2 GHz	dB	7	8.5	
	NF	Noise Figure at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 3 mA, f = 2 GHz	dB		1.5	2.5
Q2	I <sub>CBO</sub>	Collector Cutoff Current at V <sub>CB</sub> = 5 V, I <sub>E</sub> = 0	μA			0.1
	I <sub>EBO</sub>	Emitter Cutoff Current at V <sub>EB</sub> = 1 V, I <sub>C</sub> = 0	μA			0.1
	h <sub>FE</sub>	DC Current Gain <sup>1</sup> at V <sub>CE</sub> = 1 V, I <sub>C</sub> = 3 mA		100		145
	f <sub>r</sub>	Gain Bandwidth (1) at V <sub>CE</sub> = 1 V, I <sub>C</sub> = 3 mA, f = 2 GHz	GHz	4.0	4.5	
	f <sub>r</sub>	Gain Bandwidth (2) at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 20 mA, f = 2 GHz	GHz		9.0	
	C <sub>re</sub>	Feedback Capacitance <sup>2</sup> at V <sub>CB</sub> = 1 V, I <sub>E</sub> = 0, f = 1 MHz	pF		0.75	0.85
	S <sub>21E</sub>   <sup>2</sup>	Insertion Power Gain (1) at V <sub>CE</sub> = 1 V, I <sub>C</sub> = 3 mA, f = 2 GHz	dB	2.5	3.5	
	S <sub>21E</sub>   <sup>2</sup>	Insertion Power Gain (2) at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 20 mA, f = 2 GHz	dB		6.5	
	NF	Noise Figure (1) at V <sub>CE</sub> = 1 V, I <sub>C</sub> = 3 mA, f = 2 GHz	dB		1.7	2.5
NF	Noise Figure (2) at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 7 mA, f = 2 GHz	dB		1.5		





- Notes: 1. Pulsed measurement, pulse width ≤ 350 μs, duty cycle ≤ 2%.  
 2. Collector to base capacitance when measured with capacitance meter (automatic balanced bridge method), with emitter connected to guard pin of capacitance meter.

**ABSOLUTE MAXIMUM RATINGS<sup>1</sup>** (T<sub>A</sub> = 25°C)







SYMBOLS	PARAMETERS	UNITS	RATINGS	
			Q1	Q2
V <sub>CB0</sub>	Collector to Base Voltage	V	9	9
V <sub>CE0</sub>	Collector to Emitter Voltage	V	6	6
V <sub>EB0</sub>	Emitter to Base Voltage	V	2	2
I <sub>c</sub>	Collector Current	mA	30	100
P <sub>T</sub>	Total Power Dissipation	mW	150	150
			200 <sup>2</sup>	
T <sub>J</sub>	Junction Temperature	°C	150	150
T <sub>STG</sub>	Storage Temperature	°C	-65 to +150	

Note: 1. Operation in excess of any one of these parameters may result in permanent damage.  
 2. When operating both devices, the power dissipation for either device should not exceed 110 mW.







**TYPICAL PERFORMANCE CURVES** (T<sub>A</sub> = 25°C)





**TYPICAL PERFORMANCE CURVES** ( $T_A = 25^\circ\text{C}$ )



TYPICAL PERFORMANCE CURVES (TA = 25°C)



**TYPICAL PERFORMANCE CURVES** ( $T_A = 25^\circ\text{C}$ )



**TYPICAL SCATTERING PARAMETERS**

**Q1**

$V_{CE} = 3\text{ V}$ ,  $I_c = 1\text{ mA}$ ,  $Z_0 = 50\ \Omega$

FREQUENCY (GHz)	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.98	-5.93	2.38	172.32	0.02	85.76	1.00	-3.86
0.20	0.97	-11.90	2.36	165.08	0.04	81.15	0.99	-7.44
0.30	0.95	-18.17	2.39	158.35	0.06	76.27	0.97	-11.14
0.40	0.93	-24.00	2.35	151.83	0.07	72.22	0.96	-14.73
0.50	0.90	-30.10	2.35	145.70	0.09	68.30	0.94	-18.02
0.60	0.87	-36.17	2.33	140.22	0.10	64.18	0.92	-21.42
0.70	0.84	-42.49	2.30	134.45	0.12	60.68	0.89	-24.18
0.80	0.80	-48.69	2.29	129.32	0.13	56.90	0.87	-27.47
0.90	0.76	-55.28	2.29	123.53	0.14	53.94	0.84	-29.94
1.00	0.73	-61.26	2.24	118.31	0.15	51.07	0.81	-32.50
1.20	0.64	-74.79	2.19	108.30	0.16	45.85	0.76	-36.89
1.50	0.51	-96.77	2.10	93.80	0.18	39.24	0.69	-42.90
1.70	0.43	-112.09	2.00	84.74	0.19	36.24	0.65	-46.39
2.00	0.35	-138.38	1.84	72.75	0.19	32.40	0.60	-51.51
2.50	0.31	175.03	1.62	54.64	0.20	29.55	0.53	-59.91
3.00	0.35	140.64	1.41	40.02	0.21	28.96	0.47	-69.74

**Q2**

$V_{CE} = 3\text{ V}$ ,  $I_c = 1\text{ mA}$ ,  $Z_0 = 50\ \Omega$

FREQUENCY (GHz)	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.97	-14.32	2.42	166.29	0.04	80.18	0.99	-7.24
0.20	0.95	-28.41	2.36	154.31	0.07	70.77	0.96	-14.16
0.30	0.91	-42.45	2.34	143.61	0.10	62.19	0.91	-20.19
0.40	0.88	-55.88	2.25	133.74	0.13	54.42	0.87	-25.69
0.50	0.83	-69.17	2.21	124.69	0.14	48.08	0.81	-30.13
0.60	0.79	-81.80	2.14	116.51	0.16	42.00	0.77	-34.32
0.70	0.75	-93.67	2.06	108.52	0.17	37.41	0.72	-37.52
0.80	0.72	-104.67	1.98	101.49	0.17	33.30	0.68	-40.84
0.90	0.69	-115.37	1.91	94.57	0.18	29.92	0.65	-43.52
1.00	0.67	-124.80	1.81	88.40	0.18	27.31	0.62	-46.09
1.20	0.63	-142.25	1.66	77.30	0.18	23.77	0.57	-51.18
1.50	0.61	-163.80	1.46	63.16	0.17	22.24	0.51	-59.93
1.70	0.61	-175.60	1.35	54.92	0.16	24.02	0.48	-66.60
2.00	0.61	169.35	1.21	43.93	0.16	30.08	0.44	-78.77
2.50	0.64	149.69	1.02	28.22	0.19	41.91	0.39	-106.64
3.00	0.68	134.75	0.88	15.55	0.26	45.51	0.39	-141.18

## TYPICAL SCATTERING PARAMETERS

### Q1

VCE = 3 V, Ic = 3 mA, Z0 = 50 Ω

FREQUENCY (GHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.94	-9.29	6.55	168.08	0.02	84.10	0.98	-6.91
0.20	0.90	-18.39	6.32	157.85	0.04	76.93	0.95	-13.21
0.30	0.85	-27.47	6.21	148.76	0.05	71.79	0.91	-18.80
0.40	0.80	-36.15	5.98	140.53	0.06	66.81	0.86	-23.80
0.50	0.74	-44.62	5.77	133.00	0.07	63.60	0.81	-27.41
0.60	0.67	-52.69	5.51	126.23	0.08	60.13	0.76	-31.19
0.70	0.60	-60.71	5.28	119.27	0.09	58.07	0.72	-33.67
0.80	0.54	-68.45	5.03	113.12	0.10	55.93	0.68	-36.31
0.90	0.47	-75.60	4.76	107.23	0.11	54.62	0.64	-38.10
1.00	0.42	-82.57	4.50	101.99	0.11	53.45	0.61	-39.74
1.20	0.32	-96.78	4.02	92.52	0.13	51.59	0.56	-42.63
1.50	0.21	-122.39	3.42	80.83	0.15	49.61	0.50	-46.74
1.70	0.17	-143.90	3.10	74.15	0.16	48.63	0.46	-49.50
2.00	0.16	179.12	2.70	64.83	0.18	46.70	0.42	-54.02
2.50	0.22	136.13	2.24	51.62	0.21	43.76	0.36	-63.34
3.00	0.29	115.80	1.89	39.81	0.23	40.27	0.31	-75.36

### Q2

VCE = 3 V, Ic = 3 mA, Z0 = 50 Ω

FREQUENCY (GHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.91	-20.77	6.78	160.00	0.04	76.08	0.95	-14.28
0.20	0.84	-40.45	6.30	145.15	0.06	64.72	0.86	-26.08
0.30	0.76	-59.61	5.98	132.53	0.08	56.56	0.75	-34.42
0.40	0.69	-77.35	5.54	121.70	0.10	50.58	0.66	-41.09
0.50	0.62	-93.52	5.09	112.12	0.11	47.02	0.58	-45.13
0.60	0.57	-107.23	4.61	114.36	0.12	44.57	0.51	-48.78
0.70	0.53	-119.29	4.20	97.25	0.12	43.10	0.46	-51.09
0.80	0.50	-129.99	3.84	91.32	0.13	42.46	0.42	-53.42
0.90	0.48	-139.30	3.51	85.88	0.13	41.93	0.38	-55.21
1.00	0.47	-147.65	3.25	80.98	0.14	42.00	0.36	-56.92
1.20	0.46	-161.91	2.80	72.45	0.15	42.33	0.31	-60.52
1.50	0.46	-179.07	2.33	61.22	0.17	43.12	0.25	-67.97
1.70	0.47	171.72	2.10	54.61	0.18	43.54	0.21	-74.72
2.00	0.49	160.12	1.83	45.19	0.21	44.70	0.17	-89.34
2.50	0.54	144.71	1.52	31.01	0.25	42.00	0.13	-132.57
3.00	0.59	132.90	1.29	18.97	0.30	38.08	0.17	-179.42

## TYPICAL SCATTERING PARAMETERS

### Q1

VCE = 3 V, IC = 5 mA, Z0 = 50 Ω

FREQUENCY (GHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.90	-12.12	10.05	165.07	0.02	82.08	0.97	-9.12
0.20	0.84	-23.51	9.49	152.86	0.03	74.99	0.92	-17.06
0.30	0.77	-34.84	9.08	142.06	0.05	69.42	0.85	-23.23
0.40	0.69	-45.03	8.52	132.57	0.06	65.57	0.78	-28.22
0.50	0.60	-54.58	7.94	123.96	0.07	63.02	0.72	-31.57
0.60	0.52	-62.89	7.32	116.79	0.08	60.80	0.66	-34.45
0.70	0.44	-70.48	6.74	109.99	0.08	59.78	0.62	-36.34
0.80	0.38	-77.63	6.21	104.22	0.09	58.73	0.58	-38.08
0.90	0.32	-84.12	5.71	99.08	0.10	57.98	0.55	-39.38
1.00	0.28	-90.92	5.28	94.41	0.11	57.45	0.53	-40.58
1.20	0.20	-105.44	4.56	86.53	0.12	56.41	0.48	-42.73
1.50	0.13	-137.90	3.78	76.56	0.14	54.85	0.43	-46.37
1.70	0.11	-167.88	3.39	70.79	0.15	53.69	0.40	-49.23
2.00	0.13	152.80	2.93	62.58	0.18	51.42	0.37	-54.00
2.50	0.21	121.76	2.41	50.64	0.21	47.56	0.31	-64.32
3.00	0.28	107.74	2.03	39.80	0.24	42.91	0.26	-78.22

### Q2

VCE = 3 V, IC = 5 mA, Z0 = 50 Ω

FREQUENCY (GHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.84	-26.28	10.60	155.28	0.03	73.62	0.91	-19.87
0.20	0.75	-50.58	9.48	138.37	0.06	62.12	0.77	-34.36
0.30	0.64	-73.48	8.58	124.39	0.07	55.68	0.63	-43.20
0.40	0.56	-93.24	7.56	113.09	0.08	52.30	0.53	-49.31
0.50	0.49	-109.26	6.59	104.26	0.09	50.89	0.45	-52.83
0.60	0.45	-122.23	5.76	97.42	0.10	50.06	0.39	-55.78
0.70	0.43	-133.23	5.10	91.52	0.11	49.97	0.34	-57.54
0.80	0.41	-142.94	4.57	86.44	0.12	50.11	0.31	-59.42
0.90	0.40	-151.05	4.13	81.93	0.13	50.05	0.27	-60.94
1.00	0.40	-158.37	3.78	77.69	0.13	50.37	0.25	-62.43
1.20	0.40	-170.84	3.22	70.16	0.15	50.44	0.20	-66.17
1.50	0.41	174.38	2.64	60.16	0.18	49.56	0.15	-75.30
1.70	0.43	166.51	2.37	54.26	0.20	48.51	0.12	-85.04
2.00	0.45	156.30	2.05	45.69	0.23	46.68	0.08	-111.15
2.50	0.51	142.45	1.69	32.37	0.28	41.96	0.09	-179.51
3.00	0.56	131.71	1.44	20.88	0.32	36.35	0.17	146.82

## TYPICAL SCATTERING PARAMETERS

### Q1

V<sub>CE</sub> = 3 V, I<sub>c</sub> = 10 mA, Z<sub>0</sub> = 50 Ω

FREQUENCY (GHz)	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.82	-17.52	16.52	159.99	0.02	80.28	0.94	-12.68
0.20	0.72	-33.22	14.93	144.21	0.03	72.82	0.85	-22.43
0.30	0.60	-46.83	13.32	131.03	0.04	68.07	0.75	-28.43
0.40	0.49	-57.62	11.65	120.45	0.05	65.62	0.67	-32.14
0.50	0.40	-65.90	10.15	112.22	0.06	65.03	0.60	-34.25
0.60	0.33	-72.93	8.90	105.22	0.07	63.86	0.56	-35.78
0.70	0.27	-79.33	7.89	100.37	0.08	63.74	0.52	-36.80
0.80	0.22	-85.38	7.07	95.73	0.08	63.50	0.49	-37.69
0.90	0.18	-91.73	6.39	91.61	0.09	63.16	0.46	-38.46
1.00	0.15	-98.81	5.83	87.88	0.10	62.77	0.45	-39.30
1.20	0.10	-118.22	4.95	81.32	0.11	61.85	0.41	-41.01
1.50	0.07	-176.19	4.05	72.83	0.14	59.79	0.38	-44.69
1.70	0.08	149.79	3.61	67.81	0.15	58.31	0.35	-47.69
2.00	0.13	125.94	3.12	60.46	0.18	55.55	0.32	-53.15
2.50	0.21	109.57	2.54	49.58	0.22	50.37	0.27	-65.07
3.00	0.29	100.79	2.14	39.46	0.25	45.03	0.21	-81.46

### Q2

V<sub>CE</sub> = 3 V, I<sub>c</sub> = 10 mA, Z<sub>0</sub> = 50 Ω

FREQUENCY (GHz)	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.70	-38.41	18.28	146.82	0.03	69.80	0.82	-29.66
0.20	0.56	-71.49	14.88	126.35	0.05	61.45	0.61	-46.31
0.30	0.45	-97.54	11.94	112.07	0.06	58.70	0.46	-54.40
0.40	0.39	-116.40	9.67	102.58	0.07	58.67	0.37	-59.06
0.50	0.35	-130.54	8.00	95.72	0.08	59.11	0.30	-61.94
0.60	0.34	-141.64	6.81	90.48	0.09	59.40	0.26	-64.34
0.70	0.33	-150.51	5.91	85.85	0.10	59.73	0.22	-65.99
0.80	0.33	-158.31	5.24	81.79	0.11	59.53	0.19	-68.05
0.90	0.33	-164.94	4.70	78.04	0.12	59.10	0.16	-70.00
1.00	0.33	-170.77	4.27	74.52	0.14	58.94	0.14	-72.05
1.20	0.34	179.29	3.60	68.08	0.16	57.53	0.11	-78.53
1.50	0.37	167.43	2.93	59.24	0.19	54.68	0.06	-101.03
1.70	0.39	160.78	2.62	53.77	0.21	52.45	0.05	-135.60
2.00	0.42	152.28	2.26	45.88	0.25	48.84	0.06	168.53
2.50	0.48	140.09	1.85	33.78	0.30	41.93	0.14	138.30
3.00	0.54	130.31	1.57	22.81	0.34	34.93	0.22	124.44



## TYPICAL SCATTERING PARAMETERS

### Q2

V<sub>CE</sub> = 3 V, I<sub>c</sub> = 7 mA, Z<sub>0</sub> = 50 Ω

FREQUENCY (GHz)	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.78	-31.29	13.97	151.51	0.03	71.78	0.87	-24.42
0.20	0.66	-59.66	12.04	132.90	0.05	60.97	0.70	-40.28
0.30	0.54	-84.82	10.35	118.21	0.07	56.44	0.55	-48.33
0.40	0.47	-104.53	8.72	107.56	0.08	55.05	0.45	-54.30
0.50	0.42	-119.83	7.38	99.69	0.09	54.45	0.37	-57.44
0.60	0.39	-132.03	6.34	93.65	0.10	54.56	0.32	-60.00
0.70	0.37	-142.05	5.56	88.39	0.11	54.88	0.28	-61.66
0.80	0.36	-150.83	4.94	83.86	0.11	55.01	0.24	-63.45
0.90	0.36	-158.17	4.45	79.83	0.12	55.07	0.21	-65.04
1.00	0.36	-164.78	4.05	75.94	0.13	55.03	0.19	-66.66
1.20	0.37	-175.89	3.43	69.04	0.15	54.31	0.15	-71.21
1.50	0.39	170.80	2.80	59.72	0.19	52.52	0.10	-83.83
1.70	0.40	163.55	2.51	54.06	0.21	50.73	0.07	-100.27
2.00	0.43	154.21	2.17	45.65	0.24	47.90	0.05	-148.70
2.50	0.49	141.28	1.78	33.14	0.29	41.96	0.11	152.83
3.00	0.55	131.03	1.51	21.87	0.33	35.50	0.19	132.79

### Q2

V<sub>CE</sub> = 3 V, I<sub>c</sub> = 20 mA, Z<sub>0</sub> = 50 Ω

FREQUENCY (GHz)	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.51	-57.90	27.75	136.02	0.02	69.14	0.70	-39.87
0.20	0.37	-97.17	19.04	114.46	0.04	64.83	0.46	-56.12
0.30	0.31	-120.97	13.81	103.21	0.05	65.82	0.33	-62.80
0.40	0.29	-137.00	10.72	95.92	0.06	66.30	0.26	-66.88
0.50	0.28	-148.56	8.73	90.60	0.08	66.42	0.21	-69.42
0.60	0.28	-157.11	7.34	86.37	0.09	66.46	0.17	-72.27
0.70	0.28	-164.14	6.36	82.37	0.10	66.07	0.14	-74.72
0.80	0.29	-170.13	5.60	78.94	0.11	65.59	0.12	-78.14
0.90	0.29	-175.24	5.00	75.67	0.13	64.35	0.10	-82.37
1.00	0.30	-179.80	4.54	72.57	0.14	63.61	0.08	-87.43
1.20	0.32	172.24	3.81	66.74	0.16	61.26	0.05	-106.92
1.50	0.34	162.54	3.09	58.59	0.20	57.09	0.04	-169.73
1.70	0.37	156.95	2.75	53.51	0.22	54.21	0.06	160.94
2.00	0.40	149.52	2.37	46.16	0.26	46.16	0.11	140.92
2.50	0.46	138.42	1.94	34.42	0.31	34.42	0.19	127.04
3.00	0.52	129.12	1.63	23.88	0.35	23.88	0.27	117.03

**NONLINEAR MODEL**

**BJT NONLINEAR MODEL PARAMETERS(1)**

Parameters	Q1	Q2	Parameters	Q1	Q2
IS	7e-16	3.8e-16	MJC	0.34	0.48
BF	109	135.7	XCJC	0	0.56
NF	1	1	CJS	0	0
VAF	15	28	VJS	0.75	0.75
IKF	0.19	0.6	MJS	0	0
ISE	7.9e-13	3.8e-15	FC	0.5	0.75
NE	2.19	1.49	TF	2e-12	11e-12
BR	1	12.3	XTF	5.2	0.36
NR	1.08	1.1	VTF	4.58	0.65
VAR	12.4	3.5	ITF	0.01	0.61
IKR	Infinity	0.06	PTF	0	50
ISC	0	3.5e-16	TR	1e-9	32e-12
NC	2	1.62	EG	1.11	1.11
RE	1.3	0.4	XTB	0	0
RB	10	6.14	XTI	3	3
RBM	8.34	3.5	KF	0	1.5e-14
IRB	0.009	0.001	AF	1	1.22
RC	10	4.2			
CJE	0.4e-12	0.796e-12			
VJE	0.81	0.71			
MJE	0.5	0.38			
CJC	0.18e-12	0.549e-12			
VJC	0.75	0.65			

(1) Gummel-Poon Model

**UNITS**

Parameter	Units
time	seconds
capacitance	farads
inductance	henries
resistance	ohms
voltage	volts
current	amps

**MODEL RANGE**


Frequency: 0.1 to 3.0 GHz  
 Bias: VCE = 0.5 V to 5 V, IC = 1 mA to 10 mA  
 Date: 10/98

**Note:**

This nonlinear model utilized the latest data available. See our Design Parameter Library at [www.cel.com](http://www.cel.com) for this data.

**NONLINEAR MODEL**

**SCHEMATIC**



**MODEL RANGE**

Frequency: 0.1 to 3.0 GHz  
 Bias:  $V_{CE} = 0.5 \text{ V to } 5 \text{ V}$ ,  $I_C = 1 \text{ mA to } 10 \text{ mA}$   
 Date: 10/98

**BUILT-IN TRANSISTORS**

	Q1	Q2
3-pin small mini mold part No.	NE68530	NE68830

**ORDERING INFORMATION**

PART NUMBER	QUANTITY	PACKAGING
UPA836TF-T1	3000	Tape & Reel

The UPA833TF features the Q1 and Q2 in inverted positions.

EXCLUSIVE NORTH AMERICAN AGENT FOR **NEC** RF, MICROWAVE & OPTOELECTRONIC SEMICONDUCTORS

**CEL CALIFORNIA EASTERN LABORATORIES** • Headquarters • 4590 Patrick Henry Drive • Santa Clara, CA 95054-1817 • (408) 988-3500 • Telex 34-6393 • FAX (408) 988-0279  
 24-Hour Fax-On-Demand: 800-390-3232 (U.S. and Canada only) • Internet: <http://WWW.CEL.COM>

DATA SUBJECT TO CHANGE WITHOUT NOTICE

PRINTED IN USA ON RECYCLED PAPER -2/99