

Male headers soldering technique

"dimensions A + B" changeable

one row, □ 0.635 mm

| art. no. | dim. [mm] | | | art. no. | dim. [mm] | | |
|-------------------------|---|-------|------|---|-----------|-------|------|
| | A | B | C | | A | B | C |
| SLK 3 025 ... | 4.50 | 3.00 | 3.00 | SL 3 131 ... | 14.60 | 13.10 | 5.80 |
| SL 3 025 ... | 4.50 | 3.00 | 5.80 | SL 3 152 ... | 16.70 | 15.20 | 5.80 |
| SL 3 053 ... | 6.90 | 5.40 | 5.80 | SL 3 182 ... | 19.70 | 18.20 | 5.80 |
| SL 3 080 ... | 9.50 | 8.00 | 5.80 | SL 3 207 ... | 22.20 | 20.70 | 5.80 |
| SL 3 101 ... | 11.60 | 10.10 | 5.80 | | | | |
| please indicate: | ... no. of contacts one row 1-36 | | | ... surface S = selective gold-plated G = gold-plated Z = tin-plated | | | |

The surface of dimension "C" of following articles is selective gold-plated: SLK 3 025 ... S, SL 3 025 ... S.

two rows, □ 0.635 mm

| art. no. | dim. [mm] | | | art. no. | dim. [mm] | | |
|-------------------------|--|------|------|---|-----------|-------|------|
| | A | B | C | | A | B | C |
| SLK 4 025 ... | 4.50 | 3.00 | 3.00 | SL 4 101 ... | 11.60 | 10.10 | 5.80 |
| SL 4 025 ... | 4.50 | 3.00 | 5.80 | SL 4 152 ... | 16.70 | 15.20 | 5.80 |
| please indicate: | ... no. of contacts two rows 2-72 | | | ... surface S = selective gold-plated G = gold-plated Z = tin-plated | | | |

The surface of dimension "C" of following articles is selective gold-plated: SLK 4 025 ... S, SL 4 025 ... S.

V-notches permit breaking! Therefore any required number of contacts is available.
Every pin length is available on request.

IDC-connectors → H 1 - 14
Female headers 2.54 solder → G 27
Female headers 2.54 SMD → G 46 - 49
Fem. head. 2.54 solder, put through → G 29

Special male & female headers → G 19
High-prec. fem. headers 2.54 sold. → G 31 - 34
High-prec. male head.in SMD mount. → G 35
Technical data → G 75 - 80

G 10

A

B

C

D

E

F

G

H

I

K

L

M

N