


角型フレームタイプLED



Lead Frame Type LEDs

Ta=25°C

| 機種名<br>Type No. | 外觀図<br>Drawing No | 波長<br>Peak Wave-length<br>nm (Color) | 樹脂外觀<br>Lens Appearance | 絶対最大定格 Absolute Maximum Ratings |    |    |        | 電気的光学的特性 Electro Optical Characteristics |    |              |              |               |
|-----------------|-------------------|--------------------------------------|-------------------------|---------------------------------|----|----|--------|--|----|--------------|--------------|---------------|
|                 |                   |                                      |                         | IF                              | VR | Pd | ToPr   | Vf Typ.                                  | IF | Luminous Typ | Intensity IF | Ir Max        |
|                 |                   |                                      |                         | mA                              | V  | mW | °C     | V  | mA | mcd          | mA           | (VR=3V)<br>μA |
| SLP-174B-51     | P-10              | 700 (R)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 1.9                                      | 5  | 0.55         | 5            | 10            |
| SLP-274B-51     | P-10              | 565 (G)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 1.5          | 20           | 10            |
| SLP-474B-51     | P-10              | 585 (Y)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 2.5          | 20           | 10            |
| SLP-175B-51     | P-11              | 700 (R)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 1.9                                      | 5  | 0.65         | 5            | 10            |
| SLP-275B-51     | P-11              | 565 (G)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 1.5          | 20           | 10            |
| SLP-475B-51     | P-11              | 585 (Y)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 2.0          | 20           | 10            |
| SLP-159B-51     | P-12              | 700 (R)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 1.9                                      | 5  | 0.6          | 5            | 10            |
| SLP-259B-51     | P-12              | 565 (G)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 1.2          | 20           | 10            |
| SLP-459B-51     | P-12              | 585 (Y)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 1.5          | 20           | 10            |
| ○SLP-153B-51    | P-13              | 700 (R)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 1.9                                      | 5  | (0.7)        | 5            | 10            |
| ○SLP-253B-51    | P-13              | 565 (G)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | (1.5)        | 20           | 10            |
| ○SLP-453B-51    | P-13              | 585 (Y)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | (2.0)        | 20           | 10            |
| SLP-183B-51     | P-14              | 700 (R)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 1.9                                      | 5  | 0.55         | 5            | 10            |
| SLP-283B-51     | P-14              | 565 (G)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 1.5          | 20           | 10            |
| SLP-483B-51     | P-14              | 585 (Y)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 4.0          | 20           | 10            |
| SLP-155B-51     | P-15              | 700 (R)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 1.9                                      | 5  | 1.0          | 5            | 10            |
| SLP-255B-51     | P-15              | 565 (G)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 1.2          | 20           | 10            |
| SLP-455B-51     | P-15              | 585 (Y)                              | Color Diffused          | 25                              | 3  | 70 | -25~80 | 2.1                                      | 20 | 3.0          | 20           | 10            |

○印 企画中

Tolerance : ±0.2  
Unit : mm

