



SPECIFICATIONS

Current Rating: 2A AC,DC
 Voltage Rating: 125V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 800V AC/minute
 Pin Material: Phosphor Bronze/Tin-plated
 Material: Nylon 66,UL94V-0
 Pantone Color: 4685C

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2002WR-02P	2.00	6.00
A2002WR-03P	4.00	8.00
A2002WR-04P	6.00	10.00
A2002WR-05P	8.00	12.00
A2002WR-06P	10.00	14.00
A2002WR-07P	12.00	16.00
A2002WR-08P	14.00	18.00
A2002WR-09P	16.00	20.00
A2002WR-10P	18.00	22.00
A2002WR-11P	20.00	24.00
A2002WR-12P	22.00	26.00
A2002WR-13P	24.00	28.00
A2002WR-14P	26.00	30.00
A2002WR-15P	28.00	32.00

UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	2.00mm PITCH 90° WAFER
DRAWN BY	APPROVED BY		
董正一	董正一		
2004.09.07	2004.09.07		
GENERAL TOLERANCE			
B1	REVISE	2007.01.11	X.X±0.25
BO	NEW RELEASE	2005.12.05	X.XX±0.15
REV.	DESCRIPTION	DATE	X.XXX±0.05
DRAW NO.:			REV.
A2002WR-XP			B1