

REVISIONS

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED

REV																				
SHEET																				
REV																				
SHEET																				


REV STATUS OF SHEETS	REV																			
	SHEET	1	2	3	4	5	6	7	8	9	10	11	12	13						

PMIC N/A	PREPARED BY RICK C. OFFICER	DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444			
<p align="center">STANDARDIZED MILITARY DRAWING</p> <p>THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE</p> <p>AMSC N/A</p>	CHECKED BY CHARLES E. BESORE			MICROCIRCUIT, LINEAR, LOW NOISE, WIDEBAND, PRECISION, OPERATIONAL AMPLIFIER, MONOLITHIC SILICON	
	APPROVED BY MICHAEL A. FRYE	SIZE CAGE CODE 5962-91634 A 67268			
	DRAWING APPROVAL DATE 93-01-26	SHEET 1 OF 13			
	REVISION LEVEL				

1. SCOPE

1.1 Scope. This drawing forms a part of a one part - one part number documentation system (see 6.6 herein). Two product assurance classes consisting of military high reliability (device classes B, Q, and M) and space application (device classes S and V), and a choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). Device class M microcircuits represent non-JAN class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices". When available, a choice of Radiation Hardness Assurance (RHA) levels are reflected in the PIN.

1.2 PIN. The PIN shall be as shown in the following example:



1.2.1 RHA designator. Device classes M, B, and S RHA marked devices shall meet the MIL-M-38510 specified RHA levels and shall be marked with the appropriate RHA designator. Device classes Q and V RHA marked devices shall meet the MIL-I-38535 specified RHA levels and shall be marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) shall identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	HA-5221	Operational amplifier
02	HA-5222	Dual, operational amplifier

1.2.3 Device class designator. The device class designator shall be a single letter identifying the product assurance level as follows:

<u>Device class</u>	<u>Device requirements documentation</u>
M	Vendor self-certification to the requirements for non-JAN class B microcircuits in accordance with 1.2.1 of MIL-STD-883
B or S	Certification and qualification to MIL-M-38510
Q or V	Certification and qualification to MIL-I-38535

1.2.4 Case outline(s). The case outline(s) shall be as designated in MIL-STD-1835 and as follows:

<u>Outline letter</u>	<u>Descriptive designator</u>	<u>Terminals</u>	<u>Package style</u>
P	GDIP1-T8 or CDIP2-T8	8	Dual-in-line
2	CQCC1-N20	20	Square leadless chip carrier

1.2.5 Lead finish. The lead finish shall be as specified in MIL-M-38510 for classes M, B, and S or MIL-I-38535 for classes Q and V. Finish letter "X" shall not be marked on the microcircuit or its packaging. The "X" designation is for use in specifications when lead finishes A, B, and C are considered acceptable and interchangeable without preference.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-91634
		REVISION LEVEL	SHEET 2

1.3 Absolute maximum ratings. 1/

Voltage between V+ and V- terminals	36 V dc
Differential input voltage	5.0 V dc
Voltage at either input terminal	V+ to V-
Peak output current 2/	100 mA
Continuous output current	Short circuit protected
Lead temperature (soldering, 10 seconds)	+300°C
Storage temperature range	-65°C to +150°C
Power dissipation, at +75°C (P _D):	
Case P	0.9 W 3/
Case 2	1.2 W 4/
Thermal resistance, junction-to-case (θ _{JC})	See MIL-STD-1835
Thermal resistance, junction-to-ambient (θ _{JA}):	
Device type 01:	
Case P	113.5°C/W
Case 2	82.7°C/W
Device type 02:	
Case P	111.6°C/W
Case 2	81.9°C/W
Junction temperature (T _J)	+175°C

1.4 Recommended operating conditions.

Supply voltage range (V±)	±10 V dc to ±15 V dc
Common mode input voltage (V _{CM})	≤ 0.5(V+ - V-)
Load resistance (R _L)	≥ 1.0 kΩ
Ambient operating temperature range (T _A)	-55°C to +125°C

2. APPLICABLE DOCUMENTS

2.1 Government specifications, standards, bulletin, and handbook. Unless otherwise specified, the following specifications, standards, bulletin, and handbook of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATIONS

MILITARY

- MIL-M-38510 - Microcircuits, General Specification for.
- MIL-I-38535 - Integrated Circuits, Manufacturing, General Specification for.

STANDARDS

MILITARY

- MIL-STD-480 - Configuration Control-Engineering Changes, Deviations and Waivers.
- MIL-STD-883 - Test Methods and Procedures for Microelectronics.
- MIL-STD-1835 - Microcircuit Case Outlines.

1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.
 2/ Pulsed at 1.0 ms, 10% duty cycle.
 3/ Derate above +75°C at 9.0 mW/°C.
 4/ Derate above +75°C at 12.0 mW/°C.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-91634
		REVISION LEVEL	SHEET 3

BULLETIN

MILITARY

MIL-BUL-103 - List of Standardized Military Drawings (SMD's).

HANDBOOK

MILITARY

MIL-HDBK-780 - Standardized Military Drawings.

(Copies of the specifications, standards, bulletin, and handbook required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device class M shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein. The individual item requirements for device classes B and S shall be in accordance with MIL-M-38510 and as specified herein. For device classes B and S, a full electrical characterization table for each device type shall be included in this SMD. The individual item requirements for device classes Q and V shall be in accordance with MIL-I-38535, the device manufacturer's Quality Management (QM) plan, and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 for device classes M, B, and S and MIL-I-38535 for device classes Q and V and herein.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. Marking for device class M shall be in accordance with MIL-STD-883 (see 3.1 herein). In addition, the manufacturer's PIN may also be marked as listed in MIL-BUL-103. Marking for device classes B and S shall be in accordance with MIL-M-38510. Marking for device classes Q and V shall be in accordance with MIL-I-38535.

3.5.1 Certification/compliance mark. The compliance mark for device class M shall be a "C" as required in MIL-STD-883 (see 3.1 herein). The certification mark for device classes B and S shall be a "J" or "JAN" as required in MIL-M-38510. The certification mark for device classes Q and V shall be a "QML" as required in MIL-I-38535.

3.6 Certificate of compliance. For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-BUL-103 (see 6.7.3 herein). For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.7.2 herein). The certificate of compliance submitted to DESC-EC prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device class M, the requirements of MIL-STD-883 (see 3.1 herein), or for device classes Q and V, the requirements of MIL-I-38535 and the requirements herein.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-91634
		REVISION LEVEL	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions 1/ -55°C ≤ T _A ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits 2/		Unit
					Min	Max	
Input offset voltage	V _{IO}	V _{CM} = 0 V	1	ALL	-0.75	0.75	mV
			2,3		-1.5	1.5	
Input bias current	+I _B	V _{CM} = 0 V, +R _S = 100.1 kΩ, -R _S = 100Ω	1	ALL	-80	80	nA
			2,3		-200	200	
	-I _B	V _{CM} = 0 V, +R _S = 100Ω, -R _S = 100.1 kΩ	1	ALL	-80	80	nA
			2,3		-200	200	
Input offset current	I _{IO}	V _{CM} = 0 V, +R _S = 100.1 kΩ, -R _S = 100.1 kΩ	1	ALL	-50	50	nA
			2,3		-150	150	
Common mode range	+CMR	V ₊ = +3.0 V, V ₋ = -27 V	1,2,3	ALL	12		V
	-CMR	V ₊ = +27 V, V ₋ = -3.0 V	1,2,3	ALL		-12	V
Large signal voltage gain	+A _{VOL}	V _{OUT} = 0 V to 10 V	1	ALL	106		dB
			2,3		100		
	-A _{VOL}	V _{OUT} = 0 V to -10 V	1	ALL	106		dB
			2,3		100		
Common mode rejection ratio	+CMRR	ΔV _{CM} = 10 V, V ₊ = +5.0 V, V ₋ = -25 V, V _{OUT} = -10 V	1	ALL	88		dB
			2,3		86		
	-CMRR	ΔV _{CM} = -10 V, V ₊ = +25 V, V ₋ = -5.0 V, V _{OUT} = 10 V	1	ALL	88		dB
			2,3		86		

See footnotes at end of table.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-91634
		REVISION LEVEL	SHEET 5

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions <u>1/</u> -55°C ≤ T _A ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits <u>2/</u>		Unit
					Min	Max	
Output voltage swing	+V _{OUT}	R _L = 1.0 kΩ	1	ALL	12.0		V
			2,3		11.5		
	-V _{OUT}	R _L = 1.0 kΩ	1	ALL		-12.0	V
			2,3			-11.5	
Output current	+I _{OUT}	V _{OUT} = +10 V, R _L = 1.0 kΩ	1,2,3	ALL	30		mA
	-I _{OUT}	V _{OUT} = -10 V, R _L = 1.0 kΩ	1,2,3	ALL		-30	mA
Quiescent power supply current	+I _{CC}	V _{OUT} = 0 V, I _{OUT} = 0 mA	1	01		10	mA
				02		20	
			2,3	01		11	
				02		22	
	-I _{CC}	V _{OUT} = 0 V, I _{OUT} = 0 mA	1	01	-10		mA
				02	-20		
			2,3	01	-11		
				02	-22		
Power supply rejection ratio	+PSRR	ΔV _{SUP} = 10 V, V ₊ = +20 V, V ₋ = -15 V, V ₊ = +10 V, V ₋ = -15 V	1	ALL	90		dB
			2,3		86		
	-PSRR	ΔV _{SUP} = 10 V, V ₊ = +15 V, V ₋ = -20 V, V ₊ = +15 V, V ₋ = -10 V	1	ALL	90		dB
			2,3		86		

See footnotes at end of table.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-91634
		REVISION LEVEL	SHEET 6

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions 1/ -55°C ≤ T _A ≤ +125°C unless otherwise specified		Group A subgroups	Device type	Limits 2/		Unit
						Min	Max	
Offset voltage adjustment 3/	+V _{I0} (adj)			1,2,3	01	V _{I0} -1.0		mV
	-V _{I0} (adj)			1,2,3	01	V _{I0} +1.0		mV
Input noise voltage density 4/	E _n	R _S = 0Ω, C _L = 50 pF, T _A = +25°C	f _o = 10 Hz	4	01		24.0	nV/√Hz
			f _o = 100 Hz		02		16.0	
					01		8.0	
			f _o = 1.0 kHz		02		6.6	
					01		5.9	
			02			5.9		
Input noise current density 4/	I _n	R _S = 500 kΩ, C _L = 50 pF, T _A = +25°C	f _o = 10 Hz	4	01		11.5	pA/√Hz
			f _o = 100 Hz		02		24.0	
					01		6.0	
			f _o = 1.0 kHz		02		6.6	
					01		2.0	
			02			2.7		
Gain bandwidth product 4/	GBWP	V _{OUT} = 200 mV p-p, f _o = 100 kHz, C _L = 50 pF	4	ALL	100		MHz	
			5,6		88			
Unity gain bandwidth 4/	UGBW	V _{OUT} = 200 mV p-p, C _L = 50 pF	4	ALL	30		MHz	
			5,6		25			

See footnotes at end of table.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-91634

REVISION LEVEL

SHEET

7

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions ^{1/} -55°C ≤ T _A ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits ^{2/}		Unit
					Min	Max	
Slew rate ^{4/}	+SR	V _{OUT} = -2.5 V to +2.5 V, C _L = 50 pF, measured from 10 percent to 90 percent points	4,5,6	ALL	25		V/μs
	-SR	V _{OUT} = +2.5 V to -2.5 V, C _L = 50 pF, measured from 90 percent to 10 percent points	4,5,6	ALL	25		V/μs
Full power bandwidth ^{4/} ^{5/}	FPBW	V _{PEAK} = 10 V, C _L = 50 pF	4,5,6	ALL	238		kHz
Minimum closed loop stable gain ^{4/}	CLSG	C _L = 50 pF	4,5,6	ALL	1.0		V/V
Rise time ^{4/}	τ _R	V _{OUT} = ±100 mV, C _L = 50 pF, measured at 10 percent and 90 percent points	4	ALL		20	ns
			5,6			35	
Fall time ^{4/}	τ _F	V _{OUT} = ±100 mV, C _L = 50 pF, measured at 10 percent and 90 percent points	4	ALL		20	ns
			5,6			35	
Overshoot ^{4/}	±OS	V _{OUT} = ±100 mV, C _L = 50 pF	4	ALL		25	%
			5,6			30	
Power consumption ^{4/}	PC	V _{OUT} = 0 V, I _{OUT} = 0 mA, C _L = 50 pF	1,2,3	01		330	mW
				02		660	

^{1/} Unless otherwise specified, V_± = ±15 V, R_L = 1.0 kΩ, and V_{OUT} = 0 V.

^{2/} The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum, is used in this table. Negative current shall be defined as conventional current flow out of a device terminal.

^{3/} Offset adjustment range is [V_{IO} (measured) ±1.0 mV] minimum referred to output. This test is for functionality only to assure adjustment through 0 V.

^{4/} If not tested, shall be guaranteed to the limits specified in table I herein.

^{5/} Full power bandwidth is guaranteed based on slew rate measurement using FPBW = slew rate/2πV_{PEAK}.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-91634

REVISION LEVEL

SHEET

8

Device type	01		02	
Case outline	P	2	P	2
Terminal number	Terminal symbol		Terminal symbol	
1	-Balance	NC	Output 1	NC
2	-Input	-Balance	-Input 1	Output 1
3	+Input	NC	+Input 1	NC
4	V-	NC	V-	NC
5	NC	-Input	+Input 2	-Input 1
6	Output	NC	-Input 2	NC
7	V+	+Input	Output 2	+Input 1
8	+Balance	NC	V+	NC
9	---	NC	---	NC
10	---	V-	---	V-
11	---	NC	---	NC
12	---	NC	---	+Input 2
13	---	NC	---	NC
14	---	NC	---	NC
15	---	Output	---	-Input 2
16	---	NC	---	NC
17	---	V+	---	Output 2
18	---	NC	---	NC
19	---	NC	---	NC
20	---	+Balance	---	V+

NC = No connection

FIGURE 1. Terminal connections.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-91634

REVISION LEVEL

SHEET

9

3.7 Certificate of conformance. A certificate of conformance as required for device class M in MIL-STD-883 (see 3.1 herein) or device classes B and S in MIL-M-38510 or for device classes Q and V in MIL-I-38535 shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DESC-EC of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change as defined in MIL-STD-480.

3.9 Verification and review for device class M. For device class M, DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device classes M, B, and S. Device classes M, B, and S devices covered by this drawing shall be in microcircuit group number 49 (see MIL-M-38510, appendix E).

3.11 Serialization for device class S. All device class S devices shall be serialized in accordance with MIL-M-38510.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. For device class M, sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein). For device classes B and S, sampling and inspection procedures shall be in accordance with MIL-M-38510 and method 5005 of MIL-STD-883, except as modified herein. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-I-38535 and the device manufacturer's QM plan.

4.2 Screening. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. For device classes B and S, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to qualification and quality conformance inspection. For device classes Q and V, screening shall be in accordance with MIL-I-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection.

4.2.1 Additional criteria for device classes M, B, and S.

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A, B, C, or D. For device class M, the test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. For device classes B and S, the test circuit shall be submitted to the qualifying activity. For device classes M, B, and S, the test circuit shall specify the inputs, outputs, and biases, as applicable, in accordance with the intent specified in test method 1015.

(2) $T_A = +125^\circ\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein.

4.2.2 Additional criteria for device classes Q and V.

a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-I-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-I-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, and biases, as applicable, in accordance with the intent specified in test method 1015.

b. Interim and final electrical test parameters shall be as specified in table II herein.

c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in appendix B of MIL-I-38535.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-91634
		REVISION LEVEL	SHEET 10

TABLE II. Electrical test requirements.

Test requirements	Subgroups (in accordance with MIL-STD-883, method 5005, table I)			Subgroups (in accordance with MIL-I-38535, table III)	
	Device class M	Device class B	Device class S	Device class Q	Device class V
Interim electrical parameters (see 4.2)	---	1,2,3	1,2,3	1,2,3	1,2,3
Final electrical parameters (see 4.2)	1,2,3, 1/ 4,5,6	1,2,3, 1/ 4,5,6	1,2,3, 1/ 4,5,6	1,2,3, 1/ 4,5,6	1,2,3, 1/ 4,5,6
Group A test requirements (see 4.4)	1,2,3,4, 5,6	1,2,3,4, 5,6	1,2,3,4, 5,6	1,2,3,4, 5,6	1,2,3,4, 5,6
Group B end-point electrical parameters (see 4.4)	---	---	1,2,3	---	---
Group C end-point electrical parameters (see 4.4)	1	1,2,3	---	1,2,3	1,2,3
Group D end-point electrical parameters (see 4.4)	1	1,2,3	1,2,3	1,2,3	1,2,3
Group E end-point electrical parameters (see 4.4)	---	---	---	---	---

1/ PDA applies to subgroup 1.

4.3 Qualification inspection.

4.3.1 Qualification inspection for device classes B and S. Qualification inspection for device classes B and S shall be in accordance with MIL-M-38510. Inspections to be performed shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.5).

4.3.2 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-I-38535. Inspections to be performed shall be those specified in MIL-I-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.5).

4.4 Conformance inspection. Quality conformance inspection for device class M shall be in accordance with MIL-STD-883 (see 3.1 herein) and as specified herein. Quality conformance inspection for device classes B and S shall be in accordance with MIL-M-38510 and as specified herein. Inspections to be performed for device classes M, B, and S shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.5). Technology conformance inspection for classes Q and V shall be in accordance with MIL-I-38535 including groups A, B, C, D, and E inspections and as specified herein except where option 2 of MIL-I-38535 permits alternate in-line control testing.

4.4.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 7, 8, 9, 10, and 11 in table I of method 5005 of MIL-STD-883 shall be omitted.

4.4.2 Group B inspection. The group B inspection end-point electrical parameters shall be as specified in table II herein. For device class S steady-state life tests, the test circuit shall be submitted to the qualifying activity.

4.4.3 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table II herein.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-91634
		REVISION LEVEL SHEET 11

4.4.3.1 Additional criteria for device classes M and B. Steady-state life test conditions, method 1005 of MIL-STD-883:

- a. Test condition A, B, C, or D. For device class M, the test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. For device class B, the test circuit shall be submitted to the qualifying activity. For device classes M and B, the test circuit shall specify the inputs, outputs, and biases, as applicable, in accordance with the intent specified in test method 1005.
- b. $T_A = +125^{\circ}\text{C}$, minimum.
- c. Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.4.3.2 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-I-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-I-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, and biases, as applicable, in accordance with the intent specified in test method 1005.

4.4.4 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table II herein.

4.4.5 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein). RHA levels for device classes B, S, Q, and V shall be M, D, R, and H and for device class M shall be M and D.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. For device classes M, B, and S, the devices shall be subjected to radiation hardness assured tests as specified in MIL-M-38510 for the RHA level being tested. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-I-38535 for the RHA environment and level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at $T_A = +25^{\circ}\text{C} \pm 5^{\circ}\text{C}$, after exposure, to the subgroups specified in table II herein.
- c. When specified in the purchase order or contract, a copy of the RHA delta limits shall be supplied.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510 for device classes M, B, and S and MIL-I-38535 for device classes Q and V.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.1.2 Substitutability. Device classes B and Q devices will replace device class M devices.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-481 using DD Form 1693, Engineering Change Proposal (Short Form).

6.3 Record of users. Military and industrial users shall inform Defense Electronics Supply Center when a system application requires configuration control and which SMD's are applicable to that system. DESC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DESC-EC, telephone (513) 296-6047.

6.4 Comments. Comments on this drawing should be directed to DESC-EC, Dayton, Ohio 45444, or telephone (513) 296-5377.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-91634
		REVISION LEVEL SHEET 12

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-M-38510 and MIL-STD-1331.

6.6 One part - one part number system. The one part - one part number system described below has been developed to allow for transitions between identical generic devices covered by the four major microcircuit requirements documents (MIL-M-38510, MIL-H-38534, MIL-I-38535, and 1.2.1 of MIL-STD-883) without the necessity for the generation of unique PIN's. The four military requirements documents represent different class levels, and previously when a device manufacturer upgraded military product from one class level to another, the benefits of the upgraded product were unavailable to the Original Equipment Manufacturer (OEM), that was contractually locked into the original unique PIN. By establishing a one part number system covering all four documents, the OEM can acquire to the highest class level available for a given generic device to meet system needs without modifying the original contract parts selection criteria.

<u>Military documentation format</u>	<u>Example PIN under new system</u>	<u>Manufacturing source listing</u>	<u>Document listing</u>
New MIL-M-38510 Military Detail Specifications (in the SMD format)	5962-XXXXXZZ(B or S)YY	QPL-38510 (Part 1 or 2)	MIL-BUL-103
New MIL-H-38534 Standardized Military Drawings	5962-XXXXXZZ(H or K)YY	QML-38534	MIL-BUL-103
New MIL-I-38535 Standardized Military Drawings	5962-XXXXXZZ(Q or V)YY	QML-38535	MIL-BUL-103
New 1.2.1 of MIL-STD-883 Standardized Military Drawings	5962-XXXXXZZ(M)YY	MIL-BUL-103	MIL-BUL-103

6.7 Sources of supply.

6.7.1 Sources of supply for device classes B and S. Sources of supply for device classes B and S are listed in QPL-38510.

6.7.2 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DESC-EC and have agreed to this drawing.

6.7.3 Approved sources of supply for device class M. Approved sources of supply for class M are listed in MIL-BUL-103. The vendors listed in MIL-BUL-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DESC-EC.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-91634
		REVISION LEVEL	SHEET 13

STANDARDIZED MILITARY DRAWING SOURCE APPROVAL BULLETIN

DATE: 93-01-26

Approved sources of supply for SMD 5962-91634 are listed below for immediate acquisition only and shall be added to MIL-BUL-103 during the next revision. MIL-BUL-103 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DESC-EC. This bulletin is superseded by the next dated revision of MIL-BUL-103.

Standardized military drawing PIN	Vendor CAGE number	Vendor similar PIN <u>1/</u>
5962-9163401MPX	34371	HA7-5221/883
5962-9163401M2X	34371	HA4-5221/883
5962-9163402MPX	34371	HA7-5222/883
5962-9163402M2X	34371	HA4-5222/883

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE number

34371

Vendor name and address

Harris Semiconductor
P.O. Box 883
Melbourne, FL 32902-0883

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in this information bulletin.