
Search

Our commitment. Your advantage.

Products Documentation Customer Support Resources My Account

<u>Home > Products > By Type > D-Subminiature Connectors > Product Feature Selector > Product Details</u>

1-1470250-5 Product Details



Standard Board Mount Connectors

5 of 6 EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Number of Positions = 15
- Receptacle
- PCB Mount Angle = Right Angle
- Product Series = HD-22
- With Mating Connector Lock

View all Features



Quick Links


Check Pricing & Availability Search for Tooling <u>Product Feature Selector</u> **Contact Us About This Product**

1-1470250-5

TE Internal Number: 1-1470250-5 Superseded

Contact Product Information Center

View 3D PDF









Documentation & Additional Information

Product Drawings:

None Available

Catalog Pages/Data Sheets:

None Available

Product Specifications:

• AMPLIMITE* HD-22 Front Metal Shell, PCB Mounted Conn... (PDF, English)

Application Specifications:

• AMPLIMITE HD-22 Right-Angle Front Metal Shell Connectors (PDF, English)

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version B)
- 3D Model (IGES, Version B)
- 3D Model (STEP, Version B)

Additional Information:

• Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Number of Positions = 15
- <u>Gender</u> = Receptacle
- <u>PCB Mount Angle</u> = Right Angle
- <u>Product Series</u> = HD-22
- <u>Mating Connector Lock</u> = With
- Mating Connector Lock Type = Threaded Insert, 4-40 UNC
- <u>PCB Retention Feature</u> = Yes
- <u>Shell Type</u> = Front Metal Shell
- Shell Size = 1
- Footprint (mm [in]) = 8.89 [.350]
- PCB Thickness (in [mm]) = 0.062 [1.57]
- Grounding Indents = Without
- <u>Grounding Straps</u> = Without
- <u>PCB Mount Style</u> = Through Hole
- <u>Color Code</u> = None
- Sealed = No
- Post Size (mm [in]) = 0.66 [.026]
- Color = Black
- Shell Material = Low Carbon Steel

Mechanical Attachment:

- <u>Panel Attachment</u> = Without
- Boardlock Hole Diameter (mm [in]) = 3.20 [0.126]
- Boardlock Material = Copper Alloy
- Boardlock Plating = Tin-Lead over Nickel

Termination Related Features:

- <u>Grounding Clips</u> = Without
- Termination Post Length (mm [in]) = 2.15 [0.084]
- <u>Solder Tail Contact Plating</u> = Tin-Lead over Nickel

Body Related Features:

List all Documents

- <u>PCB Retention Method</u> = Boardlock(s)
- Insert Material = Copper Alloy
- Shell Plating = Nickel

Contact Related Features:

- Contact Mating Area Plating Material = Gold (15)
- Contact Shape = Round
- Contact Base Material = Copper Alloy

Housing Related Features:

- Housing Flammability Rating = UL 94V-0
- Housing Material = Thermoplastic

Industry Standards:

- RoHS/ELV Compliance = ELV compliant, 5 of 6 Compliant
- <u>Lead Free Solder Processes</u> = Not suitable for lead free processing

Operation/Application:

• Application = Standard

Packaging Related Features:

Packaging Method = Tray

Other:

Brand = AMP