




STANDARD EDGE CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

AMP PACE CONN 43POS 156X200C/L

AMP PACE | AMP ECONOMATE , AMP PACE

2-119790-9

TE Internal Number: 2-119790-9

Alias ID: 2-42934-1292

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Product Type **Connector**

Number of Dual Positions **43**

Number of Rows **2**

Housing Color **Black**

Housing Material **Polyester - GF**

Product Drawings

[CONNECTOR, AMP PACE .156 X .200](#)

PDF (**TIFF AVAILABLE**)
English

[CONNECTOR, AMP PACE .156 X .200](#)

PDF (**TIFF AVAILABLE**)
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Instruction Sheets

Instruction Sheet (U.S.)

[AMP PACE .156- X .200-In. Centerline Connectors Accessories & Tooling](#)

PDF
English

[AMP PACE .156- X .200-In. Centerline Connectors Accessories & Tooling](#)

TIF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Connector Style	Plug
	PCB Mounting Orientation	Vertical
	Row-to-Row Spacing	5.08 mm [.2 in]
	Connector System	Board-to-Board
	Connector Type	Connector Assembly
	Applies To	Printed Circuit Board
	Type of Connector	Card Edge
	Post Alignment	Clear Polyester Contact Tip Strip
<hr/>		
Configuration Features	Number of Dual Positions	43
	Number of Rows	2
	Pre-Assembled	Yes
	End Caps	Without
<hr/>		
Electrical Characteristics	Hot Pluggable	No
<hr/>		
Body Features	Post Plating Material	Tin-Lead
<hr/>		
Contact Features	Contact Termination Area Plating Material	Tin
	Contact Termination Area Plating Material Finish	Matte
	Contact Current Rating (A)	3
	Contact Mating Area Plating Material	Gold
	Underplate Material	Nickel
	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin
	Contact Termination Area Plating Thickness (µin)	100
Contact Type	Pin	
<hr/>		
Termination Features	Termination Method to PC Board	Through Hole - Press-Fit
	Termination Post Length	4.57 mm [.18 in]
<hr/>		
Mechanical Attachment	PCB Mount Alignment	Without
	Panel Mount Retention	Without
	PCB Mount Retention Type	Action/Compliant Tail
	PCB Mount Retention	With
	Mating Alignment	With

Mating Alignment Type

Polarization

Housing Features

Housing Color

Black

Housing Material

Polyester - GF

Centerline

3.96 mm [.156 in]

Housing Style

Closed End/Closed End - Standard

Dimensions

Height (in)

.545

Usage Conditions

Operating Temperature Range (°C)

-55 – 85

Operation/Application

For Use With

Mates with Plug

Industry Standards

UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Quantity

4

Packaging Method

Tube

Other

Comment

Full palladium-nickel plated posts and other platings and plating thicknesses can be made available.

Product Compliance

[Statement of Compliance](#)
PDF[VIEW ALL PRODUCT COMPLIANCE](#)