



SPECIFICATIONS

- 2-25 Circuits
- With Locking Ramp
- Nylon—UL 94V-0
- Mates with .025" [0.64mm] pins
- Accepts double cantilever crimp terminal [2510HP-T]
- Terminal retention to housing 6.6lbs [3.0Kg] Min

Dimensions (mm)					
Pos.	A	B	Pos.	A	B
02	5.60	2.54	14	36.08	33.02
03	8.14	5.08	15	38.62	35.56
04	10.68	7.62	16	41.16	38.10
05	13.22	12.70	17	43.70	40.64
06	15.76	12.70	18	46.24	43.18
07	18.30	15.24	19	48.78	45.72
08	20.84	17.78	20	51.32	48.26
09	23.38	20.32	21	53.86	50.80
10	25.92	22.86	22	56.40	53.34
11	28.46	25.40	23	58.94	55.88
12	31.00	27.94	24	61.48	58.42
13	33.54	30.48	25	64.02	60.96

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-V-2510-H-XX-PL-A**

Description: 2.54mm Pitch Female Wire Mount Housing