

MICRO

2SB621,A 2SD592,A

SILICON
TRANSISTORS

T0-92



ECB

2SB621,A (PNP) & 2SD592,A (NPN) are complementary silicon planar epitaxial transistors designed for AF output amplifiers.

ABSOLUTE MAXIMUM RATINGS

	2SD592	2SD592A
Collector-Base Voltage	30V	60V
Collector-Emitter Voltage	25V	50V
Emitter-Base Voltage		5V
Collector Current		1A
Total Power Dissipation		750mW
Operating Junction & Storage Temperature		-55 to +150°C

ELECTRICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	MIN	MAX	UNIT	TEST CONDITION
Collector Cutoff Current	ICBO		100	nA	VCB=20V IE=0
Collector-Base Breakdown Voltage	BVCBO	30	60	V	IC=10µA IE=0
Collector-Base Breakdown Voltage	2SB621 /2SD592				
Collector-Base Breakdown Voltage	2SB621A/2SD592A				
Collector-Emitter Breakdown Voltage	LVCEO	25	50	V	IC=2mA IB=0
Collector-Emitter Breakdown Voltage	2SB621 /2SD592				
Collector-Emitter Breakdown Voltage	2SB621A/2SD592A				
Emitter-Base Breakdown Voltage	BVEBO	5		V	IE=10µA IC=0
D.C. Current Gain	HFE	85	340		IC=500mA VCE=10V*
D.C. Current Gain		50			IC=1A VCE=10V*
Collector-Emitter Saturation Voltage	VCE(sat)		0.4	V	IC=500mA IB=50mA*
Base-Emitter Saturation Voltage	VBE(sat)		1.2	V	IC=500mA IB=50mA*
Current Gain Bandwidth Product	fT	200 TYP		MHz	IC=50mA VCE=10V
Output Capacitance	2SB621,A		30	pF	VCB=10V f=1MHz
Output Capacitance	2SD592,A		20	pF	

Pulse Test : Pulse Width < 300µs, Duty Cycle < 1%.

HFE Grouping

Q : 85-170

R : 120-240

S : 170-340



MICRO ELECTRONICS LTD. 美科有限公司 FAX: 3-410321

38 Hung To Road, Kwun Tong, Kowloon, Hong Kong. Cable: Microtron, Hong Kong. Telex: 43510 Micro Hx.
P.O. Box 9477, Kwun Tong. Tel: 3-430181-6, 3-899363, 3-892423, 3-898221

1-1.0mp