



RECOMMENDED PCB LAYOUT



CONTACTS	DIMENSIONS	
	A	B
02	2.54	5.08
03	5.08	7.62
04	7.62	10.16
05	10.16	12.70
06	12.70	15.24
07	15.24	17.78
08	17.78	20.32
09	20.32	22.86
10	22.86	25.40
11	25.40	27.94
12	27.94	30.48
13	30.48	33.02
14	33.02	35.56
15	35.56	38.10
16	38.10	40.64
17	40.64	43.18
18	43.18	45.72
19	45.72	48.26
20	48.26	50.80
21	50.80	53.34
22	53.34	55.88
23	55.88	58.42
24	58.42	60.96
25	60.96	63.50
26	63.50	66.04
27	66.04	68.58
28	68.58	71.12
29	71.12	73.66
30	73.66	76.20
31	76.20	78.74
32	78.74	81.28
33	81.28	83.82
34	83.82	86.36
35	86.36	88.90
36	88.90	91.44
37	91.44	93.98
38	93.98	96.52
39	96.52	99.06
40	99.06	101.60

SPECIFICATIONS 规格
CURRENT RATING 电流额定值: 3 AMP
INSULATION RESISTANCE 绝缘电阻值: 1000MΩ MIN.
CONTACT RESISTANCE 接触电阻值: 20mΩ MAX.
DIELECTRIC WITHSTANDING 耐电压: 600V AC
OPERATING TEMPERATURE 工作温度: -40°C TO +105°C
CONTACT MATERIAL 端子物料: COPPER ALLOY
INSULATOR MATERIAL 绝缘体物料:
 STANDARD 标准物料: POLYAMIDE 聚酰胺, NYLON 6T BLACK, UL 94-V0
 OPTIONS 可选物料: POLYAMIDE 聚酰胺, NYLON 6T WHITE, UL 94-V0
SOLDERING PROCESS 可焊性:
 NYLON 6T (STANDARD 标准物料) -
 IR REFLOW 回流焊: 260°C for 10 sec.
 WAVE 波峰焊: 230°C for 5-10 sec.
 MANUAL SOLDER 人工焊接: 350°C for 3-5 sec
 LCP (OPTION 可选物料) -
 IR REFLOW 回流焊: 260°C for 10 sec.
 WAVE 波峰焊: 250°C for 5-10 sec.
 MANUAL SOLDER 人工焊接: 350°C for 3-5 sec
MATES WITH 配套之母座 (SUBJECT TO PIN LENGTH 在端子长度适合的条件下):
 BG090 BG095 BG096 BG100 BG110
 BG115 BG125 BG130 BG135 BG145
 BG205

Ordering Grid

BG080 - XX - X - XXXX - XXXX - XXXX - X - X Request Samples and Quotation

No. of Contacts: 02 to 40
 Contact Plating:
 A = Gold Flash All Over
 B = Selective Gold Flash Contact Area/Tin On Tail
 C = Tin All Over
 G = 10µ" Gold Contact Area/Tin On Tail
 I = 30µ" Gold Contact Area/Tin On Tail
Standard = Gold Flash All Over

Dimension C (1/100mm) (Post Length)
Standard - 7.10mm = 0710
 Or specify Dimension C
 e.g. 2.50mm = 0250
 TOL.: ±0.2mm

Insulator Material
N = Nylon 6T Black (Standard)
 L = LCP Black
 W = Nylon 6T White

Packing Options
B = Tape and Reel with Cap (Standard)
 D = Tube
 E = Tube with Cap

Dimension D (1/100mm) (Pin Solder Area)
Standard - 1.50mm = 0150
 Or specify Dimension D
 e.g. 2.50mm = 0250
 TOL.: ±0.2mm

Dimension E (1/100mm) (Insulator to Pin Solder Area)
Standard - 1.50mm = 0150
 Or specify Dimension E
 e.g. 2.50mm = 0250
 TOL.: ±0.2mm

Part Number		Product Description	
BG080		2.54mm Pitch Pin Header, Single Row, Surface Mount, Horizontal, without Locating Peg	
Drawing Date		30th October 2006	
By	AJO	Tolerances (Except as Noted)	Units:
Detail		Length	Metric (mm)
Revision	D1	Angle	Angle
Date	16/12/14	X.X ± 0.30	
		X.XX ± 0.20	



This drawing is confidential and copyright of Global Connector Technology, Ltd (GCT). This drawing must not be copied or disclosed without written consent. E & OE

GCT
 Global Connector Technology
 www.gct.co

Not to Scale | Drawn By LYH | Sheet No. 1/1