

Pb-free
HEAT

STANLEY

1112C Series

Single Color 1608 (h=0.5 mm) Type

Features

Package	1608 (h=0.5mm) Type, Milky White resin								
Product features	<ul style="list-style-type: none"> • Outer Dimension 1.6 x 0.8 x 0.4mm (L x W x H) • Temperature range <table style="margin-left: 20px;"> <tr> <td>Storage Temperature</td> <td>: -40°C~100°C</td> </tr> <tr> <td>Operating Temperature</td> <td>: GaP(PG) : -40°C~85°C</td> </tr> <tr> <td></td> <td>GaP(PY) : -30°C~85°C</td> </tr> <tr> <td></td> <td>GaAsP : -40°C~85°C</td> </tr> </table> • Lead-free soldering compatible • RoHS compliant 	Storage Temperature	: -40°C~100°C	Operating Temperature	: GaP(PG) : -40°C~85°C		GaP(PY) : -30°C~85°C		GaAsP : -40°C~85°C
Storage Temperature	: -40°C~100°C								
Operating Temperature	: GaP(PG) : -40°C~85°C								
	GaP(PY) : -30°C~85°C								
	GaAsP : -40°C~85°C								
Dominant wavelength	<table style="margin-left: 20px;"> <tr> <td>Green</td> <td>: 567nm(PG)</td> </tr> <tr> <td>Yellow Green</td> <td>: 572nm(PY)</td> </tr> <tr> <td>Red</td> <td>: 633nm(DR)</td> </tr> </table>	Green	: 567nm(PG)	Yellow Green	: 572nm(PY)	Red	: 633nm(DR)		
Green	: 567nm(PG)								
Yellow Green	: 572nm(PY)								
Red	: 633nm(DR)								
Half Intensity Angle	<table style="margin-left: 20px;"> <tr> <td>PG</td> <td>: $\theta_x = 130$ deg., $\theta_y = 150$ deg.</td> </tr> <tr> <td>PY</td> <td>: $\theta_x = 147$ deg., $\theta_y = 152$ deg.</td> </tr> <tr> <td>DR</td> <td>: $\theta_x = 147$ deg., $\theta_y = 156$ deg.</td> </tr> </table>	PG	: $\theta_x = 130$ deg., $\theta_y = 150$ deg.	PY	: $\theta_x = 147$ deg., $\theta_y = 152$ deg.	DR	: $\theta_x = 147$ deg., $\theta_y = 156$ deg.		
PG	: $\theta_x = 130$ deg., $\theta_y = 150$ deg.								
PY	: $\theta_x = 147$ deg., $\theta_y = 152$ deg.								
DR	: $\theta_x = 147$ deg., $\theta_y = 156$ deg.								
Die materials	PG,PY : GaP, DR : GaAsP								
Rank grouping parameter	Sorted by luminous intensity per rank taping								
Assembly method	Auto pick & place machine (Auto Mounter)								
Soldering methods	Reflow soldering and manual soldering								
Taping and reel	4,000pcs per reel in a 8mm width tape. (Standard) Reel diameter: ϕ 180mm								
ESD	More than 2kV(HBM)								

Recommended Applications

Cellular Phone, Electric Household Appliances, Other General Applications

Color and Luminous Intensity

(Ta=25°C)

Part No.	Material	Emitted Color	Lens Color	Dominant Wavelength		Luminous Intensity		
				λ_d (nm)		Iv (mcd)		
				TYP.	I _F	MIN.	TYP.	I _F
PG1112C	GaP	Green	Milky White	567	20	4.5	7.6	20
PY1112C	GaP	Yellow Green		572	20	7.0	11.7	20
DR1112C	GaAsP	Red		633	20	2.4	4.1	20

Absolute Maximum Ratings

(Ta=25°C)

Item	Symbol	Absolute Maximum Ratings			Unit
		PG	PY	DR	
Power Dissipation	P_d	70	70	70	mW
Forward Current	I_F	25	25	25	mA
Pulse Forward Current ※1	I_{FRM}	60	60	60	mA
Derating (Ta=25°C or higher)	ΔI_F	0.36	0.36	0.36	mA/°C
	ΔI_{FRM}	0.86	0.86	0.86	mA/°C
Reverse Voltage	V_R	4	4	4	V
Operating Temperature	T_{opr}	-40~+85	-30~+85	-40~+85	°C
Storage Temperature	T_{stg}	-40~+100			°C

※1 I_{FRM} Measurement condition : $t_w \leq 1\text{ms.}$, Duty $\leq 1/20$.

Electro-Optical Characteristics

(Ta=25°C)

Item	Conditions	Symbol	Characteristics			Unit	
			PG	PY	DR		
Forward Voltage	I _F =20mA	V _F	TYP.	2.2	2.1	1.9	V
			MAX.	2.8	2.8	2.8	
Reverse Current	V _R =4V	I _R	MAX.	100	100	100	μ A
Peak Wavelength	I _F =20mA	λ _p	TYP.	560	570	650	nm
Dominant Wavelength	I _F =20mA	λ _d	TYP.	567	572	633	nm
Spectral Line Half Width	I _F =20mA	Δλ	TYP.	30	30	40	nm
Half Intensity Angle	I _F =20mA	2θ 1/2	TYP.	130(θ x)	147(θ x)	147(θ x)	deg.
				150(θ y)	152(θ y)	156(θ y)	





Luminous Intensity Rank

(Ta=25°C)





Rank	I _v (mcd)					
	PG		PY		DR	
	I _F =20mA		I _F =20mA		I _F =20mA	
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
A	4.5	6.4	7.0	9.9	2.4	3.4
B	5.4	7.6	8.3	11.7	2.9	4.1
C	6.4	9.0	9.9	14.0	3.4	4.8
D	7.6	10.8	11.7	16.5	4.1	5.8
E	9.0	12.8	14.0	19.8	4.8	6.8
F	10.8	-	16.5	-	5.8	-

※ Please contact our sales staff concerning rank designation.





Technical Data(PG)







Technical Data(PG)







Technical Data(PY)







Technical Data(PY)



Technical Data(DR)




Technical Data(DR)



Package Dimensions


(Unit: mm)

Weight: (1.35)mg



Recommended Soldering Pattern


(Unit: mm)




Taping Specification

(Unit: mm)

Quantity : 4,000pcs/ reel (standard)



Reflow Soldering Conditions



- 1) The above profile temperature gives the maximum temperature of the LED resin surface. Please set the temperature so as to avoid exceeding this range.
- 2) Total times of reflow soldering process shall be no more than 2 times. When the second reflow soldering process is performed, intervals between the first and second reflow should be short as possible (while allowing some time for the component to return to normal temperature after the first reflow) in order to prevent the LED from absorbing moisture.
- 3) Temperature fluctuation to the LED during the pre-heating process shall be minimized.

Manual Soldering Conditions

Iron tip temp. 350 °C (MAX.)

Soldering time and frequency 3 s (MAX.)
1 time (MAX.)

Reliability Testing Result

Reliability Testing Result	Applicable Standard	Testing Conditions	Duration	Failure
Room Temp. Operating Life	EIAJ ED-4701/100(101)	Ta = 25°C, If = Maximum Rated Current	1,000 h	0/25
Resistance to Soldering Heat	EIAJ ED-4701/300(301)	Pre-heating : 150~180°C 120s Max. Operation Heating : 230°C 40s Max. Peak Temperature : 260°C	Twice	0/25
Temperature Cycling	EIAJ ED-4701/100(105)	Minimum Rated Storage Temperature(30min) ~Normal Temperature(15min) ~Maximum Rated Storage Temperature(30min) ~Normal Temperature(15min)	5 cycles	0/25
Wet High Temp. Storage Life	EIAJ ED-4701/100(103)	Ta = 60±2°C, RH = 90±5%	1,000 h	0/25
High Temp. Storage Life	EIAJ ED-4701/200(201)	Ta = Maximum Rated Storage Temperature	1,000 h	0/25
Low Temp. Storage Life	EIAJ ED-4701/200(202)	Ta = Minimum Rated Storage Temperature	1,000 h	0/25
Vibration, Variable Frequency	EIAJ ED-4701/400(403)	98.1m/s ² (10G), 100 ~ 2KHz sweep for 20min., XYZ each direction	2 h	0/10

Failure Criteria

Items	Symbols	Conditions	Failure criteria
Luminous Intensity	Iv	If Value of each product Luminous Intensity	Testing Min. Value < Spec. Min. Value x 0.5
Forward Voltage	V _F	If Value of each product Forward Voltage	Testing Max. Value ≥ Spec. Max. Value x 1.2
Reverse Current	I _R	V _R = Maximum Rated Reverse Voltage V	Testing Max. Value ≥ Spec. Max. Value x 2.5
Cosmetic Appearance	-	-	Occurrence of notable decoloration, deformation and cracking

Special Notice to Customers Using the Products and Technical Information Shown in This Data Sheet

- 1) The technical information shown in the data sheets are limited to the typical characteristics and circuit examples of the referenced products. It does not constitute the warranting of industrial property nor the granting of any license.
- 2) For the purpose of product improvement, the specifications, characteristics and technical data described in the data sheets are subject to change without prior notice. Therefore it is recommended that the most updated specifications be used in your design.
- 3) When using the products described in the data sheets, please adhere to the maximum ratings for operating voltage, heat dissipation characteristics, and other precautions for use. We are not responsible for any damage which may occur if these specifications are exceeded.
- 4) The products that have been described to this catalog are manufactured so that they will be used for the electrical instrument of the benchmark (OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument).
The application of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. needs a high reliability and safety, and the breakdown and the wrong operation might influence the life or the human body. Please consult us beforehand if you plan to use our product for the usages of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. except OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument.
- 5) In order to export the products or technologies described in this data sheet which are under the "Foreign Exchange and Foreign Trade Control Law," it is necessary to first obtain an export permit from the Japanese government.
- 6) No part of this data sheet may be reprinted or reproduced without prior written permission from Stanley Electric Co., Ltd.
- 7) The most updated edition of this data sheet can be obtained from the address below:
<http://www.stanley-components.com>