



- △ MATERIAL: CONNECTOR-NYLON UL94V-0 (GREEN).  
 CONTACTS-0.30 [.012] THICK COPPER ALLOY  
 (0.00076 [.000030] GOLD)
- CONTACTS ACCEPT 28 AWG WIRE WITH 1.52 [.060] MAX INSULATION DIAMETER.
  - CONTACTS MUST ACCEPT 0.64±0.03 [.025±.001] SQUARE POST AND REMAIN LOCKED IN POSITION.
  - IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY NOT APPEAR ON ALL ASSEMBLIES.
  - DIMENSIONS IN BRACKETS ARE IN INCHES.
  - HOUSING FEATURES ARE: FEED THRU WITH LOCKING RAMP.

LEAD FREE

71.12 [2.800]	28	5-641244-8
68.58 [2.700]	27	5-641244-7
66.04 [2.600]	26	5-641244-6
63.50 [2.500]	25	5-641244-5
60.96 [2.400]	24	5-641244-4
58.42 [2.300]	23	5-641244-3
55.88 [2.200]	22	5-641244-2
53.34 [2.100]	21	5-641244-1
50.80 [2.000]	20	5-641244-0
48.26 [1.900]	19	4-641244-9
45.72 [1.800]	18	4-641244-8
43.18 [1.700]	17	4-641244-7
40.64 [1.600]	16	4-641244-6
38.10 [1.500]	15	4-641244-5
35.56 [1.400]	14	4-641244-4
33.02 [1.300]	13	4-641244-3
30.48 [1.200]	12	4-641244-2
27.94 [1.100]	11	4-641244-1
25.40 [1.000]	10	4-641244-0
22.86 [.900]	9	3-641244-9
20.32 [.800]	8	3-641244-8
17.78 [.700]	7	3-641244-7
15.24 [.600]	6	3-641244-6
12.70 [.500]	5	3-641244-5
10.16 [.400]	4	3-641244-4
7.62 [.300]	3	3-641244-3
5.08 [.200]	2	3-641244-2
DIM A	NO. OF POSN	ASSEMBLY

CONTAINS LEAD

71.12 [2.800]	28	2-641244-8
68.58 [2.700]	27	2-641244-7
66.04 [2.600]	26	2-641244-6
63.50 [2.500]	25	2-641244-5
60.96 [2.400]	24	2-641244-4
58.42 [2.300]	23	2-641244-3
55.88 [2.200]	22	2-641244-2
53.34 [2.100]	21	2-641244-1
50.80 [2.000]	20	2-641244-0
48.26 [1.900]	19	1-641244-9
45.72 [1.800]	18	1-641244-8
43.18 [1.700]	17	1-641244-7
40.64 [1.600]	16	1-641244-6
38.10 [1.500]	15	1-641244-5
35.56 [1.400]	14	1-641244-4
33.02 [1.300]	13	1-641244-3
30.48 [1.200]	12	1-641244-2
27.94 [1.100]	11	1-641244-1
25.40 [1.000]	10	1-641244-0
22.86 [.900]	9	641244-9
20.32 [.800]	8	641244-8
17.78 [.700]	7	641244-7
15.24 [.600]	6	641244-6
12.70 [.500]	5	641244-5
10.16 [.400]	4	641244-4
7.62 [.300]	3	641244-3
5.08 [.200]	2	641244-2
DIM A	NO. OF POSN	ASSEMBLY

# METRIC

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm (INCHES)	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ± 0.13 [.005] 3 PLC ± 4 PLC ± ANGLES ±	DWN S. HOOVER 28-DEC-2004 CHK D. BOSSI 28-DEC-2004 APVD D. BOSSI 28-DEC-2004 PRODUCT SPEC 108-1050 APPLICATION SPEC 114-1019 WEIGHT CUSTOMER DRAWING	Tyco Electronics Corporation Harrisburg, Pa 17105-3608 NAME MTA .100 CONNECTOR ASSEMBLY, 28 AWG, STANDARD SIZE A1 CAGE CODE 00779 DRAWING NO C=641244 RESTRICTED TO SCALE 6:1 SHEET 1 OF 1 REV J
----------------------------	---	--	--