



Through  
**T/H**  
Hole

# .050" BOARD STACKER FW SERIES

## SPECIFICATIONS

For complete specifications see [www.samtec.com](http://www.samtec.com)?FW

**Insulator Material:**  
Black Liquid Crystal Polymer



**Terminal Material:**  
Phosphor Bronze

**Current Rating:**  
1.75A @ 80°C ambient

**Operating Temp Range:**  
-65°C to +125°C

**Plating:**  
Sn or Au over 50µ" (1,27µm) Ni

**Mates with:**  
CLP, FFSD, FLE

## APPLICATION SPECIFIC OPTION

Single row option available. Call Samtec.

Low profile and skyscraper styles

Variable board spacing

(1,27mm) .050" pitch



**Note:** This Series is non-standard, non-returnable.

**Processing:**  
Max Processing Temp:  
230°C for 60 seconds



[www.samtec.com](http://www.samtec.com)

FW	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	D	STACKER HEIGHT	POST HEIGHT	OPTION
	02 thru 50	Specify LEAD STYLE from chart	<p><b>-G</b> = 10µ" (0,25µm) Gold on post, Gold flash on tail</p> <p><b>-L</b> = 10µ" (0,25µm) Gold on post, Tin on tail</p> <p><b>-F</b> = Gold flash on post, Tin on tail</p>		<p><b>"XXX"</b> = Stacker Height (in inches)  Example: -250 = (6,35mm) .250"</p>	<p><b>"XXX"</b> = Post Height (in inches)  (1,65mm) .065" minimum  Example: -065 = (1,65mm) .065"</p>	<p><b>-ES</b> = End Shroud (-075 post height only. Mate only with CLP.) (5,46mm) .215" to (15,49mm) .610" stacker height only 9 pins/row minimum</p> <p><b>-EP</b> = End Shroud with Guide Post (-075 post height only. Mate only with CLP) (5,46mm) .215" to (15,49mm) .610" stacker height only 9 pins/row minimum</p>

  

LEAD STYLE	TAIL (B)
-01	(1,14) .045
-02	(1,91) .075
-04	(2,29) .090

  

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)