



54F/74F657 Octal Bidirectional Transceiver with 8-Bit Parity Generator/Checker and TRI-STATE® Outputs

General Description


The 'F657 contains eight non-inverting buffers with TRI-STATE® outputs and an 8-bit parity generator/checker. It is intended for bus-oriented applications. The buffers have a guaranteed current sinking capability of 24 mA (20 mA mil) at the A port and 64 mA (48 mA mil) at the B port.

Features


- 300 Mil 24-pin slimline DIP
- Combines 'F245 and 'F280A functions in one package
- TRI-STATE outputs
- B Outputs sink 64 mA (48 mA mil)
- 12 mA source current, B side
- Input diodes for termination effects

Ordering Code: See Section 5


Logic Symbols




TL/F/9584-5



TL/F/9584-2



TL/F/9584-3



TL/F/9584-1

Unit Loading/Fan Out: See Section 2 for U.L. definitions

Pin Names	Description	54F/74F	
		U.L. HIGH/LOW	Input I_{IH}/I_{IL} Output I_{OH}/I_{OL}
A ₀ -A ₇	Data Inputs/ TRI-STATE Outputs	4.5/0.15 150/40 (33.3)	90 μ A/- 90 μ A -3 mA/24 mA (20 mA)
B ₀ -B ₇	Data Inputs/ TRI-STATE Outputs	3.5/0.117 600/106.6 (80)	70 μ A/- 70 μ A -12 mA/64 mA (48 mA)
T/R	Transmit/Receive Input	2.0/0.067	40 μ A/- 40 μ A
OE	Enable Input	2.0/0.067	40 μ A/- 40 μ A
PARITY	Parity Input/ TRI-STATE Output	3.5/0.117 600/106.6 (80)	70 μ A/- 70 μ A -12 mA/64 mA (48 mA)
ODD/EVEN	ODD/EVEN Parity Input	1.0/0.033	20 μ A/- 20 μ A
ERROR	Error Output	600/106.6 (80)	-12 mA/64 mA (48 mA)

Functional Description

The Transmit/Receive (T/R) input determines the direction of the data flow through the bidirectional transceivers. Transmit (active HIGH) enables data from the A port to the B port; Receive (active LOW) enables data from the B port to the A port.

The Output Enable (OE) input disables the parity and ERROR outputs and both the A and B ports by placing them in a HIGH-Z condition when the Output Enable input is HIGH.

When transmitting (T/R HIGH), the parity generator detects whether an even or odd number of bits on the A port are HIGH and compares these with the condition of the parity select (ODD/EVEN). If the Parity Select is HIGH and an even number of A inputs are HIGH, the Parity output is HIGH.

In receiving mode (T/R LOW), the parity select and number of HIGH inputs on port B are compared to the condition of the Parity input. If an even number of bits on the B port are HIGH, the parity select is HIGH, and the PARITY input is HIGH, then ERROR will be HIGH to indicate no error. If an odd number of bits on the B port are HIGH, the parity select is HIGH, and the PARITY input is HIGH, the ERROR will be LOW indicating an error.

Function Table

Number of Inputs That Are High	Inputs			Input/ Output	Outputs	
	OE	T/R	ODD/EVEN		Parity	ERROR
0, 2, 4, 6, 8	L	H	H	H	Z	Transmit
	L	H	L	L	Z	Transmit
	L	L	H	H	H	Receive
	L	L	H	L	L	Receive
	L	L	L	H	L	Receive
	L	L	L	L	H	Receive
1, 3, 5, 7	L	H	H	L	Z	Transmit
	L	H	L	H	Z	Transmit
	L	L	H	H	L	Receive
	L	L	H	L	H	Receive
	L	L	L	H	H	Receive
	L	L	L	L	L	Receive
Immaterial	H	X	X	Z	Z	Z

H = HIGH Voltage Level

L = LOW Voltage Level

X = Immaterial

Z = High Impedance


Function Table

Inputs		Outputs
OE	T/R	
L	L	Bus B Data to Bus A
L	H	Bus A Data to Bus B
H	X	High-Z State

H = HIGH Voltage Level

L = LOW Voltage Level

X = Immaterial

Functional Block Diagram

TL/F/9584-4

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Storage Temperature	−65°C to +150°C		
Ambient Temperature under Bias	−55°C to +125°C		
Junction Temperature under Bias	−55°C to +175°C		
V _{CC} Pin Potential to Ground Pin	−0.5V to +7.0V		
Input Voltage (Note 2)	−0.5V to +7.0V		
Input Current (Note 2)	−30 mA to +5.0 mA		
Voltage Applied to Output in HIGH State (with V _{CC} = 0V)	−0.5V to V _{CC}		
Standard Output	−0.5V to +5.5V		
TRI-STATE Output	−0.5V to +5.5V		

Current Applied to Output in LOW State (Max)

twice the rated I_{OL} (mA)

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature

Military	−55°C to +125°C
Commercial	0°C to +70°C

Supply Voltage

Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

DC Electrical Characteristics

Symbol	Parameter	54F/74F			Units	V _{CC}	Conditions
		Min	Typ	Max			
V _{IH}	Input HIGH Voltage	2.0			V		Recognized as a HIGH Signal
V _{IL}	Input LOW Voltage		0.8		V		Recognized as a LOW Signal
V _{CD}	Input Clamp Diode Voltage		−1.2		V	Min	I _{IN} = −18 mA
V _{OH}	Output HIGH Voltage	54F 10% V _{CC} 54F 10% V _{CC} 54F 10% V _{CC} 74F 10% V _{CC} 74F 10% V _{CC} 74F 10% V _{CC} 74F 5% V _{CC} 74F 5% V _{CC} 74F 5% V _{CC}	2.5 2.4 2.0 2.5 2.4 2.0 2.7 2.7 2.0		V	Min	I _{OH} = −1 mA (A _n) I _{OH} = −3 mA (A _n , B _n , Parity, ERROR) I _{OH} = −12 mA (B _n , Parity, ERROR) I _{OH} = −1 mA (A _n) I _{OH} = −3 mA (A _n , B _n , Parity, ERROR) I _{OH} = −12 mA (B _n , Parity, ERROR) I _{OH} = −1 mA (A _n) I _{OH} = −3 mA (A _n , B _n , Parity, ERROR) I _{OH} = −15 mA (B _n , Parity, ERROR)
V _{OL}	Output LOW Voltage	54F 10% V _{CC} 54F 10% V _{CC} 74F 10% V _{CC} 74F 10% V _{CC}	0.5 0.55 0.5 0.55		V	Min	I _{OL} = 20 mA (A _n) I _{OL} = 48 mA (B _n , Parity, ERROR) I _{OL} = 24 mA (A _n) I _{OL} = 64 mA (B _n , Parity, ERROR)
I _{IH}	Input HIGH Current		20 40	μA	Max	V _{IN} = 2.7V (ODD/EVEN) V _{IN} = 2.7V (T/R, OE)	
I _{BVI}	Input HIGH Current Breakdown Test		100	μA	V _{CC} = 0	V _{IN} = 7.0V (T/R, OE, ODD/EVEN)	
I _{BVIT}	Input HIGH Current Breakdown Test (I/O)		1.0 2.0	mA	Max	V _{IN} = 5.5V (Parity, B _n) V _{IN} = 5.5 (A _n)	
I _{IL}	Input LOW Current		−20 −40	μA	Max	V _{IN} = 0.5V (ODD/EVEN) V _{IN} = 0.5V (T/R, OE)	
I _{OZH}	Output Leakage Current		50	μA	Max	V _{OUT} = 2.7V (ERROR)	
I _{OZL}	Output Leakage Current		−50	μA	Max	V _{OUT} = 0.5V (ERROR)	
I _{IH} + I _{OZH}	Output Leakage Current		70 90	μA	Max	V _{I/O} = 2.7V (B _n , Parity) V _{I/O} = 2.7V (A _n)	
I _{IL} + I _{OZL}	Output Leakage Current		−70 −90	μA	Max	V _{I/O} = 0.5V (B _n , Parity) V _{I/O} = 0.5V (A _n)	
I _{OS}	Output Short-Circuit Current	−60 −100	−150 −225	mA	Max	V _{OUT} = 0V (A _n) V _{OUT} = 0V (B _n , Parity, ERROR)	
I _{CEx}	Output HIGH Leakage Current		250 1.0 2.0	μA mA mA	Max Max Max	V _{OUT} = V _{CC} (ERROR) V _{OUT} = V _{CC} (B _n , Parity) V _{OUT} = V _{CC} (A _n)	
I _{IZZ}	Bus Drainage Test		500	μA	0.0V	V _{OUT} = V _{CC} (A _n , B _n , Parity, ERROR)	
I _{CCH}	Power Supply Current	101	125	mA	Max	V _O = HIGH	
I _{CCL}	Power Supply Current	112	150	mA	Max	V _O = LOW	
I _{CCZ}	Power Supply Current	109	145	mA	Max	V _O = HIGH Z	

AC Electrical Characteristics: See Section 2 for Waveforms and Load Configurations

Symbol	Parameter	74F			54F		74F		Units	Fig No		
		$T_A = +25^\circ C$ $V_{CC} = +5.0V$ $C_L = 50 pF$			$T_A, V_{CC} = MII$ $C_L = 50 pF$		$T_A, V_{CC} = Com$ $C_L = 50 pF$					
		Min	Typ	Max	Min	Max	Min	Max				
t_{PLH} t_{PHL}	Propagation Delay A_n to B_n , B_n to A_n	2.5 3.0	4.5 4.9	8.0 7.5	2.5 3.0	9.5 8.5	2.5 3.0	9.0 8.0	ns	2-3		
t_{PLH} t_{PHL}	Propagation Delay A_n to Parity	6.5 7.0	10.1 10.9	14.0 15.0	5.5 5.5	18.0 20.5	6.0 6.0	16.0 16.5	ns	2-3		
t_{PLH} t_{PHL}	Propagation Delay ODD/EVEN to PARITY	4.5 4.5	7.8 8.8	11.0 12.0	4.0 4.5	14.0 16.5	4.0 4.5	13.0 13.5	ns	2-3		
t_{PLH} t_{PHL}	Propagation Delay ODD/EVEN to ERROR	4.5 4.5	7.5 8.2	11.0 12.0	4.0 4.5	14.0 16.5	4.0 4.5	13.0 13.5	ns	2-3		
t_{PLH} t_{PHL}	Propagation Delay B_n to ERROR	8.0 8.0	14.0 15.0	20.5 21.5	7.5 7.5	27.0 28.5	7.5 7.5	23.0 23.5	ns	2-3		
t_{PLH} t_{PHL}	Propagation Delay PARITY to ERROR	7.0 7.5	10.8 11.8	15.5 16.5	6.0 6.5	20.0 22.0	6.0 7.5	17.0 18.5	ns	2-3		
t_{PZH} t_{PZL}	Output Enable Time \bar{OE} to A_n/B_n	3.0 4.0	5.0 6.5	8.0 10.0	2.5 3.5	11.0 13.5	2.5 3.5	9.5 11.0	ns	2-5		
t_{PHZ} t_{PLZ}	Output Disable Time \bar{OE} to A_n/B_n	1.0 1.0	4.5 4.9	8.0 7.5	1.0 1.0	9.5 8.5	1.0 1.0	9.0 8.0	ns	2-5		
t_{PZH} t_{PZL}	Output Enable Time \bar{OE} to ERROR (Note 1)	3.0 4.0	5.0 7.7	8.0 10.0	2.5 3.5	11.0 13.5	2.5 3.5	9.5 11.0	ns	2-5		
t_{PHZ} t_{PLZ}	Output Disable Time \bar{OE} to ERROR	1.0 1.0	4.5 4.9	8.0 7.5	1.0 1.0	9.5 8.5	1.0 1.0	9.0 8.0	ns	2-5		
t_{PZH} t_{PZL}	Output 8Enable Time \bar{OE} to PARITY	3.0 4.0	5.0 7.7	8.0 10.0	2.5 3.5	11.0 13.5	2.5 3.5	9.5 11.0	ns	2-5		
t_{PHZ} t_{PLZ}	Output Disable Time \bar{OE} to PARITY	1.0 1.0	4.6 5.1	8.0 7.5	1.0 1.0	9.5 8.5	1.0 1.0	9.0 8.0	ns	2-5		

Note 1: These delay times reflect the TRI-STATE recovery time only and not the signal time through the buffers or the parity check circuitry. To assure VALID information at the ERROR pin, time must be allowed for the signal to propagate through the drivers (B to A), through the parity check circuitry (same as A to PARITY), and to the ERROR output after the ERROR pin has been enabled (Output Enable times). VALID data at the ERROR pin \geq (A to PARITY) + (Output Enable Time).