

**Octal buffer/line driver with 5-volt tolerant inputs/outputs;
damping resistor; 3-state; inverting**
74LVC2240A**74LVCH2240A****FEATURES**

- 5-Volt tolerant inputs/outputs, for interfacing with 5-volt logic.
- Supply voltage range of 2.7 V to 3.6 V
- In accordance with JEDEC standard no. 8-1A.
- CMOS low power consumption
- Direct interface with TTL levels
- High impedance when $V_{cc} = 0$ V
- Bushold on all data inputs (LVCH2240A only).
- integrated 30Ω damping resistor.

DESCRIPTION

The 74LVC(H)2240A is a high-performance, low-power, low-voltage, Si-gate CMOS device and superior to most advanced CMOS compatible TTL families. Inputs can be driven from either 3.3 V or 5 V devices. In 3-state operation, outputs can handle 5 V. This feature allows the use of these devices as translators in a mixed 3.3 V/5 V environment.

The 74LVC(H)2240A is an octal inverting buffer/line driver with 3-state outputs. The 3-state outputs are controlled by the output enable inputs \overline{nOE} and $\overline{2OE}$. A HIGH on nOE causes the outputs to assume a high impedance OFF-state. Schmitt-trigger action at all inputs makes the circuit highly tolerant for slower input rise and fall times.

The '2240' is identical to the '2244' but has inverting outputs.

QUICK REFERENCE DATAGND = 0 V; $T_{amb} = 25^\circ C$; $t_i = t_o \leq 2.5$ ns

SYMBOL	PARAMETER	CONDITIONS	TYPICAL	UNIT
t_{PHL}/t_{PLH}	propagation delay $1A_n$ to $1Y_n$; $2A_n$ to $2Y_n$	$C_L = 50$ pF $V_{cc} = 3.3$ V	4.0	ns
C_i	input capacitance		5.0	pF
C_{PD}	power dissipation capacitance per buffer	notes 1 and 2	20	pF

Notes to the quick reference data

1. C_{PD} is used to determine the dynamic power dissipation (P_D in μW)

$$P_D = C_{PD} \times V_{cc}^2 \times f_i + \sum (C_L \times V_{cc}^2 \times f_o)$$
 where:
 f_i = input frequency in MHz; C_L = output load capacity in pF;
 f_o = output frequency in MHz; V_{cc} = supply voltage in V;
 $\sum (C_L \times V_{cc}^2 \times f_o)$ = sum of the outputs.
2. The condition is $V_i = GND$ to V_{cc}

ORDERING INFORMATION

TYPE NUMBER	PACKAGES			
	PINS	PACKAGE	MATERIAL	CODE
74LVC(H)2240AD	20	SO	plastic	SOT163-1
74LVC(H)2240ADB	20	SSOP	plastic	SOT339-1
74LVC(H)2240APW	20	TSSOP	plastic	SOT360-1

PINNING

PIN NO.	SYMBOL	NAME AND FUNCTION
1	$\overline{1OE}$	output enable input (active LOW)
2, 4, 6, 8	$1A_0$ to $1A_3$	data inputs
3, 5, 7, 9	$2Y_0$ to $2Y_3$	bus outputs
10	GND	ground (0 V)
17, 15, 13, 11	$2A_0$ to $2A_3$	data inputs
18, 16, 14, 12	$1Y_0$ to $1Y_3$	bus outputs
19	$\overline{2OE}$	output enable input (active LOW)
20	V_{cc}	positive power supply

FUNCTION TABLE

INPUTS		OUTPUT
nOE	nA_n	nY_n
L	L	H
L	H	L
H	X	Z

H = HIGH voltage level

L = LOW voltage level

X = don't care

Z = high impedance OFF-state

**Octal buffer/line driver with 5-volt tolerant
inputs/outputs; damping resistor; 3-state; inverting**

**74LVC2240A
74LVCH2240A**




Fig.1 Pin configuration.




Fig.2 Logic symbol.




Fig.3 IEC logic symbol.




Fig.4 Functional diagram.

Octal buffer/line driver with 5-volt tolerant
inputs/outputs; damping resistor; 3-state; inverting

74LVC2240A
74LVCH2240A

DC CHARACTERISTICS FOR 74LVC(H)2240A

For the DC characteristics see chapter "LVC(H)-A family characteristics", section "Family specifications".
 I_{CC} category: MSI

AC CHARACTERISTICS FOR 74LVC(H)2240A

GND = 0 V; $t_i = t_l \leq 2.5$ ns; $C_L = 50$ pF

SYMBOL	PARAMETER	T_{amb} (°C) -40 to +85			UNIT	TEST CONDITIONS	
		MIN.	TYP.	MAX.		V_{CC} (V)	WAVEFORMS
t_{PHL}/t_{PLH}	propagation delay $1A_n$ to $1Y_n$ $2A_n$ to $2Y_n$	—	—	—	ns	1.2	Figs 5, 7
		1.5	—	9.0		2.7	
		1.5	—	8.0		3.0 to 3.6	
t_{PZH}/t_{PZL}	3-state output enable time $1OE$ to $1Y_n$ $2OE$ to $2Y_n$	—	—	—	ns	1.2	Figs 6, 7
		1.5	—	10		2.7	
		1.5	—	9.0		3.0 to 3.6	
t_{PHZ}/t_{PLZ}	3-state output disable time $1OE$ to $1Y_n$ $2OE$ to $2Y_n$	—	—	—	ns	1.2	Figs 6, 7
		1.5	—	7.0		2.7	
		1.5	—	6.0		3.0 to 3.6	

Notes: All typical values are measured at $T_{amb} = 25$ °C.

* Typical values are measured at $V_{CC} = 3.3$ V.

**Octal buffer/line driver with 5-volt tolerant
inputs/outputs; damping resistor; 3-state; inverting**

**74LVC2240A
74LVCH2240A**

AC WAVEFORMS




Fig.5 Waveforms showing the input ($1A_n$, $2A_n$) to output ($1Y_n$, $2Y_n$) propagation delays.




Fig.6 Waveforms showing the 3-state enable and disable times.




Fig.7 Load circuitry for switching times.

- Notes:**
- (1) $V_M = 1.5 \text{ V}$ at $V_{CC} \geq 2.7 \text{ V}$
 $V_M = 0.5 \cdot V_{CC}$ at $V_{CC} < 2.7 \text{ V}$
 - (2) V_{OL} and V_{OH} are the typical output voltage drop that occur with the output load.
 - (3) $V_x = V_{OL} + 0.3 \text{ V}$ at $V_{CC} \geq 2.7 \text{ V}$
 $V_x = V_{OL} + 0.1 \cdot V_{CC}$ at $V_{CC} < 2.7 \text{ V}$
 - (4) $V_y = V_{OH} - 0.3 \text{ V}$ at $V_{CC} \geq 2.7 \text{ V}$
 $V_y = V_{OH} - 0.1 \cdot V_{CC}$ at $V_{CC} < 2.7 \text{ V}$