



SPECIFICATIONS

Current rating:	3 amps
Contact material:	Phosphor bronze
Contact resistance:	20 milliohms max.
Insulation material:	PBT, UL94V-0
Withstanding:	600VAC for 1 min.
Insulation resistance:	1,000 megohms min.
Operating temperature:	-40°C to +105°C

RoHS compliant

Series	No. of Rows	Positions	Plating	Tail Length
EARS	XX	XX	XX	OX
Elevated receptacle strip	01=Single row 02=Dual row	Single row 02-40 Double row 04-80	TN=Tin GD=Gold flash SG=Gold flash/tin	OA=11.00mm OC=14.75mm

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **EARS-XX-XX-XX-OA**
 Description: Header, 2.54 pitch, female, dual rows, DIP type, base 8.50mm high