

DEVICE TYPE NO.	POLARITY	P _D @ T _c =25°C	MAXIMUM RATINGS				ELECTRICAL CHARACTERISTICS				CASE
		WATTS	I _c AMPS	BV _{CB0}	BV _{CE}	BV _{EB0}	h _{FE} MIN.	I _c AMPS	V _{CE}	f MHZ *KHZ	
2N4900	PNP	25.0	1.00	80	80	5	100	.500	1	*30	T066
2N4901	PNP	87.0	5.00	40	40	5	20	1.00	2	4	T066
2N4902	PNP	87.0	5.00	60	60	5	20	1.00	2	4	T066
2N4903	PNP	87.0	5.00	80	80	5	20	1.00	2	4	T066
2N4904	PNP	87.0	5.00	40	40	5	25	2.50	2	4	T066
2N4905	PNP	87.0	5.00	60	60	5	25	2.50	2	4	T066
2N4906	PNP	87.0	5.00	80	80	5	25	2.50	4	4	T066
2N4907	PNP	150	10.0	40	40	5	20	4.00	4	4	T03
2N4908	PNP	150	10.0	60	60	5	20	4.00	4	4	T03
2N4909	PNP	150	10.0	80	80	5	20	4.00	4	4	T03
2N4910	NPN	25.0	1.00	40	40	5	20	.500	1	3	T066
2N4911	NPN	25.0	1.00	60	60	5	20	.500	1	3	T066
2N4912	NPN	25.0	1.00	80	80	5	20	.500	1	3	T066
2N4913	NPN	88.0	5.00	40	40	5	25	2.50	2	4	T03
2N4914	NPN	88.0	5.00	60	60	5	25	2.50	2	4	T03
2N4915	NPN	88.0	5.00	80	80	5	25	2.50	2	4	T03
2N4916	PNP	.200	.100	30	30	5	60	.001	1	400	T0106
2N4917	PNP	.200	.100	30	30	5	150	.001	1	450	T0106
2N4918	PNP	30.0	1.00	40	40	5	20	.500	1	3	T0126
2N4919	PNP	30.0	1.00	60	60	5	20	.500	1	3	T0126
2N4920	PNP	30.0	1.00	80	80	5	20	.500	1	3	T0126
2N4921	NPN	30.0	1.00	40	40	5	20	.500	1	3	T0126
2N4922	NPN	30.0	1.00	60	60	5	20	.500	1	3	T0126
2N4923	NPN	30.0	1.00	80	80	5	20	.500	1	3	T0126
2N4924	NPN	1.00	.200	100	100	5	40	.150	10	100	T039
2N4925	NPN	1.00	.200	150	150	5	40	.150	10	100	T039
2N4926	NPN	5.00	.050	200	200	7	20	.030	10	30	T039
2N4927	NPN	5.00	.050	250	250	7	20	.030	10	30	T039
2N4928	PNP	.600	.100	100	100	4	20	.001	10	100	T039
2N4929	PNP	1.00	.050	150	150	4	25	.010	10	100	T039
2N4931	PNP	1.00	.050	250	250	4	20	.010	10	20	T039
2N4943	NPN	.800	1.00	120	80	7	100	.150	10	150	T039
2N4957	PNP	.200	.030	30	30	3	20	.002	10	1200	T072
2N4958	PNP	.200	.030	30	30	3	20	.002	10	1000	T072
2N4959	PNP	.200	.030	30	30	3	20	.002	10	1000	T072
2N4960	NPN	.800	1.00	60	60	6.5	60	.001	10	250	T039
2N4961	NPN	.500	1.00	80	80	6.5	60	.001	10	250	T039
2N4962	NPN	.800	1.00	60	60	6.5	60	.001	10	250	T018
2N4963	NPN	.500	1.00	80	80	6.5	60	.001	10	250	T018
2N4964	PNP	.200	.100	50	40	5	40	.001	5	60	T0106
2N4965	PNP	.200	.100	50	40	5	100	.001	5	60	T0106
2N4966	NPN	.200	.030	50	40	6	40	.001	5	40	T0106
2N4967	NPN	.200	.030	50	40	6	100	.001	5	40	T0106
2N4968	NPN	.200	.030	30	25	6	40	.001	5	40	T0106
2N4969	NPN	.200	.500	50	30	5	20	.150	1	150	T0106
2N4970	NPN	.200	.500	50	30	5	100	.150	10	200	T0106
2N4971	PNP	.200	.500	50	40	5	40	.150	10	200	T0106
2N4972	PNP	.200	.500	50	40	5	100	.150	10	200	T0106
2N5038	NPN	140	20.0	150	90	7	20	12.0	5	60	T03
2N5039	NPN	140	20.0	120	75	7	20	10.0	5	60	T03
2N5042	PNP	.800	1.00	40	40	5	40	.150	1	500	T039
2N5055	PNP	.200	.100	12	12	4.5	12	.001	.5	550	T0105
2N5056	PNP	.360	.100	15	15	4.5	12	.001	.5	600	T018
2N5057	PNP	.360	.100	15	15	4.5	20	.001	.5	800	T018
2N5058	NPN	1.00	.150	300	300	7	35	.030	25	30	T039
2N5059	NPN	1.00	.150	250	250	6	30	.030	25	30	T039
2N5067	NPN	88.0	5.00	40	40	5	20	1.00	2	4	T03
2N5068	NPN	88.0	5.00	60	60	5	20	1.00	2	4	T03
2N5069	NPN	88.0	5.00	80	80	5	20	.050	2	4	T03
2N5109	NPN	2.50	.400	40	20	3	40	.050	15	1200	T039
2N5127	NPN	.200	.100	20	12	3	12	.002	10	150	T0106
2N5128	NPN	.200	.500	15	12	3	35	.050	10	150	T0105
2N5129	NPN	.300	.500	15	12	3	35	.050	10	150	T0106
2N5130	NPN	.200	.050	30	12	1	12	.008	10	450	T0106

