



SPECIFICATIONS

Current Rating: 3 Amp
 Contact Material: Phosphor Bronze
 Contact Resistance: 20mΩ Max.
 Insulation Material: Polyester, UL94V-0
 Insulation Resistance: 1000MΩ Min.
 Withstanding: 600V AC
 Operating Temp.: -40°C to +105°C

- Use PBT plastic material for 02~24 pins
- Use PA6T plastic for 25~40 pins

Series	Rows	Profile	Positions	Pin Length	Plating
ARS	XX		XX	CS (A/B)	
Receptacle Strip 2.54mm (.100") Pitch	01=Single, Straight 02=Dual, Straight 03=Single, R/A 04=Dual, R/A	Blank=8.5mm L3=5.65mm	Single Row=02-40 Dual Row=04-80	See drawing	TN=Tin GD=Gold SG=Duplex

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/30/08
				Checked	Lizzy	04/30/08
				Drawn	Tina	04/30/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **ARS-03-XX-XX-CS(XX)-XX**

Description: Single Row Right Angle Receptacle Strip