

74F2243

Quad Bus Transceiver with 25Ω Series Resistors in the Outputs

General Description

The 'F2243 is a quad bus transmitter/receiver which can be used for 4-line asynchronous 2-way data communications between data busses. It is designed to drive the capacitive inputs of MOS memory drivers, address drivers, clock drivers, and bus-oriented transmitters/receivers.

The 25Ω series resistors in the outputs reduce ringing and eliminate the need for external resistors.

Features

- 25Ω series resistors in outputs eliminate the need for external resistors
- 2-Way asynchronous data bus communication
- TRI-STATE® outputs
- 12 mA source current
- Designed to drive the capacitive inputs of MOS devices
- Guaranteed 4000V minimum ESD protection


Ordering Code:

See Section 11

Commercial	Package Number	Package Description
74F2243SC (Note 1)	M14A	14-Lead (0.150" Wide) Molded Small Outline, JEDEC


Note 1: Devices also available in 13" reel. Use suffix = SCX.

Logic Symbol



TL/F/9530-1

Connection Diagram



TL/F/9530-2

Unit Loading/Fan Out: See Section 2 for U.L. definitions

Pin Names	Description	74F	
		U.L. HIGH/LOW	Input I_{IH}/I_{IL} Output I_{OH}/I_{OL}
\bar{E}_1	Enable Input (Active LOW)	1.0/1.67	20 μ A/-1 mA
E_2	Enable Input (Active HIGH)	1.0/1.67	20 μ A/-1 mA
A_n, B_n	Inputs Outputs	3.5/2.67 750/20	70 μ A/-1.6 mA -15 mA/12 mA

Truth Table

Inputs		Inputs/Outputs	
\bar{E}_1	E_2	A_n	B_n
L	L	Input	$B = A$
L	H	N/A	N/A
H	L	Z	Z
H	H	$A = B$	Input

H = HIGH Voltage Level

L = LOW Voltage Level

Z = High Impedance

N/A = Not Allowed

Absolute Maximum Ratings (Note 1)

Storage Temperature	−65°C to +150°C		
Ambient Temperature under Bias	−55°C to +125°C		
Junction Temperature under Bias	−55°C to +175°C		
Plastic	−55°C to +150°C		
V _{CC} Pin Potential to Ground Pin	−0.5V to +7.0V		
Input Voltage (Note 2)	−0.5V to +7.0V		
Input Current (Note 2)	−30 mA to +5.0 mA		
Voltage Applied to Output in HIGH State (with V _{CC} = 0V)	−0.5V to V _{CC}		
Standard Output	−0.5V to +5.5V		
TRI-STATE Output	−0.5V to +5.5V		
Current Applied to Output in LOW State (Max)	twice the rated I _{OL} (mA)		
ESD Last Passing Voltage (Min)	4000V		

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature Commercial	0°C to +70°C
Supply Voltage Commercial	+4.5V to +5.5V

DC Electrical Characteristics

Symbol	Parameter	74F			Units	V _{CC}	Conditions
		Min	Typ	Max			
V _{IH}	Input HIGH Voltage	2.0			V		Recognized as a HIGH Signal
V _{IL}	Input LOW Voltage		0.8		V		Recognized as a LOW Signal
V _{CD}	Input Clamp Diode Voltage			−1.2	V	Min	I _{IN} = −18 mA
V _{OH}	Output HIGH Voltage 74F 10% V _{CC}	2.4			V	Min	I _{OH} = −3 mA (A _n , B _n)
	74F 10% V _{CC}	2.0					I _{OH} = −15 mA (A _n , B _n)
	74F 5% V _{CC}	2.7					I _{OH} = −3 mA (A _n , B _n)
V _{OL}	Output LOW Voltage		0.50		V	Min	I _{OL} = 1 mA (A _n , B _n)
			0.75				I _{OL} = 12 mA (A _n , B _n)
I _{IH}	Input HIGH Current			20	μA	Max	V _{IN} = 2.7V (E ₁ , E ₂)
I _{BVI}	Input HIGH Current Breakdown Test			100	μA	Max	V _{IN} = 7.0V (E ₁ , E ₂)
I _{BVIT}	Input HIGH Current Breakdown Test (I/O)			1.0	mA	Max	V _{IN} = 5.5V (A _n , B _n)
I _{IL}	Input LOW Current			−1.0	mA	Max	V _{IN} = 0.5V (E ₁ , E ₂)
I _{IH} + I _{OZH}	Output Leakage Current			70	μA	Max	V _{OUT} = 2.7V (A _n , B _n)
I _{IL} + I _{OZL}	Output Leakage Current			−1.6	mA	Max	V _{OUT} = 0.5V (A _n , B _n)
I _{OS}	Output Short-Circuit Current	−100	−225		mA	Max	V _{OUT} = 0V (A _n , B _n)
I _{CEx}	Output HIGH Leakage Current			250	μA	Max	V _{OUT} = V _{CC}
I _{CCH}	Power Supply Current	64	80		mA	Max	V _O = HIGH
I _{CCL}	Power Supply Current	64	90		mA	Max	V _O = LOW
I _{CCZ}	Power Supply Current	71	90		mA	Max	V _O = HIGH Z

AC Electrical Characteristics: See Section 2 for Waveforms and Load Configurations

Symbol	Parameter	74F		74F		Units	Fig. No.	
		$T_A = +25^\circ\text{C}$ $V_{CC} = +5.0\text{V}$ $C_L = 50 \text{ pF}$		$T_A, V_{CC} = \text{Com}$ $C_L = 50 \text{ pF}$				
		Min	Typ	Max	Min	Max		
t_{PLH}	Propagation Delay A_n to B_n , B_n to A_n	1.5	7.0	1.5	7.0	ns	2-3	
t_{PHL}		2.5	8.0	2.0	8.0			
t_{PZH}	Output Enable Time \bar{E}_1 to B_n , E_2 to A_n	1.5	9.0	1.0	9.5	ns	2-5	
t_{PZL}		2.5	11.5	2.5	12.0			
t_{PHZ}	Output Disable Time \bar{E}_1 to B_n , E_2 to A_n	1.5	9.0	1.0	9.5			
t_{PLZ}		1.5	8.5	1.5	9.5			