



Available Q2, 1995

Hex Non-Inverter

**DV74HC34
DV74HCT34**

This device contains six independent three-stage Non-inverters, each of which performs the logic $Y = A$ function.

- Output Drive Capability: 10 LSTTL Loads
- Outputs Directly Interface to CMOS, NMOS, and TTL
- Operating Voltage Range: 2 to 6 V for HC devices
- Low Input Current: 1 μ A
- DC, AC parameters guaranteed from -55°C to 125°C



**TRUTH TABLE
 $Y = A$**

Inputs	Outputs
A	Y
L	L
H	H

H = High Logic Level
L = Low Logic Level

34

ABSOLUTE MAXIMUM RATINGS

Maximum ratings are those values beyond which damage to the device may occur.

Symbol	Parameter	Value	Unit
V _{CC}	DC Supply Voltage (Referenced to GND)	-0.5 to +7.0	V
V _{IN}	DC Input Voltage (Referenced to GND)	-1.5 to V _{CC} +1.5	V
V _{OUT}	DC Output Voltage (Referenced to GND)	-0.5 to V _{CC} +0.5	V
I _{IN}	DC Input Current, per Pin	± 20	mA
I _{OUT}	DC Output Current, per Pin	± 25	mA
I _{CC}	DC Supply Current, V _{CC} and GND Pins	± 50	mA
T _{STG}	Storage Temperature Range	-65 to +150	°C
T _L	Lead Temperature, 1mm from Case for 10 Seconds	260	°C

GUARANTEED OPERATING CONDITIONS

Symbol	Parameter	Min	Max	Unit
V _{CC}	DC Supply Voltage, HC (HCT), Referenced to GND	2.0 (4.5)	6.0 (5.5)	V
V _{IN} , V _{OUT}	DC Input Voltage, Output Voltage, Referenced to GND	0	V _{CC}	V
T _A	Ambient Temperature	-55	+125	°C
t _r , t _f	Input Rise and Fall Time: HC: V _{CC} =2.0V HCT: V _{CC} =5.5V / HC: V _{CC} =4.5V HC: V _{CC} =6.0V	0 0 0	1000 500 400	ns

DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Conditions	V _{cc} V	Guaranteed Limits			Unit
				25°C to -55°C	≤85°C	≤125°C	
V _{IH}	High Level Input Voltage (Referenced to GND)	V _{OUT} = 0.1 V I _{OUT} ≤ 20 μA	2.0 4.5 6.0	1.5 3.15 4.2	1.5 3.15 4.2	1.5 3.15 4.2	V
V _{IL}	Low Level Input Voltage	V _{OUT} = V _{cc} - 0.1 V I _{OUT} ≤ 20 μA	2.0 4.5 6.0	0.5 1.35 1.8	0.5 1.35 1.8	0.5 1.35 1.8	V
V _{OH}	Minimum High Level Output Voltage	V _{IN} = V _{IL} I _{OUT} < 20 mA	2.0 4.5 6.0	1.9 4.4 5.9	1.9 4.4 5.9	1.9 4.4 5.9	V
		V _{IN} = V _{IL} , I _{OUT} < 4.0 mA I _{OUT} < 5.2 mA	4.5 6.0	3.98 5.48	3.84 5.34	3.70 5.20	V
V _{OL}	Maximum Low Level Output Voltage	V _{IN} = V _{IH} I _{OUT} ≤ 20 μA	2.0 4.5 6.0	0.1 0.1 0.1	0.1 0.1 0.1	0.1 0.1 0.1	V
		V _{IN} = V _{IH} I _{OUT} < 4.0 mA I _{OUT} < 5.2 mA	4.5 6.0	0.26 0.26	0.33 0.33	0.40 0.40	V
I _{IN}	Maximum Input Leakage Current	V _{IN} = V _{cc} or GND	6.0	± 0.1	± 1.0	± 1.0	μA
I _{cc}	Maximum Quiescent Supply Current	V _{IN} = V _{cc} or GND I _{OUT} ≤ 0 μA	6.0	2.0	20	40	μA

SWITCHING CHARACTERISTICS over full operating conditions (C_L=50 pF, Input t_f=t_r=6ns)

Symbol	Parameter	V _{cc} V	Guaranteed Limit			Unit
			25°C to -55°C	≤85°C	≤125°C	
t _{PLH} , t _{PHL}	Propagation Delay Time, Input A To Output Y	2.0 4.5 6.0	90 18 15	115 23 20	135 27 23	ns
t _{T LH} , t _{T HL}	Output Transition Time Any Output	2.0 4.5 6.0	75 15 13	95 19 16	110 22 19	ns
C _{IN}	Maximum Input Capacitance	—	10	10	10	pF
C _{PD}	Power Dissipation Capacitance (Per Inverter) Used to determine the no-load dynamic power consumption, P _D = C _{PD} V _{CC} ² f + I _{cc} V _{CC}	Typical @ 25°C, V _{CC} = 5 V			20	pF

DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Conditions	V _{cc} V	Guaranteed Limits			Unit
				25°C to -55°C	≤85°C	≤125°C	
V _{IH}	High Level Input Voltage (Referenced to GND)	V _{OUT} = 0.1 V I _{OUT} ≤ 20 μA	4.5 5.5	2 2	2 2	2 2	V
V _{IL}	Low Level Input Voltage	V _{OUT} = V _{cc} - 0.1 V I _{OUT} ≤ 20 μA	4.5 5.5	0.8 0.8	0.8 0.8	0.8 0.8	V

HCT- 34 (Contd.)

Symbol	Parameter	Conditions	V _{CC} V	Guaranteed Limits			Unit
				25°C to -55°C	≤85°C	≤125°C	
V _{OH}	Minimum High Level Output Voltage	V _{IN} = V _{IL} I _{OUT} ≤ 20 μA	4.5 5.5	4.4 5.4	4.4 5.4	4.4 5.4	V
		V _{IN} = V _{IL} I _{OUT} ≤ 4.0 mA	4.5	3.98	3.84	3.70	V
V _{OL}	Maximum Low Level Output Voltage	V _{IN} = V _{IH} I _{OUT} ≤ 20 μA	4.5 5.5	0.1 0.1	0.1 0.1	0.1 0.1	V
		V _{IN} = V _{IH} I _{OUT} ≤ 4.0 mA	4.5	0.26	0.33	0.40	V
I _{IN}	Maximum Input Leakage Current	V _{IN} = V _{CC} or GND	5.5	±0.1	±1.0	±1.0	μA
I _{CC}	Maximum Quiescent Supply Current	V _{IN} = V _{CC} or GND I _{OUT} = 0 μA	5.5	2.0	20	40	μA

Δ I _{CC}	Additional Quiescent Supply Current	V _{IN} =2.4 V, Any One Input V _{IN} =V _{CC} or GND, Other Inputs I _{out} =0 μA	5.5	≥-55°C	25°C to 125°C	mA
				2.9	2.4	


Total Supply Current = I_{CC}+ΣΔI_{CC}

SWITCHING CHARACTERISTICS over full operating conditions (V_{CC}=5V, C_L=50 pF, Input t_f=t_r=6ns)

Symbol	Parameter	Guaranteed Limit			Unit
		25°C to -55°C	≤85°C	≤125°C	
t _{PLH} t _{PHL}	Propagation Delay Time, Input A To Output Y	22	28	33	ns
t _{TLH} , t _{THL}	Output Transition Time Any Output	15	19	22	ns
C _{IN}	Maximum Input Capacitance	10	10	10	pF

C _{PD}	Power Dissipation Capacitance (Per Inverter) Used to determine the no-load dynamic power consumption, P _D = C _{PD} V _{CC} ² f + I _{CC} V _{CC}	Typical @ 25°C, V _{CC} = 5 V		pF
		22	22	

SWITCHING WAVEFORMS



Input and Output threshold voltage, V_T=50% V_{CC} for HC; 1.3V for HCT
V_H=V_{CC} for HC, 3V for HCT