



SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2006H-02P	2.00	4.60
A2006H-03P	4.00	6.60
A2006H-04P	6.00	8.60
A2006H-05P	8.00	10.60
A2006H-06P	10.00	12.60
A2006H-07P	12.00	14.60
A2006H-08P	14.00	16.60
A2006H-09P	16.00	18.60
A2006H-10P	18.00	20.60
A2006H-11P	20.00	22.60
A2006H-12P	22.00	24.60
A2006H-13P	24.00	26.60
A2006H-14P	26.00	28.60
A2006H-15P	28.00	30.60
A2006H-16P	30.00	32.60

		UNIT	SCALE	
		mm	1 of 1	
		DRAWN BY	APPROVED BY	
		陳耀元	董正一	
B3	REVISE	2006.05.20	2005.03.02	
B2	REVISE	2006.05.07	GENERAL TOLERANCE	
B1	REVISE	2006.02.17	X. X±0.25	ANGLE±
B0	NEW RELEASE	2005.10.07	X. XX±0.15	
REV.	DESCRIPTION	DATE	X. XXX±0.05	
			TITLE:	
			2.00mm PITCH HOUSING	
			DRAW NO. :	
			A2006H-XP	
			REV. B3	