

## 塑封普通整流二极管


反向电压 600 --- 800V

正向电流 1.2A

## General Purpose Plastic Rectifier

Reverse Voltage 600 to 800V

Forward Current 1.2A



## 特征 Features

- 低的反向漏电流 Low reverse leakage
- 较强的正向浪涌承受能力 High forward surge capability
- 高温焊接保证 High temperature soldering guaranteed:  
250°C/10 秒, 0.375" (9.5mm) 引线长度。  
250°C 10 seconds, 0.375" (9.5mm) lead length,
- 引线可承受5 磅 (2.3kg) 拉力。 5 lbs. (2.3kg) tension

## 机械数据 Mechanical Data

- 端子: 镀锡轴向引线 Terminals: Plated axial leads
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性 TA = 25°C 除非另有规定。

Maximum Ratings &amp; Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	ERC05 -06	ERC05 -08	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	$V_{RRM}$	600	800	V
最大均方根电压 Maximum RMS voltage	$V_{RMS}$	420	560	V
最大直流阻断电压 Maximum DC blocking voltage	$V_{DC}$	600	800	V
最大正向平均整流电流 Maximum average forward rectified current	$I_{F(AV)}$	1.2		A
峰值正向浪涌电流 8.3ms 单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	$I_{FSM}$	100		A
最大反向峰值电流 @TA = 75°C Maximum peak reverse current full cycle	$I_{R(AV)}$	30		μA
典型热阻 Typical thermal resistance	$R_{\theta JA}$	45		°C/W
工作结温和存储温度 Operating junction and storage temperature range	$T_j, T_{STG}$	-50 --- +150		°C

电特性 TA = 25°C 除非另有规定。


Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	ERC05 -06	ERC05 -08	单位 Unit
最大正向电压 Maximum forward voltage	$V_F$	1.2		V
最大反向电流 Maximum reverse current	$I_R$	10	100	μA
典型结电容 Type junction capacitance	$C_j$	22		pF

特性曲线 Characteristic Curves


正向特性曲线 (典型值)

TYPICAL FORWARD CHARACTERISTIC



正向电流降额曲线

FORWARD CURRENT DERATING CURVE



浪涌特性曲线 (最大值)

MAXIMUM NON REPETITIVE PEAK FORWARD SURGE CURRENT

