



TYPE	Maximum Peak Reverse Voltage	Maximum Average Rectified Current @ Half-Wave Resistive Load 60Hz		Maximum Forward Peak Surge Current @ 8.3ms Superimposed	Maximum Reverse Current @ PRV @ 25°C T _A	Maximum Forward Voltage @ 25°C T _A	
	PRV	I _o @ T _A		I _{FM} (Surge)	I _R	I _{FM}	V _{FM}
	V _{PK}	A _{AV}	°C	A _{PK}	μA _{dc}	A _{PK}	V _{PK}

1.5 AMPERES/RC-2



W005L	50	1.5	50	50	10	1.0	1.0
W01L	100	1.5	50	50	10	1.0	1.0
W02L	200	1.5	50	50	10	1.0	1.0
W04L	400	1.5	50	50	10	1.0	1.0
W06L	600	1.5	50	50	10	1.0	1.0
W08L	800	1.5	50	50	10	1.0	1.0
W10L	1000	1.5	50	50	10	1.0	1.0

2.0 AMPERES/RC-2



RC201	50	2.0	50	50	10	1.0	1.0
RC202	100	2.0	50	50	10	1.0	1.0
RC203	200	2.0	50	50	10	1.0	1.0
RC204	400	2.0	50	50	10	1.0	1.0
RC205	600	2.0	50	50	10	1.0	1.0
RC206	800	2.0	50	50	10	1.0	1.0
RC207	1000	2.0	50	50	10	1.0	1.0

2.0 AMPERES/RS-2



RS201	50	2.0	50	50	10	1.0	1.0
RS202	100	2.0	50	50	10	1.0	1.0
RS203	200	2.0	50	50	10	1.0	1.0
RS204	400	2.0	50	50	10	1.0	1.0
RS205	600	2.0	50	50	10	1.0	1.0
RS206	800	2.0	50	50	10	1.0	1.0
RS207	1000	2.0	50	50	10	1.0	1.0
KBP005	50	2.0	50	50	10	1.0	1.0
KBP01	100	2.0	50	50	10	1.0	1.0
KBP02	200	2.0	50	50	10	1.0	1.0
KBP04	400	2.0	50	50	10	1.0	1.0
KBP06	600	2.0	50	50	10	1.0	1.0
KBP08	800	2.0	50	50	10	1.0	1.0
KBP10	1000	2.0	50	50	10	1.0	1.0