



SPECIFICATIONS
 Voltage rating: 250VAC, 350VDC
 Current rating: 5 amps AC/DC
 Body material: Nylon 66, UL94V-0
 Contact resistance: 10 milliohms max.
 Insulation resistance: 1,000 megohms min.
 Withstanding: 1,500VAC for 1 min.
 Temperature range: -25°C to +85°C

| Dimensions (mm) | |
|-----------------|----------|
| P | 4.2 |
| P1 | 4.2±0.1 |
| W | 11.6±0.1 |
| W1 | 9.6±0.1 |
| W2 | 7.6±0.1 |
| H | 19.6±0.1 |
| H1 | 10.7±0.1 |
| L | 5.5±0.1 |
| L1 | 2.8±0.1 |

| Dimensions (mm) | | |
|-----------------|-------|-------|
| Pos. | A±0.3 | B±0.2 |
| 02 | 5.4 | — |
| 04 | 9.6 | 4.2 |
| 06 | 13.8 | 8.4 |
| 08 | 18.0 | 12.6 |
| 10 | 22.2 | 16.8 |
| 12 | 26.4 | 21.0 |
| 14 | 30.6 | 25.2 |
| 16 | 34.8 | 29.4 |
| 18 | 39.0 | 33.6 |
| 20 | 43.4 | 37.8 |
| 22 | 47.4 | 42.0 |
| 24 | 51.9 | 46.2 |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 08/10/99 |
| | | | | Checked | Lizzy | 08/10/99 |
| | | | | Drawn | Tina | 08/10/99 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | | | | UNIT: mm |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-2416-XX**

Description: PS-2 terminal