















130 ... 230 MHz
class C for FM mobile applications

TYPE	PACKAGE	CONFIG.	V _{CC} (V)	P _{out} min (W)	f _o (MHz)	P _{in} (W)	G _p min (dB)	η _c min (%)	
SD 1134-5	.280 4LSL (B)	CE	7,5	0,5	150	0,1	7	—	
SD 1080-2	XO-72 SL	CE	7,5	0,75	175	0,1	8	—	
SD 1115-2	TO-117 SL	CE	7,5	2	175	0,25	8	—	
SD 1012-4	.280 4LSL (B)	CE	7,5	2,5	175	0,79	5	—	
SD 1135-3	.280 4LSL (B)	CE	7,5	2,5	150	0,22	11	—	
2N 4427	TO-39	CE	12	1	175	0,1	10	—	
SD 1484-10	TO-46	CE	12,5	1	175	0,1	10	—	
SD 1127	TO-39	CE	12,5	4	175	0,4	10	—	
2N 6080	.380 4L STUD	CE	12,5	4	175	0,25	12	60	
SD 1574	TO-220	CE	12,5	5	175	0,5	10	—	
SD 1012-3	.380 4LFL	CE	12,5	6	175	0,25	9	—	
SD 1133	.380 4L STUD	CE	12,5	10	175	1	10	—	
SD 1143	.380 4L STUD	CE	12,5	10	175	1	10	—	
SD 1143-1	.380 4LFL	CE	12,5	10	175	1	10	—	
2N 6081	.380 4L STUD	CE	12,5	15	175	3,5	6,3	60	
SD 1014-6	.380 4LFL	CE	12,5	15	175	3,5	6,3	—	
SD 1575	TO-220	CE	12,5	15	175	4	6,3	—	
2N 6082	.380 4L STUD	CE	12,5	25	175	6	6,2	50	
SD 1229-1	.380 4LFL	CE	12,5	25	175	7,9	5	—	
SD 1272	.380 4L STUD	CE	12,5	25	175	3	9,2	—	
SD 1272-2	.380 4LFL	CE	12,5	25	175	3	9,2	—	
SD 1274	.380 4L STUD	CE	12,5	30	175	3	10	—	
SD 1274-1	.380 4L FL	CE	12,5	30	175	3	10	—	
2N 6083	.380 4L STUD	CE	12,5	30	175	8,1	5,7	50	
SD 1577	TO-220	CE	12,5	30	175	9	5,2	—	
2N 6084	.380 4L STUD	CE	12,5	40	175	14	4,5	50	
SD 1018-6	.380 4LFL	CE	12,5	40	175	14	4,5	70	
SD 1018-15	.380 4LFL	CE	12	40	175	12	4,5	70	
SD 1278	.380 4L STUD	CE	12,5	40	175	10	6	—	
SD 1275	.380 4L STUD	CE	12,5	40	175	5	9	—	
SD 1275-1	.380 4L FL	CE	12,5	40	175	5	9	—	
SD 1428*	.500 6LFL	CE	12,5	45	175	11,3	6,5	50	
SD 1477*	.500 6LFL	CE	12,5	100	175	25	6	—	
SD 1441*	.500 6LFL	CE	12,5	150	175	40	5	—	
SD 1021	.380 4L STUD	CE	12,5	5,5	230	1,3	6,2	60	
SD 1022	.380 4L STUD	CE	12,5	30	230	5,5	7,4	60	
2N 5589	.380 NARROW 4L STUD	CE	13,6	3	175	0,2	8,2	50	
2N 3924	TO-39	CE	13,6	4	175	1	6	70	
2N 3926	TO-60	CE	13,6	7	175	1,7	5,4	70	
2N 5590	.380 4L STUD	CE	13,6	10	175	2,3	5,2	50	
2N 3927	TO-60	CE	13,6	12	175	4	4,8	80	
2N 5591	.380 4L STUD	CE	13,6	25	175	8,3	4,4	50	
SD 1273	.380 4L STUD	CE	13,6	40	160	5	9	55	
2N 3553	TO-39	CE	28	2,5	175	0,25	10	—	
2N 5641	.380 NARROW 4L STUD	CE	28	7	175	0,45	8,4	60	
2N 3632	TO-60	CE	28	13,5	175	3,5	5,8	—	
2N 5642	.380 4L STUD	CE	28	20	175	1,4	8,2	60	
2N 5643	.380 4L STUD	CE	28	40	175	6,6	7,6	60	
THB 94	.500 4LFL	CE	28	50 §	175	10	7	65	
THY 94	.550 4L STUD	CE	28	50 §	175	10	7	65	
TH 564	.500 6LFL	CE	28	150	175	15	10	60	

* Internally input matched.
§ : Typical value.