



Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

Features

- High reliability
- SOD-323 surface mount package
- Low reverse current level
- For Surface Mount Applications
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0


Maximum Ratings

- Junction Temperature: 150°C
- Storage Temperature: -65°C to +150°C
- Power Dissipation: 200mW
- Maximum Forward Voltage @ 100mA: 1.5Volts

**BZX384C2V4
THRU
BZX384C39**


**Small Signal
Zener Diode
2.4 to 39 Volts**

SOD323



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.090	.107	2.30	2.70	
B	.063	.071	1.60	1.80	
C	.045	.053	1.15	1.35	
D	.031	.045	0.80	1.15	
E	.010	.016	0.25	0.40	
G	.004	.018	0.10	0.45	
H	.004	.010	0.10	0.25	
J	-----	.006	-----	0.15	

SUGGESTED SOLDER PAD LAYOUT



Type	Marking	Zener Voltage Range		Dynamic Resistance			Temperature Coefficient of Zener Voltage	Reverse Leakage current	
		I_{ZT} mA	for V_{ZT} V	r_{zT}	r_{zK}	at I_{ZK} mA	$v_Z @ I_{ZT}$ $10^{-4}/$	I_R μA	V_R V
2V4	W1	5	2.2~2.6	<100	275	1	-9~-4	50	1
2V7	W2	5	2.5~2.9	<100	600	1	-9~-4	20	1
3V0	W3	5	2.8~3.2	<95	600	1	-9~-3	10	1
3V3	W4	5	3.1~3.5	<95	600	1	-8~-3	5	1
3V6	W5	5	3.4~3.8	<90	600	1	-8~-3	5	1
3V9	W6	5	3.7~4.1	<90	600	1	-7~-3	3	1
4V3	W7	5	4.0~4.6	<90	600	1	-6~-1	3	1
4V7	W8	5	4.4~5.0	<80	500	1	-5~2	3	2
5V1	W9	5	4.8~5.4	<60	480	1	-3~4	2	2
5V6	WA	5	5.2~6.0	<40	400	1	-2~6	1	2
6V2	WB	5	5.8~6.6	<10	150	1	-1~7	3	4
6V8	WC	5	6.4~7.2	<15	80	1	2~7	2	4
7V5	WD	5	7.0~7.9	<15	80	1	3~7	1	5
8V2	WE	5	7.7~8.7	<15	80	1	4~7	0.7	5
9V1	WF	5	8.5~9.6	<15	100	1	5~8	0.5	6
10	WG	5	9.4~10.6	<20	150	1	5~8	0.2	7
11	WH	5	10.4~11.6	<20	150	1	5~9	0.1	8
12	WI	5	11.4~12.7	<25	150	1	6~9	0.1	8
13	WK	5	12.4~14.1	<30	170	1	7~9	0.1	8
15	WL	5	13.8~15.6	<30	200	1	7~9	0.05	0.7V _{Znom}
16	WM	5	15.3~17.1	<40	200	1	8~9.5	0.05	0.7V _{Znom}
18	WN	5	16.8~19.1	<45	225	1	8~9.5	0.05	0.7V _{Znom}
20	WO	5	18.8~21.2	<55	225	1	8~10	0.05	0.7V _{Znom}
22	WP	5	20.8~23.3	<55	250	1	8~10	0.05	0.7V _{Znom}
24	WR	5	22.8~25.6	<70	250	1	8~10	0.05	0.7V _{Znom}
27	WS	2	25.1~28.9	<80	300	0.5	8~10	0.05	0.7V _{Znom}
30	WT	2	28~32	<80	300	0.5	8~10	0.05	0.7V _{Znom}
33	WU	2	31~35	<80	325	0.5	8~10	0.05	0.7V _{Znom}
36	WW	2	34~38	<90	350	0.5	8~10	0.05	0.7V _{Znom}
39	WX	2	37~41	<130	350	0.5	10~12	0.05	0.7V _{Znom}

¹⁾ Measured with pulses $T_p=20mS$

²⁾ Tighter tolerances available request: BZX384B2V4 ~ BZX384B39

³⁾ Valid provided that electrodes are kept at ambient temperature, $T=25$.



Micro Commercial Components

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.

Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

*****APPLICATIONS DISCLAIMER*****

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.