


Specifications:

Contact rating: 2A, 36V DC
 Contact resistance: 50mOhm max.
 Insulation resistance: 1 000MOhm min. at 500V DC
 Dielectric strength: 2 000V RMS (50/60Hz)
 Operating temperature: -40°C to +85°C
 Electrical life: 50 000 cycles
 Operating force: 4N max.
 Torque: 5-14Nm max. applied to nut
 Switching function: off - mom
 IP class: IP65 protection
 LED supply voltage: 3V DC

Material:
 Bushing / button: stainless steel with
 varnished polished
 Contact: silver alloy
 Nut: nickel plated brass
 Base: PBT

CONTACT CONFIGURATION



| x | LED colour |
|---|------------|
| R | red |
| G | green |
| Y | yellow |
| O | orange |
| B | blue |
| W | white |



| Tolerances:0.00 to 30.00: ±0.20mm | | | Date | Name | MAV01LB32M3FRx3V |
|-----------------------------------|-------|------|----------------|------|------------------|
| 30.01 to 80.00: ±0.25mm | | | 01/10 | dr | |
| | | | | | 30 19 87 |
| | | | | | |
| | | | | | |
| | | | | | |
| Operating temperature | 05/11 | dr | knitter-switch | | 30 19 87 |
| Operating temperature | 04/10 | dr | | | |
| Modifications | Date | Name | | | Page |
| | | | | | 1/1 |