



Poles	DIMENSION(mm)	
	A	B
2	2.50	7.30
3	5.00	9.90
4	7.50	12.50
5	10.00	14.80
6	12.50	17.40
7	15.00	20.10
8	17.50	22.20

ELETRICAL:

CURRENT RATING: 3A AC/DC
 VOLTAGE RATING: 250V AC/DC
 CONTACT RESISTANCE: 20 mΩ max.
 WITHSTANDING VOLTAGE: 1000 VAC for 1 min.
 INSULATION RESISTANCE: 1000 MΩ min.
 TEMPERATURE RANGE: -25°C to 85°C

MATERIAL:

CONTACT: Copper Alloy, Tin Plated
 BASE: Nylon 66 UL94V-0

HOW TO ORDER:

W 0 4 3 - X X 4 1 - 0 0 - Z

OF POSITIONS: 02 - 08 HOUSING & TERMINATION TYPE: 4 - HOUSING FOR CONTACTS RoHS COMPLIANT

Rev	Drawn	Checked	Approved	Date			
0	A.M.	S.M.	S.M.	01/10/02	SMP TECHNOLOGY, INC.		
A	B.S.	S.M.	S.M.	08/04/08			
					Contact Housing for (Contact P/N:w043-0042-00)		
TOL. DEC.	.X +/- 0.2	.XX +/- 0.15	.XXX +/- 0.10	ANGLE +/-	UNIT: mm	P/N:W043-XX41-000-Z	Pg: 1