


500 mW DO-35 Hermetically Sealed Glass Zener Voltage Regulators



Maximum Ratings (Note 1)

Rating	Symbol	Value	Units
Maximum Steady State Power Dissipation @TL≤75°C, Lead Length = 3/8"	P _D	500	mW
Derate Above 75°C		4.0	mW/°C
Operating and Storage Temperature Range	T _J , T _{stg}	-65 to +200	°C

Note 1: Some part number series have lower JEDEC registered ratings.



L = Logo
 xxxxB = 1NxxxxB Device Code

Specification Features:

- Zener Voltage Range = 2.4V to 110V
- ESD Rating of Class 3 (>6 KV) per Human Body Model
- DO-35 Package (DO-204AH)
- Double Slug Type Construction
- Metallurgical Bonded Construction
- RoHS Compliant
- Solder Hot Dip Tin (Sn) Lead Finish


Specification Features:

Case : Double slug type, hermetically sealed glass

Finish : All external surfaces are corrosion resistant and leads are readily solderable

Polarity : Cathode indicated by polarity band

Mounting: Any



ELECTRICAL CHARACTERIZATION ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Device (Note 2.)	Device Marking	Zener Voltage (Note 3.)			Zener Impedance (Note 4.)			Leakage Current		I_{ZM} (Note 5.)	
		V_Z (Volts)			$@I_{ZT}$	$Z_{ZT} @I_{ZT}$	$Z_{ZK} @I_{ZK}$	$I_R @V_R = 1V$			
		Min	Nom	Max	(mA)	(Ω)	(Ω)	(mA)	(μA)		(Volts)
1N5985B	1N5985B	2.280	2.4	2.520	5	100	1800	0.25	100	1	208
1N5986B	1N5986B	2.565	2.7	2.835	5	100	1900	0.25	75	1	185
1N5987B	1N5987B	2.850	3.0	3.150	5	95	2000	0.25	50	1	167
1N5988B	1N5988B	3.135	3.3	3.465	5	95	2200	0.25	25	1	152
1N5989B	1N5989B	3.420	3.6	3.780	5	90	2300	0.25	15	1	139
1N5990B	1N5990B	3.705	3.9	4.095	5	90	2400	0.25	10	1	128
1N5991B	1N5991B	4.085	4.3	4.515	5	88	2500	0.25	5	1	116
1N5992B	1N5992B	4.465	4.7	4.935	5	70	2200	0.25	3	1.5	106
1N5993B	1N5993B	4.845	5.1	5.355	5	50	2050	0.25	2	2	98
1N5994B	1N5994B	5.320	5.6	5.880	5	25	1800	0.25	2	3	89
1N5995B	1N5995B	5.890	6.2	6.510	5	10	1300	0.25	1	4	81
1N5996B	1N5996B	6.460	6.8	7.140	5	8	750	0.25	1	5.2	74
1N5997B	1N5997B	7.125	7.5	7.875	5	7	600	0.25	0.5	6	67
1N5998B	1N5998B	7.790	8.2	8.610	5	7	600	0.25	0.5	6.5	61
1N5999B	1N5999B	8.645	9.1	9.555	5	10	600	0.25	0.1	7	55
1N6000B	1N6000B	9.50	10	10.50	5	15	600	0.25	0.1	8	50
1N6001B	1N6001B	10.45	11	11.55	5	18	600	0.25	0.1	8.4	45
1N6002B	1N6002B	11.40	12	12.60	5	22	600	0.25	0.1	9.1	42
1N6003B	1N6003B	12.35	13	13.65	5	25	600	0.25	0.1	9.9	38
1N6004B	1N6004B	14.25	15	15.75	5	32	600	0.25	0.1	11	33
1N6005B	1N6005B	15.20	16	16.80	5	36	600	0.25	0.1	12	31
1N6006B	1N6006B	17.10	18	18.90	5	42	600	0.25	0.1	14	28
1N6007B	1N6007B	19.00	20	21.00	5	48	600	0.25	0.1	15	25
1N6008B	1N6008B	20.90	22	23.10	5	55	600	0.25	0.1	17	23
1N6009B	1N6009B	22.80	24	25.20	5	62	600	0.25	0.1	18	21
1N6010B	1N6010B	25.65	27	28.35	5	70	600	0.25	0.1	21	19
1N6011B	1N6011B	28.50	30	31.50	5	78	600	0.25	0.1	23	17
1N6012B	1N6012B	31.35	33	34.65	5	88	700	0.25	0.1	25	15
1N6013B	1N6013B	34.20	36	37.80	5	95	700	0.25	0.1	27	14
1N6014B	1N6014B	37.05	39	40.95	2	130	800	0.25	0.1	30	13
1N6015B	1N6015B	40.85	43	45.15	2	150	900	0.25	0.1	33	12
1N6016B	1N6016B	44.65	47	49.35	2	170	1000	0.25	0.1	36	11
1N6017B	1N6017B	48.45	51	53.55	2	180	1300	0.25	0.1	39	9.8
1N6018B	1N6018B	53.20	56	58.80	2	200	1400	0.25	0.1	43	8.9
1N6019B	1N6019B	58.90	62	65.10	2	225	1400	0.25	0.1	47	8.0
1N6020B	1N6020B	64.60	68	71.40	2	240	1600	0.25	0.1	52	7.4
1N6021B	1N6021B	71.25	75	78.75	2	265	1700	0.25	0.1	56	6.7
1N6022B	1N6022B	77.90	82	86.10	2	280	2000	0.25	0.1	62	6.1
1N6023B	1N6023B	86.45	91	95.55	2	300	2300	0.25	0.1	69	5.5
1N6024B	1N6024B	95.00	100	105.0	1	500	2600	0.25	0.1	76	5.0
1N6025B	1N6025B	104.5	110	115.5	1	650	3000	0.25	.1	82	4.5

 VF Forward Voltage = 1.5V max @ $I_F = 100\text{mA}$ for all types

2. TOLERANCE AND VOLTAGE DESIGNATION

The type numbers listed have a standard tolerance on the nominal zener voltage of $\pm 5\%$.

3. ZENER VOLTAGE (V_Z) MEASUREMENT

The zener voltage (V_Z) is tested under pulse conditions such that T_J is no more than 2°C above T_A .

4. ZENER IMPEDANCE (Z_Z) DERIVATION


Z_{ZT} and Z_{ZK} are measured by dividing the AC voltage drop across the device by the AC current applied. The specified limits are for $I_{Z(AC)} = 0.1 I_{Z(DC)}$ with AC frequency = 60Hz.

5. MAXIMUM ZENER CURRENT RATINGS (I_{ZM})

This data was calculated using nominal voltages. The maximum current handling capability on a worst case basis is limited by the actual zener voltage at the operation point and the power duration curve.

Package Outline

Case Outline




DIM	DO-35			
	Millimeters		Inches	
	Min	Max	Min	Max
A	0.46	0.56	0.018	0.022
B	3.05	5.08	0.120	0.200
C	25.40	38.10	1.000	1.500
D	1.52	2.29	0.060	0.090

Note: all dimensions are within JEDEC standard.

This datasheet presents technical data of Tak Cheong's Zener Diodes. Complete specifications for the individual devices are provided in the form of datasheets. A comprehensive Selector Guide is included to simplify the task of choosing the best set of components required for a specific application. For additional information, please visit our website <http://www.takcheong.com>.

Although information in this datasheet has been carefully checked, no responsibility for the inaccuracies can be assumed by Tak Cheong. Please consult your nearest Tak Cheong's sales office for further assistance.

Tak Cheong reserves the right to make changes without further notice to any products herein to further improve reliability, function or design, cost and productivity.

TAK CHEONG® and  are registered trademarks of Tak Cheong Electronics (Holdings) Co., Ltd.