



SYNSEMI SEMICONDUCTOR


Licensed by **ON Semiconductor**,
a trademark of **Semiconductor
Components Industries, LLC** for
Zener Technology and Products.

500 mW DO-35 Hermetically Sealed Glass Zener Voltage Regulators

Maximum Ratings (Note 1)

Rating	Symbol	Value	Unit
Maximum Steady State Power Dissipation @ $T_L \leq 75^\circ\text{C}$, Lead Length = 3/8"	P_D	500	mW
Derate Above 75°C		4.0	mW/ $^\circ\text{C}$
Operating and Storage Temperature Range	T_J, T_{sg}	-65 to +200	$^\circ\text{C}$

1. Some part number series have lower JEDEC registered ratings.



Specification Features

- Zener Voltage Range = 2.4 V to 12 V
- ESD Rating of Class 3 (>16 KV) per Human Body Model
- DO-35 Package (DO-204AH)
- Double Slug Type Construction
- Metallurgical Bonding



Mechanical Characteristics

Case : Double slug type, hermetically sealed glass

Finish : All external surfaces are corrosion resistant and leads are readily solderable.

Polarity : Cathode indicated by polarity band

Mounting: Any

Maximum Lead Temperature for Soldering Purposes

230°C, 1/16" from the case for 10 seconds

MARKING DIAGRAM



L = Logo
 1NxxxxA = Device Code
 Y = Year
 WW = Work Week

Ordering Information

Device	Package	Shipping
1NxxxxA	Axial Lead	3000 Units / Box
1NxxxxARL	Axial Lead	5000 Units / Tape & Reel
1NxxxxARL2 *	Axial Lead	5000 Units / Tape & Reel
1NxxxxARA1 !	Lead Form	3000 Units / Radial Tape & Ammo
1NxxxxARA2 i	Lead Form	3000 Units / Radial Tape & Ammo
1NxxxxATA	Axial Lead	5000 Units / Tape & Ammo
1NxxxxATA2 *	Axial Lead	5000 Units / Tape & Ammo
1NxxxxARR1 !	Lead Form	3000 Units / Radial Tape & Reel
1NxxxxARR2 i	Lead Form	3000 Units / Radial Tape & Reel

* The "2" suffix refers to 26 mm tape spacing.

! Polarity band **up** with cathode lead off first.


i Polarity band **down** with cathode lead off first.

Devices listed in **bold italic** are Synsemi **Preferred** devices. **Preferred** devices are recommended choices for future use and best overall value.

1N4370A Series

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 1.5 \text{ V Max} @ I_F = 200 \text{ mA}$ for all types)

Symbol	Parameter
V_Z	Reverse Zener Voltage @ I_{ZT}
I_{ZT}	Reverse Current
Z_{ZT}	Maximum Zener Impedance @ I_{ZT}
I_{ZM}	Maximum DC Zener Current
I_R	Reverse Leakage Current @ V_R
V_R	Reverse Voltage
I_F	Forward Current
V_F	Forward Voltage @ I_F



ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 1.5 \text{ V Max} @ I_F = 200 \text{ mA}$ for all types)

Device (Note 2.)	Device Marking	Zener Voltage (Note 3.)			Z_{ZT} (Note 4.) @ I_{ZT}	I_{ZM} (Note 5.)	$I_R @ V_R = 1 \text{ V}$		
		V _Z (Volts)		@ I_{ZT}			$T_A = 25^\circ\text{C}$	$T_A = 150^\circ\text{C}$	
		Min	Nom	Max	(mA)	(mA)	(μA)	(μA)	
1N4370A	1N4370A	2.28	2.4	2.52	20	30	150	100	200
1N4371A	1N4371A	2.57	2.7	2.84	20	30	135	75	150
1N4372A	1N4372A	2.85	3.0	3.15	20	29	120	50	100
1N746A	1N746A	3.14	3.3	3.47	20	28	110	10	30
1N747A	1N747A	3.42	3.6	3.78	20	24	100	10	30
1N748A	1N748A	3.71	3.9	4.10	20	23	95	10	30
1N749A	1N749A	4.09	4.3	4.52	20	22	85	2	30
1N750A	1N750A	4.47	4.7	4.94	20	19	75	2	30
1N751A	1N751A	4.85	5.1	5.36	20	17	70	1	20
1N752A	1N752A	5.32	5.6	5.88	20	11	65	1	20
1N753A	1N753A	5.89	6.2	6.51	20	7	60	0.1	20
1N754A	1N754A	6.46	6.8	7.14	20	5	55	0.1	20
1N755A	1N755A	7.13	7.5	7.88	20	6	50	0.1	20
1N756A	1N756A	7.79	8.2	8.61	20	8	45	0.1	20
1N757A	1N757A	8.65	9.1	9.56	20	10	40	0.1	20
1N758A	1N758A	9.50	10	10.5	20	17	35	0.1	20
1N759A	1N759A	11.40	12	12.6	20	30	30	0.1	20

2. TOLERANCE AND TYPE NUMBER DESIGNATION (V_Z)

The type numbers listed have a standard tolerance on the nominal zener voltage of $\pm 5\%$.

3. ZENER VOLTAGE (V_Z) MEASUREMENT

Nominal zener voltage is measured with the device junction in the thermal equilibrium at the lead temperature (T_L) at $30^\circ\text{C} \pm 1^\circ\text{C}$ and $3/8"$ lead length.

4. ZENER IMPEDANCE (Z_Z) DERIVATION

Z_{ZT} and Z_{ZK} are measured by dividing the ac voltage drop across the device by the ac current applied. The specified limits are for $I_{Z(ac)} = 0.1 I_{Z(dc)}$ with the ac frequency = 60 Hz.

5. MAXIMUM ZENER CURRENT RATINGS (I_{ZM})

Values shown are based on the JEDEC rating of 400 mW where the actual zener voltage (V_Z) is known at the operating point, the maximum zener current may be increased and is limited by the derating curve.

1N4370A Series




Figure 1. Steady State Power Derating

1N4370A Series

APPLICATION NOTE - ZENER VOLTAGE

Since the actual voltage available from a given zener diode is temperature dependent, it is necessary to determine junction temperature under any set of operating conditions in order to calculate its value. The following procedure is recommended:

Lead Temperature, T_L , should be determined from:

$$T_L = \theta_{LA} P_D + T_A$$

θ_{LA} is the lead-to-ambient thermal resistance ($^{\circ}\text{C/W}$) and P_D is the power dissipation. The value for θ_{LA} will vary and depends on the device mounting method. θ_{LA} is generally 30 to 40°C/W for the various clips and tie points in common use and for printed circuit board wiring.

The temperature of the lead can also be measured using a thermocouple placed on the lead as close as possible to the tie point. The thermal mass connected to the tie point is normally large enough so that it will not significantly respond to heat surges generated in the diode as a result of pulsed operation once steady-state conditions are achieved. Using the measured value of T_L , the junction temperature may be determined by:

$$T_J = T_L + \Delta T_{JL}$$

ΔT_{JL} is the increase in junction temperature above the lead temperature and may be found from Figure 2 for dc power:

$$\Delta T_{JL} = \theta_{JL} P_D$$

For worst-case design, using expected limits of I_Z , limits of P_D and the extremes of $T_J(\Delta T_J)$ may be estimated. Changes in voltage, V_Z , can then be found from:

$$\Delta V = \theta_{VZ} T_J$$

θ_{VZ} , the zener voltage temperature coefficient, is found from Figures 4 and 5.

Under high power-pulse operation, the zener voltage will vary with time and may also be affected significantly by the zener resistance. For best regulation, keep current excursions as low as possible.

Surge limitations are given in Figure 7. They are lower than would be expected by considering only junction temperature, as current crowding effects cause temperatures to be extremely high in small spots, resulting in device degradation should the limits of Figure 7 be exceeded.




Figure 2. Typical Thermal Resistance




Figure 3. Typical Leakage Current

1N4370A Series

TEMPERATURE COEFFICIENTS

(-55°C to +150°C temperature range; 90% of the units are in the ranges indicated.)




Figure 4a. Range for Units to 12 Volts




Figure 4b. Range for Units 12 to 100 Volts




Figure 4c. Range for Units 120 to 200 Volts




Figure 5. Effect of Zener Current




Figure 6a. Typical Capacitance 2.4-100 Volts




Figure 6b. Typical Capacitance 120-200 Volts

1N4370A Series






Figure 7a. Maximum Surge Power 1.8-91 Volts



**Figure 7b. Maximum Surge Power DO-35
100-200Volts**



**Figure 8. Effect of Zener Current on
Zener Impedance**




Figure 9. Effect of Zener Voltage on Zener Impedance




Figure 10. Typical Forward Characteristics

1N4370A Series




Figure 1. Zener Voltage versus Zener Current - V_Z = 1 thru 16 Volts




Figure 12. Zener Voltage versus Zener Current - V_Z = 15 thru 30 Volts

1N4370A Series




Figure 13. Zener Voltage versus Zener Current - V_Z = 30 thru 105 Volts




Figure 14. Zener Voltage versus Zener Current - V_Z = 110 thru 220 Volts